

# Mobile Wheel Weighing



### **LIGHTWEIGHT, PORTABLE DESIGN**

Weighing only 57 pounds (26 kg) per platform and featuring integral carrying handles, the CWL-40 axle pads are light enough for easy transport from location to location. The interlocking rubber ramps easily snap in place once you're ready to weigh!



### COMPLETE WEIGHING KIT

Cardinal Scale's CWL-40KIT contains two CWL-40 axle pads, rubber ramps, and necessary cables, plus Cardinal's 190A weight indicator with axle weighing software and P150 direct thermal ticket printer. Both the 190A indicator and P150 printer may be powered by rechargeable lithium ion batteries (optional - 190A / standard - P150). The USA-made 190A indicator features two RS232 serial ports (to connect with a printer and remote display) and the one-inchhigh backlit LCD is visible in direct sunlight and at night. The 190A's capacitive touch keys and IP69K-rated enclosure mean you'll never have to worry about inclement weather affecting the weight indicator. The P150 high-speed printer is compact and robust with a long-life printing head.

### Factoring Axle Weights

After each axle is weighed, simply press the **PRINT** key on the weight indicator to accumulate that axle's weight. Cardinal's 190A also features **traffic control auto mode** when used with a remote display with traffic lights and printer.

9:47	01-27-13
1	9740 lb
2	16320 lb
3	15980 lb
4	15880 lb
5	15700 lb
Total	73620 lb


# 8,560 lb axle 1 13,980 lb 14,560 lb axle 2 axle 3 axle 4 axle 5

### PRINT TICKETS:

- Axle Weights
- Gross Weight
- Time
- Date



- Wide Platform Size Accomodates Dual Axles
- Corrosion-Resistant, Durable Weighing Platforms
- Capable of Weighing up to 40,000-lb (18,000-kg) Axle Loads
- Low-Profile Platforms (1.7-in / 43-mm High) with Integral Handles
- Optional Rechargeable Lithium Ion Battery and Car Battery Cables





## **CWL-40 SPECIFICATIONS**

Capacity:	20,000 lb (9,000 kg) per platform or 40,000 lb (18,000 kg) for single axle
Division Size:	20 lb
Safe Overload:	150% of capacity
Output per Platform:	1.75 mV/V
Number of Load Cells:	6 each strain gauge load cells
Maximum Resolution:	1,000 divisions
Input Resistance:	750 ohms
Output Resistance:	750 ohms
Accuracy:	The greater of +/-0.3% of applied load or 1 division
Platform Size:	24.5 in L x 14 in W (62 cm L x 36 cm W) weighing surface
Overall Size:	28.5 in L x 17.5 in W x 1.7 in H (72 cm L x 45 cm W x 4 cm H) including carrying handles
Ramps:	Interlocking, slip-resistant rubber ramps measure 28.5 in L x 10 in W (72 cm L x 25 cm W) each
Deck Construction:	Aluminum
Single Axle Pad Weight:	57 lb (26 kg) per platform
Shipping Weights: CWL-40 CWL-40KIT	263 lb (119 kg) 280 lb (127 kg)
Cable Lengths: Wheel Pad to Wheel Pad Wheel Pad to Indicator	63 inches / 160 cm 50 feet / 15 m

MODELS	
CWL-40	CWL-40KIT
Includes:	Complete Kit Includes: <ul> <li>2 portable axle pad platforms</li> <li>2 sets of interlocking black rubber ramps per platform</li> <li>Wheel pad to wheel pad interface cable assembly</li> <li>Wheel pad to weight indicator interface cable assembly</li> <li>Model 190A weight indicator with axle weighing software</li> <li>Model P150 rechargeable lithium ion thermal printer</li> </ul>

Cardinal Scale reserves the right to improve, enhance or modify features and specifications without prior notice. All registered trademarks are the property of their respective owners.

# Cardinal Scale Manufacturing Co. 203 E. Daugherty, Webb City, MO 64870 USA Pb: 417-673-4631 or 800-441-4237 • Fax: 417-673-5001 www.CardinalScale.com

**SOLD BY:**