# TOSHIBA

TOSHIBA Bar Code Printer

# B-EX Series

## Key Operation Specification

# Table of Contents

# 1 SCOPE

This specification describes key operations using the keys and the LCD display of the B-EX series high-end industrial general-purpose bar code printers.

The B-EX4T1-G and B-EX4T1-T are hereinafter collectively referred to as "B-EX4T1", the B-EX4T2-G, B-EX4T2-T, B-EX4T2-H are referred to as "B-EX4T2", the B-EX6T2-G and B-EX6T2-T are referred to as "B-EX6T2", and B-EX4D2-G is referred to as "B-EX4D", respectively.

# 2 OUTLINE

Key operations are different depending on the printer mode: Online mode, in which operations are carried out through the keys and error messages are displayed while the printer is connected to the host such as a PC, and the system mode, in which self-test and setting of various parameters are performed.

This specification describes the key operation procedures with the printer keys and the LCD panel.

The names of the keys and LCD messages used in this specification are written in English

# 3 OPERATION PANEL

| | | Graphic LCD |
| --- | --- | --- |

ONLINE LED

FEED key

LEFT key

MODE key

CANCEL key

ERROR LED

PAUSE key

RESTART key

UP key

RIGHT key

ENTER key

DOWN key

1

# 4 OUTLINE OF EACH MODE

This chapter describes the outline of each mode supported by the printer. Refer to each chapter for detailed information.

## 4.1 ONLINE MODE

This mode is mainly used by users (operators).

The label or tag can be issued in the online mode. When an error occurs, the help function shows the cause of an error, troubleshooting, and recovery from the error. The threshold setting, described below, is also a part of the online mode.

### 4.1.1 Threshold setting mode

Threshold setting mode is provided to correct a print failure with pre-printed media.

When using pre-print label, detection of a print position may be disabled with the usual media sensor threshold, depending on the ink type. Such error can be prevented by setting the threshold just for the pre-printed media to be used. Since the threshold setting value is stored in the non-volatile memory, it is unnecessary to set the threshold again as long as the same pre-print media is used.

### 4.1.2 RFID calibration mode

In the RFID calibration mode, the distance to the optimum tag write/read position and AGC value required for properly writing/reading data on/from RFID tags are obtained through a calibration, the obtained values are set on the printer automatically, and they are reflected in the printer operation.

To write/read data on/from RFID tags with the bar code printer, it was necessary to manually set a distance to the write/read position and an AGC value, which controls the target tag, with @003 command and in the system mode.   These are automatically done in the RFID calibration mode.

This specification is supported from the firmware version C1.2 for the B-EX4T1-G/T-QM/CN.

### 4.1.3 Information mode

In the information mode, the total feed amount counted during feed and printing operations is displayed on the LCD or printed in units of centimeter and inch.

Printing of the feed amount is performed on request.

This specification is supported from the following firmware versions:
- B-EX4T1-G/T-QM/CN: C1.0I
- B-EX4T2-G/T-QM-CN: C1.0F

## 4.2 SYSTEM MODE

Turning the power on while holding down the both [FEED] and [PAUSE] keys, or the [MODE] key alone activates the system mode. This mode is mainly used by service persons or the Production Dept. for adjustment before shipment. The system mode contains the menus which might be changed not so frequently.

In addition to the menus common to the User System Mode, such as parameter setting, fine adjustment, and BASIC setting, there are sensor adjustment, interface, RFID and RTC setting menus.

Furthermore, self-diagnosis, test print, RAM clear to initialize the printer settings, pre-shipment adjustment for factory use, and the menu which enables saving parameter settings, external characters, TPCL commands to the external USB memory or copying the data from the USB memory to the printer are provided. The values set in this mode are stored in the non-volatile memory.

## 4.3 USER SYSTEM MODE

The user system mode is accessible from the online mode. This mode, mainly used by users (administrator) or service persons, contains the menus which might be frequently changed.

In addition to the menus common to the System Mode, such as parameter setting, fine adjustment, and BASIC setting, there are LAN/WLAN setting, auto calibration, dump function which enables the printer to dump received data.

The values set in this mode are stored in the non-volatile memory.

## 4.4 DOWNLOAD MODE

This mode is used to download boot and main programs.

## 4.5 AUTO CONFIGURATION MODE

This mode is used to update printer firmware stored in USB memory.

# 5 GENERAL VIEW OF KEY OPERATION

［Power OFF］

Power on → **Online mode**

[Online]

[FEED] key → [Feeds one label]

[PAUSE] key → [Pause]

[RESTART] key

Display
```
      (REMAIN)   0
      PAUSE
```

## Threshold setting mode

Hold down the [PAUSE] key for a few seconds.

```
SELECT PAPER SENSOR
1)REFL. (PRE-PRINT)
2)TRANS. (PRE-PRINT)
```

## RFID calibration mode    *1

Hold down the [ENTER] key for a few seconds.

```
RFID CALIBRATION


Start  ==> ENTER
Cancel ==> CANCEL
```

*1: Supported from the firmware version of C1.2 for the B-EX4T1-G/T-QM/CN.

## Information mode    *2

Hold down the [UP] key for a few seconds.

```
BCP COUNTER
123456789 cm
123456789.1 inch

PUSH ENTER OR CANCEL
```

*2: Supported from the firmware version C1.0I (B-EX4T1-G/T-QM/CN) and C1.0F (B-EX4T2-G/T-QM/CN).

## User mode

Hold down the [RESTART] or [MODE] key for a few seconds.

Hold down the [MODE] key for a few seconds.

```
USER SYSTEM MODE V1.0
<1>RESET
<2>PARAMETER SET
<3>ADJUST SET
<4>LAN/WLAN
```

<Continued on the next page.>

<Continued from the previous page.>

| Download mode |
| --- |

```
DOWNLOAD MODE
  Waiting for data...
  □□□□□
```

Turn the power on while holding down the [FEED], [RESTART] and [PAUSE] keys.

| System mode |
| --- |

```
SYSTEM MODE    V1.0
<1>DIAG.
<2>PARAMETER SET
<3>ADJUST SET
<4>TEST PRINT
```

Turn the power on while holding down the [FEED] and [PAUSE] keys at the same time or holding down the [MODE] keys.

| Auto configuration mode |
| --- |

```
USB TO PRINTER
Config file test
TOSHIBA TEC
```

Turn the power on while holding down the [CANCEL] key. (See NOTE 3)

NOTES:
1. To enter the download mode, system mode or auto configuration mode, keep holding down the key until each display is shown.
2. Power off
   When the power switch of the printer is turned off, the ONLINE and ERROR LEDs synchronously flash at a 500-ms interval (ON: 250ms, OFF: 250ms). When the LEDs are unlit, the printer power turns off.
   The power switch shall not be turned on again while these LEDs are flashing. Otherwise, "SYSTEM ERROR 02 POWER FAILURE" message will be displayed, and the LCD message may corrupt before the error message is displayed.
3. For the conditions to enter the Auto Configuration Mode, refer to Section 11.2 Preparation for USB Memory.

# 6 ONLINE MODE

## 6.1 KEY FUNCTION

The printer behavior is not guaranteed when undefined key is operated.

### 6.1.1 Online Mode Display

| Key | Function |
|---|---|
| [FEED] | (1) Feeds one piece of media.<br>Ejects one piece of media.<br>Used to adjust the media to the proper position. If printing is attempted with the media improperly positioned, printing is not performed at the proper position. One or two pieces of media need to be fed to adjust the paper position before printing.<br>(2) Prints the data in the image buffer on one piece of media according to the system mode setting.<br>**NOTE:** A Clear Command or a command for drawing shall not be sent while printing caused by a depression of the [FEED] key. If it is sent, the layout will be destroyed, and the media will not be printed properly. Also, if printing is performed by a depression of the [FEED] key while the data is being drawn in the image buffer, the layout may be destroyed.<br>* For details of the following cases, refer to the parameter setting section.<br>• How to issue the label stock having the label pitch of 25.4 mm or less in the cut issue mode when the disc cutter is used.<br>• How to issue the label stock having the minimum label pitch or less for each print speed in the cut issue mode when the rotary cutter is used.<br>* In the strip mode, feeds labels even when the peel-off sensor is detecting a label.<br>* When Media Load parameter is enabled, a media feed is performed to find the print start position depending on the condition. For details, refer to Section 8.4.1.1 MEDIA LOAD. |
| [RESTART] | (1) Resumes printing after a temporary stop of printing or after an error.<br>(2) Places the printer in the usual initial state, which is obtained when the power is turned on.<br>(3) Places the printer in the user system mode. |
| [PAUSE] | (1) Stops label printing temporarily.<br>(2) Programs the threshold value. |
| [MODE] | (1) Places the printer in the user system mode. |
| [CANCEL] | (1) Clears the job. |
| [ENTER] | (1) Displays help messages.<br>(2) Saves the log/receive buffer data. (B-EX4T1 Japan mode with firmware V1.0I only)<br>(3) Places the printer in the RFID calibration mode.<br>(Supported from the firmware version of C1.2 for B-EX4T1-G/T-QM/CN.) |
| [UP] | (1) Places the printer in the Information mode.<br>(Supported from the firmware version C1.0I for B-EX4T1-G/T-QM/CN and C1.0F for the B-EX4T2-G/T-QM/CN.) |
| [DOWN] | (1) No function. |
| [LEFT] | (1) No function. |
| [RIGHT] | (1) Displays help messages. |

### 6.1.2 Help Display

| Key | Function |
|---|---|
| [FEED] | (1) Ends help display. |
| [RESTART] | (1) Ends help display. |
| [PAUSE] | (1) Ends help display. |
| [MODE] | (1) Ends help display. |
| [CANCEL] | (1) Ends help display. |
| | (2) Returns to the previous help page. |
| | (3) Ends help display. |
| [ENTER] | (1) Ends help display. |
| | (2) Goes to the next help page. |
| | (3) Ends help display. |
| [UP] | (1) Moves the cursor upward. |
| [DOWN] | (1) Moves the cursor downward. |
| [LEFT] | (1) Returns to the previous help page. |
| | (2) Ends help display. |
| [RIGHT] | (1) Goes to the next help page. |
| | (2) Ends help display. |

### 6.1.3 Manual Threshold Setting Display

| Key | Function |
|---|---|
| [FEED] | (1) Moves the cursor upward. |
| | (2) Re-sets |
| [RESTART] | (1) Moves the cursor downward. |
| [PAUSE] | (1) Sets the threshold. |
| | (2) Fixes the selection. |
| [MODE] | No function. |
| [CANCEL] | No function. |
| [ENTER] | (1) Fixes the selection. |
| | (2) Ends manual threshold setting. |
| [UP] | (1) Moves the cursor upward. |
| [DOWN] | (1) Moves the cursor downward. |
| [LEFT] | (1) Goes to the judgment result page |
| | (2) Goes to the fine adjustment setting menu |
| [RIGHT] | (1) Goes to the detail page. |
| | (2) Goes to the fine adjustment setting menu |

## 6.2 LED FUNCTION

| [ONLINE] LED | Indicates that the printer is in online state. |
| | Flashes when the printer is communicating with the host. |
| | Flashes at a 500-msec. interval (ON: 250ms., OFF: 250ms) in synchronization with the [ERROR] LED when the printer is turned off. |
| [ERROR] LED | Indicates that the printer is in error state. |
| | Flashes when a ribbon near end condition is detected. |
| | Flashes when a system error occurs (at a 1-second interval (ON: 500 ms., OFF: 500 ms.) |
| | Flashes at a 500-msec. interval (ON: 250ms., OFF: 250ms) in synchronization with the [ONLINE] LED when the printer is turned off. |

NOTE: If the wireless LAN is being linked at power off time, both [ONLINE] and [ERROR] LEDs turn on, not flash.

## 6.3 LCD FUNCTION

The LCD displays the messages which indicate the printer status.

| LCD | Type | Graphics LCD |
| | Size | 128 dots (W) X 64 dots (H) |
| | Display structure | Maximum of 21 digits x 5 lines |

## 6.4 ONLINE MODE LCD DISPLAY

### 6.4.1 Online Mode LCD Display Example

| Printer condition | LCD Display | Display contents |
|---|---|---|

**Online**

```
B-EX4T1-T        V1.0A
        ONLINE
PRINTED         000000
IP:192.168.010.020
```

← Model name, Firmware version (*5)
← Message
← The number of labels printed (*1)
← IP address etc. (*4)
← Icon

**Pause**

```
             (TO DO) 123
        PAUSE
```

← The number of remaining labels to print (*2)
← Message
← 1st line of the error message
← 2nd line of the error message (*6)
← Icon

**Head open**

```
             (TO DO) 123
        HEAD OPEN
Close the print
head block.
                    Help ▶
```

← The number of remaining labels to print (*2)
← Message
← 1st line of the error message
← 2nd line of the error message
← Icon, Help guide (*3)

* Whether to display or hide the 1$^{st}$, 3$^{rd}$ and 4$^{th}$ lines of online mode display can be selected in the system mode.
* Refer to "Icon display" for Icon in detail.


(*1) The number of labels printed is the cumulative number of labels printed while the printer is activated.   It is reset to zero when the printer is turned on. During an issue with the cut interval specified, the number of labels is updated when the label is cut normally.

(*2) [The number of remaining labels to print] = [Specified number of labels to print] – [The number of normally printed labels before occurrence of an error or placing the printer in pause]
When the number of remaining labels to print is zero, it is not displayed. During an issue with the cut interval specified, the number of remaining labels is updated when the label is cut normally.

(*3) The help guide is displayed only when applicable help message exists.

(*4) The message displayed in this area is IP address or supplemental information like ribbon near end.

- When LAN/WLAN setting is disabled, the IP address is not displayed even if displaying IP address is enabled in the system mode.
- The ribbon near end message is displayed when a ribbon near end is detected, regardless of whether or not displaying the ribbon near end message is enabled in system mode.
  A ribbon near end is detected depending on diameter of the unused ribbon. The diameter of 38mm is equivalent to 30-meter ribbon and the diameter of 43 mm is equivalent to 70-meter ribbon, respectively.


(*5) The model name description

B-EX 4 T 1 – T

| | |
|---|---|
| Head resolution | G: 203dpi, T: 300/305dpi, H: 600dpi |
| Type | 1: Type1, 2: Type2 |
| Print method | T: Thermal transfer/Direct thermal, D: Direct thermal |
| Print width | 4: 4" width, 6: 6" width |
| Series model | |

(*6) The ribbon near end message may be displayed on this line. The condition for display is the same as *4.

### 6.4.2 Icon

Five kinds of icon are displayed in the bottom line of the online mode display.

These icons are displayed only in the online mode display.

| Icon | Explanation |
|---|---|
| Wireless LAN icon | ● Displayed and used when the wireless LAN module is mounted.<br>● The graph shows the strength of radio wave.<br><br>Y  Graph 0: Outside the communication range<br><br>Y₁  Graph 1: Strength of radio wave is weak.<br><br>Y₁₁  Graph 2: Strength of radio wave is middle<br><br>Y₁₁₁  Graph 3: Strength of radio wave is strong |
| Link icon | ● Displayed and used when the wireless LAN module is mounted.<br>● Displayed while the printer is communicating by wireless LAN.<br>● Blinks while roaming.<br><br>OFF: No connection<br><br>ON: Connecting to an access point<br><br>Blink: Roaming (*4) |
| Data transmission icon | ● Appears when a print job is present.<br><br>ON: Print job is present. |
| RFID icon | ● Displayed and used when the RFID module is mounted.<br>● Appears when a communication between the printer and the RFID module is enabled.<br>● Blinks during a communication with the RFID module.<br>- The communication includes the one without radio wave output.<br>- Blinks after radio wave output is instructed to the module even when no radio wave is output.<br>(Blinks while the module stops outputting radio wave or changing the channel under the influence of other carrier.)<br><br>RF  ON: Module type is set and ready to communicate<br><br>RF⇔  Blink: Communicating |
| Ribbon near end icon | ● Ribbon near end is detected.<br>● Blinks when the ribbon is close to the end.<br>● Ribbon near end is detected depending on the diameter of unused ribbon. ∅38 mm is equivalent to 30-meter ribbon and ∅43 mm is equivalent to 70-meter ribbon.<br><br>Blinking: Ribbon near end state (*4) |

(*4) Icon blinks at a 1-second interval (ON for 500 msec. and OFF for 500 msec.)

### 6.4.3 Online Mode Display Transition, Operation example

```
B-EX4T1-T     V1.0A
       ONLINE
PRINTED       000000
IP:192.168.010.020
```
Idling or normal issuing

When [PAUSE] key is pressed while printing:

```
             (TO DO) 123
       PAUSE
```
Printing is stopped

When [RESTART] key is pressed, the printer resumes printing if there is remaining data

If the print head is opened while printing:

```
             (TO DO) 123
       HEAD OPEN
Close the print
head block.
              Help▶
```
Help guide is displayed.

Close the print head.

Press [RIGHT] key.

```
|Feeding or printing
|was attempted with
|head block open.
◀Finish      Next ▶
```
Help guide message for head open (*1)

If the print head is opened while idling:

```
       HEAD OPEN
Close the print
head block.
```

Close the print head.

If an error occurs while printing:

```
             (TO DO) 123
       NO PAPER
Load new media.
              Help▶
```
Printing is stopped and Help guide is displayed.

Load media.
When [RESTART] key is pressed, the printer resumes printing if there is remaining data.

Press [RIGHT] key.

```
▲The media has run
|out.
|The media is not
▼set.
◀Finish      Next ▶
```
Help message for NO PAPER (*1)

(*1) Refer "HELP DISPLAY TRANSITION, OPERATION EXAMPLE" for help display.

## 6.5 HELP DISPLAY

### 6.5.1 Explanation of Help Display

When "Help" is displayed at the lower right of the online mode display, pressing [RIGHT] or [ENTER] key causes the help message to be shown.

Help message is displayed on the upper four lines. When the message exceeds four lines, the hidden lines can be displayed by scrolling down. When scrolling is possible, the up and down arrows are provided on the scrollbar on the left.

Display example:

```
Feeding or printing    ← 1st line of help message
was attempted with     ← 2nd line of help message
head block open.       ← 3rd line of help message
                       ← 4th line of help message
                       ← Help guide
◀Finish       Next ▶
```

Since the help message is within three lines, the scroll bar is not provided with up and down arrows.

```
The media has run      ← 1st line of help message
out.                   ← 2nd line of help message
The media is not       ← 3rd line of help message
set.                   ← 4th line of help message
                       ← Help guide
◀Finish       Next ▶
```

Since the help message exceeds four lines, the scroll bar is provided with the up and down arrows.

### 6.5.2 Help Display Transition, Operation Example

The help consists of three pages, which are Help1, Help2 and Help3.

Help1 shows the detail of the error, Help2 shows a troubleshooting, and Help3 shows how to recover from the error.

Display transition
[LEFT] key
[CANCEL] key

Display transition
[RIGHT] key
[ENTER] key

Online mode
```
        (TO DO) 123
      NO PAPER
Load new media.

▓▓▓▓▓      Help▶
```

Error detail
```
▲The media has run
 out.
 The media is not
▼set.
◀Finish      Next▶
```

Scroll the display with the [UP] or [DOWN] key.

Troubleshooting
```
 Load new media.
 Load the media.
 Readjust the media
 sensor level.
◀Prev        Next▶
```

Scroll the display with the [UP] or [DOWN] key.

How to recover from error
```
▲Press the RESTART
 Key to restart
 printing.
▼Adjust the media
◀Prev      Finish▶
```

Scroll the display with the [UP] or [DOWN] key.

（*5） When a key other than above is pressed, the help display is ended and returned to the online mode display.

13

## 6.6  MANUAL THRESHOLD SETTING

### 6.6.1  Outline  of  Threshold  setting

When a label stock is printed, the printer automatically corrects the print position by detecting gaps between the labels using the transmissive sensor to maintain a constant print position.   However, when a preprinted label is used, some ink may prevent proper gap detection.   In this case, it is required to manually program the transmissive sensor threshold through key operations and store the value in the non-volatile memory.

Selecting "3: Transmissive Sensor (when using the preprinted label)" for the sensor type of the Issue Command enables printing at a constant print position.

When the media with black marks printed on the back side is used, the printer automatically corrects the print position by detecting the black marks by using the reflective sensor.   However, if there is reflective rate variation at a portion other than the black mark, the print position cannot be corrected properly.   In this case, it is required to manually program the reflective sensor threshold through key operations and store the value in the non-volatile memory.

Selecting "4: Reflective Sensor (when using a manual threshold value)" for the sensor type of the Issue Command enables printing at a constant print position.

### 6.6.2 Threshold Setting Operation Example

[Online mode]
1. Normal state

```
B-EX4T1-T      V1.0A
      ONLINE
PRINTED       000000
IP:192.168.010.020
```

↓ Press [PAUSE] key

[Online mode]
2. Pause state

```
      PAUSE
```

↓ Hold down [PAUSE] key for 3 seconds

[Threshold setting]
3. Media sensor selection

```
SELECT PAPER SENSOR
1)REFL. (PRE-PRINT)
2)TRANS. (PRE-PRINT)
```

Move the cursor with the [UP] or [DOWN] key

↓ Press [ENTER] key

[Threshold setting]
4. Waiting for the media to be loaded

```
1)REFL. (PRE-PRINT)
THRESHOLD MODE
Load the media.
Press the PAUSE Key
to start the
```

Scroll the display with the [UP] or [DOWN] key

↓ Press [PAUSE] key

[Threshold setting]
5. Calibration

```
1)REFL. (PRE-PRINT)
THRESHOLD MODE

Calibrating
```

Hold down the [PAUSE] key to keep feeding the media

↓ Release [PAUSE] key.

When the [PAUSE] key is released, media feed stops

↓                    ↓

[Threshold setting]
6a. Result: OK (Mid.)

```
1)REFL. (PRE-PRINT)
Result: OK (Mid.)
---A---A--Threshold
          Baseline
Retry FEED    Detail▶
```

↓

Pressing the [FEED] key returns the display to "3. Media sensor selection."
Pressing the [ENTER] key returns the display to "2. Pause condition."
Pressing the [RIGHT] key causes the display to go to "7a/7b. Detail.

↓

[Threshold setting]
6b. Result: NG (1)

```
1)REFL. (PRE-PRINT)
Result: Failed (1)
  X____X_ Threshold
          Baseline
Retry FEED    Detail▶
```

↓ Press [RIGHT] key ↓

[Threshold setting]
7a. Detail: OK (Mid.)

```
1)REFL. (PRE-PRINT)
Peak     : 3.7V
Threshold : 2.7V
Baseline : 1.3V
◀Result    Adjust▶
```

↓

Pressing the [RIGHT] key causes the display to go to "8a. Sensor Fine adjustment."
Pressing the [LEFT] key returns the display to "6a. Judgment."

↓                    ↓

[Threshold setting]
7b. Detail: NG (1)

```
1)REFL. (PRE-PRINT)
Peak     : 2.1V
Threshold : 1.3V
Baseline : 1.2V
◀Result
```

Pressing the [LEFT] key returns the display to "6b. Judgment

↓ Press [RIGHT] key

[Threshold setting]
8a. Sensor fine adjustment

```
THRESHOLD <REFL.>

    1.0 V

( 0.0  -  4.0 V)
```

Operation is same as 8.5.9 reflective sensor fine adjustment

Pressing the [PAUSE], [ENTER] or [CANCEL] key returns the display to "6a. Judgment

15

Judgment result

| Display example | Displayed item | Explanation |
|---|---|---|
| 1)REFL. (PRE-PRINT)<br>Result: OK (Mid.)<br>---A---A--Threshold.<br>Baseline<br>Retry FEED　Detail▶ | • Sensor type<br>• Result (Text)<br>• Result (Graph)<br>• Key operation guide | The calibration result is shown. |
| | | Pressing the [FEED] key returns the display to the media sensor selection and enables a threshold setting. |
| | | Pressing the [RIGHT] key shows the measured voltages. |
| | | Pressing the [ENTER] key terminates the threshold setting. |
| 1)REFL. (PRE-PRINT)<br>Result: OK (Mid.)<br>---A---A--Threshold.<br>Baseline<br>◀Adjust　Detail▶ | • Sensor type<br>• Result (Text)<br>• Result (Graph)<br>• Key operation guide | The result of fine adjusted threshold setting is shown. |
| | | Pressing the [LEFT] key returns the display to the threshold fine adjustment. |
| | | The [RIGHT] and [ENTER] keys function in the same way as above. |

The threshold setting result is indicated with one of the following icon types.

| No. | Display example | Icon name | Explanation |
|---|---|---|---|
| 1 | ---A---A--Threshold.<br>Baseline | OK (Mid.) | Print position is detectable with the media sensor. Threshold is at the midpoint between the peak and the baseline. |
| 2 | ---A---A-Threshold<br>Baseline | OK (High) | Threshold is near the peak voltage, so detection of a gap/black mark may fail if the voltage difference is very small. (Adjusting the threshold to the midpoint between the peak and the baseline enables more accurate detection.) |
| 3 | --A---A_Threshold_<br>Baseline | OK (Low) | Threshold is near the baseline voltage, so detection of a gap/black mark may fail if the voltage difference is very small. (Adjusting the threshold to the midpoint between the peak and the baseline enables more accurate detection.) |
| 4 | ---X---X_Threshold<br>Baseline | NG (1) | Print position is not detectable with the media sensor. Sensor adjustment is necessary. |
| 5 | ---X---X_Baseline<br>Threshold | NG (1) | Print position is not detectable with the media sensor. Sensor adjustment is necessary.<br>(Threshold ≤ Baseline) |
| 6 | --A---A_Baseline<br>Threshold | NG (2) | Print position is not detectable with the media sensor.<br>(Calibration may enable print position detection, but it is very difficult.) |

Detailed display

| Display example | Displayed item | Explanation |
|---|---|---|
| 1)REFL. (PRE-PRINT)<br>Peak      : 3.7V<br>Threshold : 2.7V<br>Baseline  : 1.3V<br>◀Result      Adjust▶ | • Sensor type<br>• Peak value<br>• Threshold voltage<br>• Baseline voltage<br>• Key operation guide | The calibration result and the threshold voltage are displayed.<br>Pressing the [RIGHT] key enables setting a threshold fine adjustment value.<br>Pressing the [LEFT] key returns the display to the calibration result display. |

(Supplementary Explanation)

(1) When the [PAUSE] key is released within 3 seconds while the printer is paused, the [PAUSE] key is invalid.

(2) To program the threshold, 1.5 pieces or more label shall be fed.   (If the label feed amount is insufficient, the threshold may not be properly programmed.   In this case, the threshold setting is required again.)

(3) While the head is lifted, the [PAUSE] key is invalid even if the [PAUSE] key is held down for 3 seconds or more.

(4) When the proper print position is not obtained even after threshold setting, the sensor may be improperly adjusted.   In this case, readjust the sensor in system mode, and program the threshold.

When the backing paper of the label is too thick, the transmissive sensor needs to be readjusted.

In addition, make sure that "3: Transmissive sensor (when using the preprinted label)" or "4: Reflective sensor (when using a manual threshold value)" is selected for sensor type of the Feed Command and the Issue Command.

(5) Paper end and ribbon end are not detectable during the threshold setting. (The setting continues as long as the [PAUSE] key is held down even if the printer runs short of media or ribbon.)

(6) The detailed display is shown when the [RIGHT] key is pressed while the result is displayed. The measured sensor level and the currently programmed threshold fine adjustment value can be checked.

Fine adjustment value = Peak voltage – Threshold voltage

(7) Pressing the [LEFT] key returns the detailed display to the result display. Pressing the [RIGHT] key causes the display to go to threshold fine adjustment screen.   This is the same menu with the threshold fine adjustment menu in section 8.5.9 (Reflective sensor) or 8.5.10 (Transmissive sensor).

(8) After setting the threshold fine adjustment value, the screen returns to the result display.

(9) While the result of fine adjusted threshold setting is shown, pressing the [LEFT] key returns the display to the threshold fine adjustment screen and pressing the [RIGHT] key goes to the detailed display.

(10) During threshold setting, the media is fed at the same speed with that for the previous issue.

(11) Whether the threshold setting succeeded or not can be checked with either of the following methods.

■ Media feed with the [FEED] key
1. While the judgment result is displayed, press the [FEED] key to terminate the threshold setting.
   → The printer is placed in the pause state.

2. Press the [RESTART] key to clear the pause state.
   → The printer is placed in the online state.

3. Hold down the [MODE] key.
   → The printer enters the user system mode.

4. Select "<2>PARAMETER SET", "Software Set", then "THRESHOLD SELECT" with the [UP], [DOWN] and [ENTER] keys.

5. Select the applicable media sensor type ("REFLECT" or "TRANS.") and press the [ENTER] key.
   → The selected sensor type display is shown.

6. Select "MANUAL SET", press the [ENTER] key, then [MODE] key.
   → User system mode menu is displayed.

7.  Select "<1> RESET" and press the [ENTER] key.
    → After the printer is reset, it is placed in the online mode.

8.  Press the [FEED] key to feed the media.
    → If a paper jam occurs or the media does not stop at the print start position, retry the threshold setting.


■ Sending Issue command

1.  Press the [FEED] key while the judgment result is displayed to terminate the threshold setting.
    → The printer is placed in the pause state.

2.  Press the [RESTART] key to clear the pause state.
    → The printer is placed in the online state.

3.  Hold down the [MODE] key.
    → The printer enters the user system mode.

4.  Select "<2>PARAMETER SET", "Software Set", then "THRESHOLD SELECT" with the [UP], [DOWN] and [ENTER] keys.

5.  Select the media sensor type ("REFLECT" or "TRANS.") depending on the sensor type specified by the Issue Command, and press the [ENTER] key.

| Sensor type in Issue Command | Setting |
|---|---|
| 0: No sensor | Whether the threshold setting succeeded or not cannot be checked. |
| 1: Reflective sensor | Select "REFLECT". When the selected sensor type display is shown, select "MANUAL SET" and press the [ENTER] key. * Select the media sensor type to the one for which the threshold was set. |
| 2: Transmissive sensor (when using normal labels) | Select "TRANS." When the selected sensor type display is shown, select "MANUAL SET" and press the [ENTER] key. * Select the media sensor type to the one for which the threshold was set. |
| 3: Transmissive sensor (when using preprinted labels) | No setting is necessary. |
| 4: Reflective sensor (when using a manual threshold value) | No setting is necessary. |

6.  Press the [MODE] key.
    → User system mode menu is displayed.

7.  Select "<1> RESET" and press the [ENTER] key.
    → After the printer is reset, it is placed in the online mode.

8.  Send an Issue Command to make the printer print.
    → If a paper jam occurs or the media does not stop at the print start position, retry the threshold setting.

## 6.7 RFID CALIBRATION

* Supported from the firmware version of C1.2 for the B-EX4T1-G/T-QM/CN.

The supported RFID tag types are the following three, which are used at Decathlon.  The others are unusable.

**UPM Web for Store**



**UPM Web for Warehouse**



**IER for Warehouse**

### 6.7.1 Outline of the RFID Calibration

The RFID calibration is a function to automatically determine the distance to the optimum write/read position and AGC value required for properly writing/reading data on/from RFID tags.

When the result of an RFID calibration is saved (by pressing the [ENTER] key) while the detected values are shown on the screen, the value obtained through the RFID calibration is set for the CALIB. AGC and CALIB. POSITION parameters in the system mode and the CALIB. MODE is turned on automatically.

NOTES:

1. Note that the optimum write/read positions and AGC value obtained through RFID calibration do not guarantee a perfect write/read, so they should be used as a guide.
2. Prior to an RFID calibration, be sure to perform an automatic calibration (<7>AUTO CALIB. in the user system mode) to place the media at the print start position.
3. If an RFID calibration is performed without placing the media at the print start position, an improper value may be set, which may cause an error message, "RFID WRITE ERROR", to be shown during writing/reading data or data to be written on/read from a wrong tag.
4. If an error message, "RFID WRITE ERROR", often appears while writing/reading data on/from RFID tags with CALIB. MODE parameter enabled, perform an automatic calibration (<7>AUTO CALIB. in the user system mode) or change the setting value for the POWER LEVEL parameter in the system mode, then perform an RFID calibration again.
5. If an RFID calibration is performed while the actual antenna position is different from that set for the ANTENNA POSITION parameter in the system mode, an improper value may be set, which may cause an error message, "RFID WRITE ERROR", to be shown during writing/reading data or data to be written on/read from a wrong tag.

| Actual antenna position | | Antenna position set in the system mode |
|---|---|---|
| Rotation of antenna | Wave director position | |
| 0° | 0 mm | FRONT |
| 0° | 9 mm | CENTER |
| 180° | 12 mm | REAR |

## 6.7.2 RFID Calibration Operation Example

NOTE: Be sure to place the RFID media at the print start position in advance by performing an automatic calibration (<7>AUTO. CALIB.).

[Online mode]
1. Normal state

```
B-EX4T1-T        V1.0A
       ONLINE
PRINTED       000000
IP:192.168.010.020
▐▌⚡⚙RFI▐▌
```

↓ Press [PAUSE] key.

[Online mode]
2. Pause state

```
        PAUSE



▐▌⚡⚙RFI▐▌
```

↓ Hold down [ENTER] key for 3 seconds.

[RFID Calibration]
3. Calibration start

```
RFID CALIBRATION



Start  ==> ENTER
Cancel ==> CANCEL
```

Press [CANCEL] key to return to the normal state.

↓ Press [ENTER] key.

[RFID Calibration]
4. Calibration is being performed.

```
RFID CALIBRATION

Calibrating...
```

↓

[RFID Calibration]
5a. Result: Detected.

```
RFID CALIBRATION

POSITION    +031.0 mm
AGC           4
Set    ==> ENTER
Cancel ==> CANCEL
```

Pressing the [ENTER] key returns the display to 1. Normal state.
The value of "POSITION" is set for "CALIB. POSITION", the value of "AGC" is set for "CALIB. AGC", and "CALIB. MODE" is turned ON.

Pressing the [CANCEL] key returns the display to 1. Normal state.
Values of "POSITION" and "AGC" on the display are not saved.

[RFID Calibration]
5a. Result: Not found.

```
RFID CALIBRATION

POSITION      NOT FOUND
AGC           NOT FOUND

Cancel ==> CANCEL
```

Pressing the [CANCEL] key returns the display to 1.
No value is saved.

(Supplementary Explanation)

(1) The position and AGC value obtained through an RFID calibration are calibrated with reference to the media at the print start position.

(2) When the [ENTER] key is released within 3 seconds while the printer is paused, the [ENTER] key is invalid.

(3) After performing an RFID calibration, the printer returns the RFID media to the print start position.

(4) An RFID calibration is enabled when the FORWARD WAIT parameter is set to ON.   In this case, the printer feeds the RFID media to the print start position temporarily, performs an RFID calibration, then returns the media to the former position.

(5) If an engine-related error (such as print head open, paper end, ribbon end, and ribbon near end) occurs during an RFID calibration, the printer stops at the moment the error occurs. Therefore, the media dos not return to the print start position (or the forwarded position in the case the FORWARD WAIT parameter is ON.)   In this case, the LCD will show the display of 5a. Result Not detected.

(6) An RFID calibration is inoperable in the strip mode.

(7) Do not send a command to the printer while an RFID calibration is being performed.   If a command is sent during an RFID calibration, printer operation is not guaranteed.

## 6.8 INFORMATION MODE

### 6.8.1 Outline of the Information Mode

In the information mode, the total feed amount counted during feed and printing operations is displayed on the LCD, and printed in units of centimeter and inch on request.

The feed amount is counted at the end of feed or printing, and saved in the non-volatile memory.

NOTES:

1. The effective range of the feed amount[*1] is as follows. When the feed amount exceeds the maximum, the maximum value will be saved.

    In unit of centimeter:  0 to 320000000
    In unit of inch:        0.0 to 125984251.9

2. In the following cases, feed or printing is not counted in this feed amount[*1].
   Reverse feed, Forward feed to the strip position, Pre-strip feed, Auto forward feed, Void printing on RFID media, RFID tag position adjustment command (@003 command), Pre-reverse feed when an expansion I/O device is connected, Printing in offline (Diag. test print, maintenance counter print, test print, dump), printing in the information mode, manual threshold, automatic calibration, and RFID calibration

3. Since the feed amount[*1] is counted based on the label pitch specified by the command, a large margin of error may be generated if the command-specified label pitch differs from the actually-measured label pitch.

4. Since the counted feed amount is saved in the non-volatile memory (EEPROM), replacement of the EEPROM is prohibited. (Except for the case the Main PC board is replaced with a service part.)

     (*1): Feed amount counted in the information mode

### 6.8.2 Information Mode Operation Example

[Online mode]
1. Normal state

```
B-EX4T1-T          V1.0A
       ONLINE
PRINTED         000000
IP:192.168.010.020
```

↓ Press [PAUSE] key.

[Online mode]
2. Pause state

```
        PAUSE
```

↓ Hold down [UP] key for 3 seconds.

[Information mode]
3. Feed amount is displayed.

```
BCP COUNTER
123456789 cm
123456789.1 inch

PUSH ENTER OR CANCEL
```

Press [CANCEL] key to return to 1. Normal state.

↓ Press [ENTER] key.

[Information mode]
4. Printing is performed.

```
B-EX4T1-T          V1.0A
       ONLINE
PRINTED         000000
IP:192.168.010.020
```

After printing is finished, the display returns to 1. Normal state.


(Supplementary Explanation)

(1)  When printing is performed in this mode, a quick reset is performed.

Performing a quick reset causes the print count (number of labels issued) to be reset to zero and the image buffer to be cleared.   When the automatic calibration is enabled, a calibration is performed after the quick reset.

When the automatic call at power on parameter is enabled in the Saved data call command, saved data will be called after a quick reset.

(2)  Previous print conditions are applied to the printing performed in this mode, except:

Printing direction

When the mirror printing has been specified, only the mirror printing is not performed. Therefore, the bottom first mirror printing and top first mirror printing will be changed to bottom first printing and top first printing, respectively.

Effective print width and X-coordinate fine adjustment

TYPE1:   When the feed amount reaches the max. number of digits, the print position is centered.

TYPE 2:  When the feed amount reaches the max. number of digits, the print position is left-aligned with a 25-mm left margin.

(3)  Before shifting to the Information mode, make sure that the printer has not received any commands related to feed or drawing.   If the printer has received such commands, printing will not be performed and the printer will return to the normal state.   At this time, a quick reset will not be performed.

(4)  Do not send a command to the printer in the information mode.

## 6.8.3 Information Mode Print Sample

<Print sample>

TYPE1:

```
                320000000cm
                125984251.9"
```

TYPE2:

```
320000000cm
125984251.9"
```

<Print data>

| Item | Information | Range |
|------|-------------|-------|
| 1st line | Feed amount in the information mode (Unit: cm) | 0 to 320000000 |
| 2nd line | Feed amount in the information mode (Unit: inch) | 0 to 125984251.9 |

## 6.9 JOB CANCELLATION

### 6.9.1 Outline of the Job Cancellation

The [CANCEL] key enables cancellation of subsequent print jobs.

Holding down the [CANCEL] key for 3 seconds while the printer is in an error* or pause state causes the printer to start a quick reset and shift to the online mode.

As long as the [CANCEL] key is held down, the data in the receive buffer is all discarded.

Job cancellation is finished when the [CANCEL] key is released, and the printer restores to the normal condition.

*: Errors which can be recovered by a depression of the [RESTART] key.
   For details, refer to Section 6.8 LCD MESSAGES AND LED INDICATIONS.

*: A command error may occur if the [CANCEL] key is released before the all received data has been discarded.

### 6.9.2 Job Cancellation Operation Example

[Online mode]
1. Normal condition

```
B-EX4T1-T      V1.0A
       ONLINE
PRINTED        000000
```

↓ Occurrence of an error of depression of the [PAUSE] key.

[Online mode]
2. Pause or error condition

```
     PAPER JAM
A media feed error
occurred.
              Help▶
```

```
       PAUSE
```

↓ Hold down [PAUSE] key for 3 seconds.

[Online mode]
3. Job cancellation after quick reset

```
B-EX4T1-T      V1.0A
       ONLINE
PRINTED        000000
```

As long as the [CANCEL] key is held down, received data is discarded.

↓ Release the [CANCEL] key.

[Online mode]
4. Normal condition

```
B-EX4T1-T      V1.0A
       ONLINE
PRINTED        000000
```

The printer restores to the online mode.

25

## 6.10 Saving Log/Receive Buffer Data

### 6.10.1 Outline of Log Data Save

When the [ENTER] key is held down for 3 seconds while the printer is in online or pause, the printer automatically save the print log and restart.

### 6.10.2 Conditions

#### 6.10.2.1 Model

B-EX4T Type1 JP model with firmware V1.0I only

#### 6.10.2.2 Option

- The RFID module must not installed.
- The expansion I/O board must be installed.
- A USB memory must be fitted.

#### 6.10.2.3 Mode

To save the print log, the printer must be in the online or pause state.

### 6.10.3 Data to be Saved

#### 6.10.3.1 Data type

Data to be saved is print logs and receive buffer data.   Both are the same with those described in Section 9.10 LOG and 9.9 Dump Mode.

#### 6.10.3.2 The number of files to be saved

Up to 10 files can be saved each.
When the number of files exceed 10, the latest file will be erased.

#### 6.10.3.3 Storage location and file name

Unlike those described in Section 9.10 LOG and 9.9 Dump Mode, the files are saved in "/ATA0/LOGDATA/" direction under the following name:

    Log file:              LOG00001.TXT to LOG00010.TXT
    Receive buffer data:   LOG00001.BIN to LOG00010.BIN

### 6.10.4 Time Required

It takes about 9 seconds for the printer to restore to the online state after it starts saving.

### 6.10.5 Log Save Operation Example

[Online mode]
[Pause mode]
1. Normal condition

```
B-EX4T1-T        V1.01
      ONLINE
PRINTED       000000
```

```
        PAUSE
```

↓ Hold down the [ENTER] key for 3 seconds.

[Log save mode]
Log files are saved.
(Nothing happens to
the LCD.)

```
B-EX4T1-T        V1.01
      ONLINE
PRINTED       000000
```

```
        PAUSE
```

↓ The log file has been saved.

After saving the log
file, the printer
restarts.

```
B-EX Series
   Initializing...
```

After saving the log file, the printer automatically restarts.    Release the [ENTER] key at this timing.

27

## 6.11 LCD MESSAGES AND LED INDICATIONS

| No | LCD Message 2nd line (English) | LED indications | | Printer status | Restoration by the [RESTART] key Yes/No | Acceptance of Status Request and Reset Command Yes/No |
|---|---|---|---|---|---|---|
| | | ON LINE | ERROR | | | |
| 1 | ONLINE | ○ | ● | In the online mode | ― | Yes |
| 1 | ONLINE | ◉ | ● | In the online mode (Communicating) | ― | Yes |
| 2 | HEAD OPEN | ● | ● | A feed or an issue was attempted with the head opened. | ― | Yes |
| 3 | PAUSE | ● | ● | In a pause state | Yes | Yes |
| 4 | COMMS ERROR | ● | ○ | A parity error or framing error has occurred during communication by RS-232C. | Yes | Yes |
| 5 | PAPER JAM | ● | ○ | A paper jam occurred during paper feed. Paper was not set properly. Label actually used and the selected media sensor type do not match. The media sensor position does not align with the black mark position. The actual media size and the specified media length do not match. The level of media sensor is not suitable for the actual media. The gap of label cannot be detected due to pre-printing. | Yes | Yes |
| 6 | CUTTER ERROR | ● | ○ | A paper jam occurred in the cutter. The cutter did not move from the home position. The cutter cover was open. | Yes | Yes |
| 7 | NO PAPER | ● | ○ | The media has run out. The media has not been set. Media sensor level is not suitable for the paper used. | Yes | Yes |
| 8 | NO RIBBON | ● | ○ | The ribbon has run out. | Yes | Yes |
| 9 | HEAD OPEN | ● | ○ | A feed or an issue was attempted with the head opened. (Except media feed caused by the [FEED] key or Expansion I/O) | Yes | Yes |
| 10 | HEAD ERROR | ● | ○ | A broken dot error has occurred in the thermal head. The error has occurred in the head driver. | Yes | Yes |
| 11 | EXCESS HEAD TEMP | ● | ○ | The thermal head temperature has become excessively high. | No | Yes |
| 12 | RIBBON ERROR | ● | ○ | An abnormal condition occurred with the sensor for determining the torque of the ribbon motor. A ribbon jam occurred. The ribbon has been torn. The ribbon has not been set. | Yes | Yes |
| 13 | REWIND FULL | ● | ○ | An overflow error has occurred in the rewinder unit. | Yes | Yes |
| 14 | SAVING ####KB/&&&&KB or | ○ | ● | Writable characters or PC command save mode. | ― | Yes |

| | | | | | | |
|---|---|:-:|:-:|---|:-:|:-:|
| | SAVING %,%%%.%%%KB | | | | | |
| 15 | FORMAT ####KB/&&&&KB or FORMAT %,%%%.%%%KB | ○ | ● | Initializing the storage area. | ― | Yes |
| 16 | NOW LOADING… | ○ | ● | Downloading TrueType font or BASIC program | ― | Yes |
| 17 | MEMORY WRITE ERR. | ● | ○ | An error has occurred while writing data into the memory for storage. (USB memory, flash ROM on the CPU board) | No | Yes |
| 18 | FORMAT ERROR | ● | ○ | An erase error has occurred while formatting the memory for storage (USB memory, flash Rom on the CPU board) | No | Yes |
| 19 | MEMORY FULL | ● | ○ | Saving failed because of the insufficient capacity of the memory for storage (USB memory, flash ROM on the CPU board) | No | Yes |
| 20 | SYNTAX ERROR Command error (Refer *1, *2) | ● | ○ | A command error has occurred while analyzing the command. | Yes | Yes |
| 21 | POWER FAILURE | ● | ○ | A momentary power interruption has occurred. (The LCD message may corrupt before the error message is displayed.) | No | No |
| 22 | EEPROM ERROR | ● | ○ | A backup EEPROM cannot be read/write pr. | No | No |
| 23 | SYSTEM ERROR | ● | ○ | When any abnormal operations as below are performed, a system error occurs. (a) Command fetch from an odd address (b) Access to the word data from a place other than the boundary of the word data (c) Access to the long word data from a place other than the boundary of the long word data (d) Access to the area of 80000000H to FFFFFFFFH in the logic space in the user system mode. (e) Undefined command placed in other than the delay slot has been decoded. (f) Undefined command in the delay slot has been decoded. (g) Command to rewrite the delay slot has been decoded. | No | No |
| 24 | DHCP CLIENT INIT… | ● | ● | Initializing DHCP CLIENT. * Only when DHCP is enabled | ― | ― |
| 25 | RFID WRITE ERROR | ● | ○ | The printer did not succeed in writing data onto the RFID tag after having retried for the specified times. | Yes | Yes |
| 26 | RFID ERROR | ● | ○ | The printer cannot communicate with the RFID module. | No | Yes |

| 27 | INPUT PASSWORD | ● | ● | The printer is waiting for a password to be entered. | No | No |
|---|---|---|---|---|---|---|
| 28 | PASSWORD INVALID | ● | ● | A wrong password was entered consecutively for three times. | No | No |
| 29 | RFID CONFIG ERR | ● | ○ | B-EX700-RFID-U2-EU/US-R, B-EX700-RFID-U4-EU/US-R, U4 module preinstall model only RFID module's destination code is not specified. | No | No |
| 30 | LOW BATTERY (Refer to *4,5) | ● | ○ | RTC battery is low. | No | Yes |
| 31 | INTERNAL COM ERR | ● | ● | A hardware error has occurred in the internal serial interface. | No | No |

Explanation of symbols

| Symbol | Explanation | Range |
|---|---|---|
| ○: | ON | — |
| ⊙: | Blinking | — |
| ●: | OFF | — |
| %%,%%%,%%%: | Remaining memory size of the external USB memory | 0 to 09,999,999 (Kbyte) |
| ####: | Remaining memory size for PC command storage area in the internal memory | 0 to 3072 (Kbyte) |
| &&&&: | Remaining memory size for writable character storage area | 0 to 3147 (Kbyte) |

(*1) When there is command error in received command, up to 42 bytes of error command, starting from the command code, are shown on 3<sup>rd</sup> and 4<sup>th</sup> lines of the LCD.

(*1) When there is command error in received command, up to 42 bytes of error command, starting from the command code, are shown on 3rd and 4th lines of the LCD.
(However, [LF] and [NUL] are not displayed. Also, 43rd bytes and later are not displayed.)

Display example

```
        (TO DO)     0
     SYNTAX ERROR
{D1544,1042,1524|}{C
|}{PC000;0025,B=AC
Tıl凶昌囲卹        Help▶
```

(Example 1)
  [ESC] PC001;0**A**00,0300,2,2,A,00,B [LF][NUL]
        └──── Command error

    LCD Display

| Command error |
| --- |
| PC001;0A00,0300,2,2,A |
| ,00,B |

(Example 2)
  [ESC]T20**G**30[LF][NUL]
      └──── Command error

    LCD Display

| Command Error |
| --- |
| T20G30 |

(Example 3)
  [ESC] PC002;0100,0300,15,15,A,00,00,J0101,+000000000**A**,Z10,P1[LF][NUL]
                         └──── Command error

    LCD display

| Command error |
| --- |
| PC002;0100,0300,15,15 |
| ,A,00,00,J0101,+00000 |

(*2) When a command error is displayed, the code other than 20H - 7FH and A0H - DFH is displayed as "?" (3FH).

(*3) When the ribbon near end detection is enabled, the error LED blinks at a 1-second interval (ON for 500 msec. OFF for 500 msec.) while the printer is in a ribbon near end state and displays message number 1, 2 or 3.

(*4) The battery check does not work when the printer is being reset and the RTC is not mounted.

(*5) It is necessary to follow the procedure below to use RTC function under a low battery condition.
 Turn off the printer power while the printer is in an error state. Start the printer in the system mode, set the date and time for the RTC again, then reset the printer to place the printer in online state.
 * The printer can print the programmed date and time until it is turned off.

LCD message (2$^{nd}$ line)

| No | English |
|---|---|
| 1 | ONLINE |
| 2 | HEAD OPEN |
| 3 | PAUSE |
| 4 | COMMS ERROR |
| 5 | PAPER JAM |
| 6 | CUTTER ERROR |
| 7 | NO PAPER |
| 8 | NO RIBBON |
| 9 | HEAD OPEN |
| 10 | HEAD ERROR |
| 11 | EXCESS HEAD TEMP |
| 12 | RIBBON ERROR |
| 13 | REWIND FULL |
| 14 | SAVING   ####KB/&&&&KB<br>SAVING     %%,%%%,%%%KB |
| 15 | FORMAT   ####KB/&&&&KB<br>FORMAT     %%,%%%,%%%KB |
| 16 | NOW LOADING… |
| 17 | SETTING MODE |
| 18 | MEMORY WRITE ERR. |
| 19 | FORMAT ERROR |
| 20 | MEMORY FULL |
| 21 | SYNTAX ERROR |
| 22 | POWER FAILURE |
| 23 | EEPROM ERROR |
| 24 | SYSTEM ERROR |
| 25 | DHCP CLIENT INIT… |
| 26 | RFID WRITE ERROR |
| 27 | RFID ERROR |
| 28 | INPUT PASSWORD |
| 29 | PASSWORD INVALID |
| 30 | RFID CONFIG ERR |
| 31 | LOW BATTERY |
| 32 | INTERNAL COM ERR |

| No | German |
|---|---|
| 1 | ONLINE |
| 2 | Kopf offen. |
| 3 | PAUSE |
| 4 | Kommunikations-Fehler |
| 5 | PAPIERSTAU |
| 6 | Messer Fehler |
| 7 | Kein Papier. |
| 8 | KEIN FARBBAND |
| 9 | Kopf offen. |
| 10 | Kopf Fehler |
| 11 | Kopftemp. zu hoch |
| 12 | FARBBAND FEHLER |
| 13 | AUFWICKLER VOLL |
| 14 | SAVING   ####KB/&&&&KB<br>SAVING     %%,%%%,%%%KB |
| 15 | FORMAT   ####KB/&&&&KB<br>FORMAT     %%,%%%,%%%KB |
| 16 | NOW LOADING... |
| 17 | SETTING MODE |
| 18 | MEMORY WRITE ERROR |
| 19 | FORMAT ERROR |
| 20 | Speicher voll |
| 21 | SYNTAX ERROR |
| 22 | POWER FAILURE |
| 23 | EEPROM Fehler |
| 24 | SYSTEM ERROR |
| 25 | DHCP CLIENT INIT... |
| 26 | RFID WRITE ERROR |
| 27 | RFID FEHLER |
| 28 | INPUT PASSWORD |
| 29 | PASSWORT ungültig |
| 30 | RFID CONFIG Error |
| 31 | Batterie schwach |
| 32 | INTERNAL COMM ERROR |

| No | French |
|---|---|
| 1 | PRETE |
| 2 | TÊTE OUVERTE |
| 3 | PAUSE |
| 4 | ERREURS DE COMMUNICAT |
| 5 | BOURRAGE PAPIER |
| 6 | ERREUR MASSICOT |
| 7 | PAS DE PAPIER |
| 8 | PAS DE RUBAN |
| 9 | TÊTE OUVERTE |
| 10 | ERREUR DE TÊTE |
| 11 | TETE TROP CHAUDE |
| 12 | ERREUR RUBAN |
| 13 | REENROULEUR PLEIN |
| 14 | SAUVE   ####KB/&&&&KB<br>SAUVE     %%,%%%,%%%KB |
| 15 | FORMAT   ####KB/&&&&KB<br>FORMAT     %%,%%%,%%%KB |
| 16 | CHARGEMENT ... |
| 17 | MODE REGLAGES |
| 18 | ERR. ECRITURE MÉMOIRE |
| 19 | ERREUR DE FORMAT |
| 20 | MÉMOIRE PLEINE |
| 21 | ERREUR DE SYNTAXE |
| 22 | ERREUR D'ALIMENTATION |
| 23 | ERREUR EEPROM |
| 24 | ERREUR SYSTÈME |
| 25 | INIT CLIENT DHCP ... |
| 26 | ERREUR ECRITURE RFID |
| 27 | ERREUR RFID |
| 28 | INPUT PASSWORD |
| 29 | MOT DE PASSE INVALIDE |
| 30 | ERREUR CONFIG. RFID |
| 31 | BATTERIE FAIBLE |
| 32 | ERREUR COMM. INT. |

| No | Dutch | | No | Spanish | | No | Japanese |
|---|---|---|---|---|---|---|---|
| 1 | IN LIJN | | 1 | PREPARADA | | 1 | |
| 2 | PRINTKOP OPEN. | | 2 | CABEZAL ABIERTO | | 2 | |
| 3 | PAUZE | | 3 | PAUSA | | 3 | |
| 4 | COMMUNICATIE FOUT | | 4 | ERROR DE COMUNICACION | | 4 | |
| 5 | PAPIER STORING. | | 5 | ATASCO DE PAPEL | | 5 | |
| 6 | FOUT SNIJMES | | 6 | ERROR DE CORTADOR | | 6 | |
| 7 | GEEN PAPIER | | 7 | SIN PAPEL | | 7 | |
| 8 | GEEN LINT | | 8 | SIN CINTA | | 8 | |
| 9 | PRINTKOP OPEN. | | 9 | CABEZAL ABIERTO | | 9 | |
| 10 | FOUT PRINTKOP | | 10 | ERROR DE CABEZAL | | 10 | |
| 11 | PRINTKOP OVERHIT. | | 11 | EXCESO TEMP. CABEZAL | | 11 | |
| 12 | LINT FOUT | | 12 | ERROR DE CINTA | | 12 | |
| 13 | OPROLEENHEID VOL | | 13 | REBOBINADOR LLENO | | 13 | |
| 14 | OPSLAAN ####KB/&&&&KB<br>OPSLAAN %%,%%%,%%%KB | | 14 | SALVAR ####KB/&&&&KB<br>SALVAR %%,%%%,%%%KB | | 14 | |
| 15 | FORMAT ####KB/&&&&KB<br>FORMAT %%,%%%,%%%KB | | 15 | FORMATO ####KB/&&&&KB<br>FORMATO %%,%%%,%%%KB | | 15 | |
| 16 | LADEN . . . | | 16 | CARGANDO... | | 16 | |
| 17 | INSTELMODUS | | 17 | MODO CONFIG. | | 17 | |
| 18 | MEM SCHRIJF FOUT | | 18 | ERROR DE ESCRITURA | | 18 | |
| 19 | FORMAT FOUT | | 19 | ERROR DE FORMATO | | 19 | |
| 20 | GEHEUGEN VOL | | 20 | MEMORIA LLENA | | 20 | |
| 21 | SYNTAX FOUT | | 21 | ERROR DE SINTAXIS | | 21 | |
| 22 | VOEDING FOUT | | 22 | FALLO DE ALIMENTACION | | 22 | |
| 23 | FOUT EEPROM | | 23 | ERROR EN LA EEPROM | | 23 | |
| 24 | SYSTEEM FOUT. | | 24 | ERROR DE SISTEMA | | 24 | |
| 25 | INIT CLIENT DHCP | | 25 | INIC. CLIENTE DHCP... | | 25 | |
| 26 | SCHRIJFFOUT RFID | | 26 | ERROR ESCRITURA RFID | | 26 | |
| 27 | RFID FOUT | | 27 | ERROR EN RFID | | 27 | |
| 28 | INPUT PASSWORD | | 28 | INPUT PASSWORD | | 28 | |
| 29 | ONGELDIG PASWOORD | | 29 | CONTRASEÑA NO VALIDA | | 29 | |
| 30 | RFID CONFIG. FOUT | | 30 | ERROR DE CONFIG. RFID | | 30 | |
| 31 | LAGE BATTERIJ. | | 31 | BATERIA BAJA | | 31 | |
| 32 | INTERNE COMM. FOUT | | 32 | ERR INTERNO COMUNIC. | | 32 | |

| No | Italian | | No | Portuguese | | No | Chinese |
|---|---|---|---|---|---|---|---|
| 1 | On Line | | 1 | PREPARADA | | 1 | ONLINE |
| 2 | Testina Aperta | | 2 | CABECA ABERTA | | 2 | 打印头打开 |
| 3 | PAUSA | | 3 | PAUSA | | 3 | 暂停 |
| 4 | Errore Seriale | | 4 | ERRO DE COMUNICACAO | | 4 | 通讯错误 |
| 5 | Carta inceppata | | 5 | PAPEL ENCRAVADO | | 5 | 卡纸 |
| 6 | Errore Taglierina | | 6 | ERRO DE CORTADOR | | 6 | 切刀错误 |
| 7 | Manca Carta | | 7 | SEM PAPEL | | 7 | 缺纸 |
| 8 | Manca Nastro | | 8 | SEM FITA | | 8 | 无碳带 |
| 9 | Testina Aperta | | 9 | CABECA ABERTA | | 9 | 打印头打开 |
| 10 | ERRORE TESTINA | | 10 | ERRO DE CABECA | | 10 | 打印头错误 |
| 11 | Temp. testa alta | | 11 | EXCESSO TEMP. CABECA | | 11 | 过高打印头温度。 |
| 12 | ERRORE NASTRO | | 12 | ERRO DE FITA | | 12 | 碳带错误 |
| 13 | REWINDER PIENO | | 13 | REBOBINADOR CHEIO | | 13 | 回卷器满 |
| 14 | SALVA ####KB/&&&&KB<br>SALVA %%,%%%,%%%KB | | 14 | SALVAR ####KB/&&&&KB<br>SALVAR %%,%%%,%%%KB | | 14 | 保存 ####KB/&&&&KB<br>保存 %%,%%%,%%%KB |
| 15 | FORMAT ####KB/&&&&KB<br>FORMAT %%,%%%,%%%KB | | 15 | FORMATO ####KB/&&&&KB<br>FORMATO %%,%%%,%%%KB | | 15 | 格式化 ####KB/&&&&KB<br>格式化 %%,%%%,%%%KB |
| 16 | CARICAMENT | | 16 | A CARREGAR... | | 16 | 正在加载… |
| 17 | Configurazione | | 17 | MODO CONFIG. | | 17 | 设置模式 |
| 18 | Err. Scritt. memoria | | 18 | ERRO DE ESCRITA | | 18 | 内存写入错误 |
| 19 | ERRORE FORMATTAZIONE | | 19 | ERRO DE FORMATO | | 19 | 格式化错误 |
| 20 | Memoria piena | | 20 | MEMORIA CHEIA | | 20 | 内存满 |
| 21 | SYNTAX ERROR | | 21 | ERRO DE SINTAXE | | 21 | 语法错误 |
| 22 | ERRORE ALIMENT. | | 22 | FALHA DE ALIMENTACAO | | 22 | 电源故障 |
| 23 | Errore EEPROM | | 23 | ERRO NA EEPROM | | 23 | EEPROM 错误 |
| 24 | SYSTEM ERROR | | 24 | ERRO DE SISTEMA | | 24 | 系统错误。 |
| 25 | DHCP CLIENT INIT... | | 25 | INIC. CLIENTE DHCP... | | 25 | DHCP 客户端初始化… |
| 26 | RFID WRITE ERROR | | 26 | ERRO ESCRITA RFID | | 26 | RFID 写入错误 |
| 27 | RFID ERROR | | 27 | ERRO EM RFID | | 27 | RFID 错误 |
| 28 | INPUT PASSWORD | | 28 | INPUT PASSWORD | | 28 | INPUT PASSWORD |
| 29 | PASSWORD ERRATA | | 29 | SENHA INVALIDA | | 29 | 密码无效 |
| 30 | RFID CONFIG ERR | | 30 | ERRO DE CONFIG. RFID | | 30 | RFID 配置错误 |
| 31 | BATTERIA BASSA | | 31 | POUCA BATERIA | | 31 | 电量低 |
| 32 | Errore Comm Interna | | 32 | ERR INTERNO COMUNIC. | | 32 | 内部通讯错误 |

| No | Korean |
|---|---|
| 1 | 온라인 |
| 2 | 헤드 열림 |
| 3 | PAUSE |
| 4 | 통신 에러. |
| 5 | 용지 잼 |
| 6 | 커터 에러 |
| 7 | 종이가 없습니다. |
| 8 | 리본이 없습니다. |
| 9 | 헤드 열림 |
| 10 | 써멀헤드 에러. |
| 11 | 헤드 이상 과열. |
| 12 | 리본 에러 |
| 13 | 리와인더에 가득 참 |
| 14 | 등록　　####KB/&&&&KB<br>등록　　%%,%%%,%%%KB |
| 15 | 초기화　####KB/&&&&KB<br>초기화　%%,%%%,%%%KB |
| 16 | 등록중 |
| 17 | 　　　설정 모드 중 |
| 18 | 메모리 쓰기 에러. |
| 19 | 초기화 에러 |
| 20 | 메모리 오버 |
| 21 | 커맨드 에러 |
| 22 | 전원 이상 |
| 23 | EEPROM 에러 |
| 24 | 시스템 에러 |
| 25 | DHCP CLIENT 초기화중 |
| 26 | RFID 쓰기 에러 |
| 27 | RFID 에러 |
| 28 | INPUT PASSWORD |
| 29 | 패스워드 에러 |
| 30 | RFID 설정 에러 |
| 31 | 배터리 저전압 |
| 32 | 내부 시리얼 에러 |

# 7 DISPLAY PATTERN AND KEY OPERATION FOR SYSTEM MODE AND USER MODE

## 7.1 LIST BOX WITH SCROLLBAR

The list box is used for displaying the menus or items to be selected.　It is comprised of the following parts.



The knob appears on the scrollbar when the number of scroll lines is over 4 lines.

There are three types of list box with scrollbar, as follows.

| | Display |
|---|---|
| Menu display (without setting value) |  |
| Menu display (with setting value) |  |
| Setting value selection display |  |

Key function (Menu display)

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Returns to the top menu without saving changes. |
| [CANCEL] | [FEED] + [RESTART] | Returns to the upper hierarchy without saving changes. |
| [ENTER] | [PAUSE] | Displays a next screen. |
| [UP] | [RESTART] | Moves the cursor upward. The cursor does not move any further when the selected option is listed at the top. |
| [DOWN] | [FEED] | Moves the cursor downward. The cursor does not move any further when the selected option is listed at the bottom. |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

Key function (value setting display)

| Key | Compatible Key | Function |
|-----|----------------|----------|
| [MODE] | None | Returns to the top menu without saving changes. |
| [CANCEL] | [FEED] + [RESTART] | Returns to the upper hierarchy without saving changes. |
| [ENTER] | [PAUSE] | Saves the changes and returns to the upper hierarchy. |
| [UP] | [RESTART] | Moves the cursor upward. The cursor does not move any further when the selected option is listed at the top. |
| [DOWN] | [FEED] | Moves the cursor downward. The cursor does not move any further when the selected option is listed at the bottom. |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

When multiple keys other than specified above ([FEED] + [RESTART]) are pressed at the same time, the printer behavior is not guaranteed.

Movement of the cursor when scrolled

The cursor moves in the following way with a depression of the [UP] or [DOWN] key. The following table shows the example of depression of the [DOWN] key. The [UP] key functions in the same way.

| Display | Key operation | |
|---|---|---|
| SYSTEM MODE  V1.0<br>■<1>DIAG.<br><2>PARAMETER SET<br><3>ADJUST SET<br><4>TEST PRINT | | |
| SYSTEM MODE  V1.0<br><1>DIAG.<br><2>PARAMETER SET<br><3>ADJUST SET<br><4>TEST PRINT | Press [DOWN] key | The position of the displayed menus remains unchanged and only the cursor moves to one line below. |
| SYSTEM MODE  V1.0<br><1>DIAG.<br><2>PARAMETER SET<br><3>ADJUST SET<br><4>TEST PRINT | Press [DOWN] key | The position of the displayed menus remains unchanged and only the cursor moves to one line below. |
| SYSTEM MODE  V1.0<br><2>PARAMETER SET<br><3>ADJUST SET<br><4>TEST PRINT<br><5>SENSOR ADJUST | Press [DOWN] key | The entire menu moves up by one line and the cursor moves to the next item. |
| | | |
| SYSTEM MODE  V1.0<br><11>RTC<br><12>Z-MODE<br><13>USB MEMORY<br><14>RESET | Press [DOWN] key | The entire menu moves up by one line and the cursor moves to the next item. |
| SYSTEM MODE  V1.0<br><11>RTC<br><12>Z-MODE<br><13>USB MEMORY<br><14>RESET | Press [DOWN] key | The position of the displayed menus remains unchanged and only the cursor moves to one line below. |

The cursor position when shifting from upper menu to its sub menu

When shifting from upper menu to its sub menu, the cursor is positioned at the topmost item except for RFID setting menu. (Because the RFID menu items show the setting value.)

The cursor position when shifting from upper menu to its subordinate value setting display

When shifting from upper menu to its subordinate value setting display, the cursor is positioned at the currently selected item.

The cursor position when shifting from sub menu or value setting display to its upper menu

When shifting from lower menu or value setting display to its upper menu, the cursor is positioned at the previously selected item.

When the [MODE] key is pressed while the main menu is displayed:

When the [MODE] key is pressed while the main menu of the system mode or user system mode, the cursor is positioned at the topmost item.

When the [CANCEL] key is pressed while the main menu is displayed:

When the [CANCEL] key is pressed while the main menu of the system mode or user system mode, the cursor does not move from the current position.

## 7.2 VALUE SETTING DISPLAY

The value setting display is used for setting a value by increasing or decreasing it.
It is comprised of the following parts.

Display example



FEED ADJ. ← Title

Setting range →

+0.0mm

(-50.0 - +50.0mm)

Setting value ←

The currently programmable item is highlighted.
The display of the symbols like "+" and "-", and the unit of measure like "mm" and "step" differs depending on the item to be set.

| | Display |
|---|---|
| Setting display with one field | FEED ADJ.<br><br>+0.0mm<br><br>(-50.0 - +50.0mm) |
| Setting display with multiple fields (placed horizontally) | IP ADDRESS<br><br><br>192.168.010.020 |
| Setting display with multiple fields (placed vertically) | READ RETRY<br>5 times<br>(  0 - 255 times)<br>4.0 sec<br>( 0.0  -  9.9 sec) |

Key function (Setting display with one field)

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Returns to the top menu without saving changes. |
| [CANCEL] | [FEED] + [RESTART] | Returns to the upper hierarchy without saving changes. |
| [ENTER] | [PAUSE] | Saves the changes and returns to the upper hierarchy. |
| [UP] | [RESTART] | Increases the setting value by specified step. When the setting value reaches the maximum, it does not increase any further. |
| [DOWN] | [FEED] | Decreases the setting value by specified step. When the setting value reaches the minimum, it does not decrease any further. |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

Key operation (Setting display with multiple fields (horizontal))

| Key | Compatible Key | Function |
|-----|----------------|----------|
| [MODE] | None | Returns to the top menu without saving changes. |
| [CANCEL] | [FEED] + [RESTART] | Returns to the upper hierarchy without saving changes. |
| [ENTER] | [PAUSE] | Saves the changes and returns to the upper hierarchy. |
| [UP] | [RESTART] | Increases the setting value by specified step. When the setting value reaches the maximum, it does not increase any further. |
| [DOWN] | [FEED] | Decreases the setting value by specified step. When the setting value reaches the minimum, it does not decrease any further. |
| [LEFT] | None | Moves the cursor to the left field.　The cursor does not move any further when the left-most field is selected. |
| [RIGHT] | None | Moves the cursor to the right field.　The cursor does not move any further when the right-most field is selected. |

Key function (Setting display with multiple fields (vertical))

| Key | Compatible Key | Function |
|-----|----------------|----------|
| [MODE] | None | Returns to the top menu without saving changes. |
| [CANCEL] | [FEED] + [RESTART] | Returns to the upper hierarchy without saving changes. |
| [ENTER] | [PAUSE] | Saves the changes and returns to the upper hierarchy. |
| [UP] | [RESTART] | Increases the setting value by specified step. When the setting value reaches the maximum, it does not increase any further. |
| [DOWN] | [FEED] | Decreases the setting value by specified step. When the setting value reaches the minimum, it does not decrease any further. |
| [LEFT] | None | Moves the cursor to the upper field.　The cursor does not move any further when the topmost field is selected. |
| [RIGHT] | None | Moves the cursor to the lower field.　The cursor does not move any further when the bottom field is selected. |

## 7.3 INFORMATION DISPLAY

The information display is used when no input or setting is performed.
It is consists of the following parts.

Display example



Title ⟶ CHECKING & PRINT

PRINTING ⟵ Information

| | Display |
|---|---|
| | CHECKING & PRINT<br><br>PRINTING |
| Scroll | FILE MAINTENANCE<br>※00 ZEBRASTMSX5.<br>01 ------------<br>02 SHORT.BAS<br>03 ------------ |
| RFID tag read | ID READ<br>TAG    1/1<br><br>00010203 04050607<br>08090A0B 0C0D0E0F |

Key function

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Displays the top menu. |
| [CANCEL] | [FEED] + [RESTART] | Displays the upper hierarchy. |
| [ENTER] | [PAUSE] | Displays the upper hierarchy. |
| [UP] | [RESTART] | No function |
| [DOWN] | [FEED] | No function |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

Key function (Scroll)

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Displays the top menu. |
| [CANCEL] | [FEED] + [RESTART] | Displays the upper menu. |
| [ENTER] | [PAUSE] | Displays the upper menu. |
| [UP] | [RESTART] | Moves the cursor upward. The cursor does not move any further when it is positioned at the top. |
| [DOWN] | [FEED] | Moves the cursor downward. The cursor does not move any further when it is positioned at the bottom. |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

Key function (RFID tag read)

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Displays the top menu without saving changes. |
| [CANCEL] | [FEED] + [RESTART] | Displays the upper menu without saving changes. |
| [ENTER] | [PAUSE] | RFID tag is read again. |
| [UP] | [RESTART] | Displays the data of the previous tag. The display does not change when the first tag data is being shown. |
| [DOWN] | [FEED] | Displays the data of the next tag.  The display does not change when the last tag data is being shown. |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

## 7.4 SENSOR ADJUSTMENT DISPLAY

The sensor adjustment display is used only when the level of the sensors provided on the printer is adjusted.
It is comprised of the following parts.

Display example



| | Display |
|---|---|
| Before adjustment | REFLECT<br>0.0V<br><br>Set a blank label<br>[ENTER] for 3sec |
| After adjustment | REFLECT<br>0.0V *<br><br>Adjust Complete |

Key function (before adjustment)

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Displays the top menu. |
| [CANCEL] | None | Displays the upper hierarchy. |
| [ENTER] | None | When held down for 3 seconds or more, the sensor adjustment is performed.<br>When this key is released within 3 seconds, the display returns to the upper hierarchy display. |
| [UP] | None | No function |
| [DOWN] | None | No function |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

Key function (after adjustment)

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Displays the top menu. |
| [CANCEL] | None | Displays re-adjustment menu. |
| [ENTER] | None | Displays the upper menu. |
| [UP] | None | No function |
| [DOWN] | None | No function |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

The asterisk "*" shown on the right side of the adjustment value indicates the completion of adjustment.

The voltage under adjustment is updated approximately every 200 msec.

## 7.5  TEMPERATURE  DISPLAY

Temperature display is used only for displaying the print head temperature and ambient temperature.
It is comprised of the following parts.

Display example

Title ⟶ 
```
TEMPERATURE

THERMAL HEAD   20 ℃      ← Print head temperature
OPEN-AIR       13 ℃      ← Ambient temperature
```

| | Display |
|---|---|
| | TEMPERATURE <br><br> THERMAL HEAD   20 ℃ <br> OPEN-AIR       13 ℃ |

Key function

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Displays the top menu. |
| [CANCEL] | None | Displays the upper hierarchy display. |
| [ENTER] | None | Displays the upper hierarchy display. |
| [UP] | None | No function |
| [DOWN] | None | No function |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

Each temperature is updated approximately every 200 msec.

## 7.6 FILE SELECTION DISPLAY

File selection display is used for selecting a file when copying data from USB memory to the printer.
It is comprised of the following parts.

Display example



Title

Scroll bar

Scroll lines (4 lines)

The scrollbar on the file selection display is not provided with the knob regardless of the number of files.

There are two types of file selection displays, as follows.

| Copy data selection display | USB TO PRINTER<br>B-EX4T1-0000.DAT<br>B-EX4T1-0001.DAT<br>B-EX4T1-0002.DAT<br>B-EX4T1-0003.DAT |
|---|---|
| CFG file selection display | USB TO PRINTER<br>B-EX4T1-0000.CFG<br>B-EX4T1-0001.CFG<br>B-EX4T1-0002.CFG<br>B-EX4T1-0003.CFG |

Key function

| Key | Compatible Key | Function |
|---|---|---|
| [MODE] | None | Displays the top menu without selecting a file. |
| [CANCEL] | [FEED]+[RESTART] | Displays the previous display without selecting a file. |
| [ENTER] | [PAUSE] | Displays the next display. |
| [UP] | [RESTART] | Moves the cursor upward. The cursor does not move any further when it is positioned at the top. |
| [DOWN] | [FEED] | Moves the cursor downward. The cursor does not move any further when it is positioned at the bottom. |
| [LEFT] | None | No function |
| [RIGHT] | None | No function |

Printer operation is not guaranteed when multiple keys are pressed except for those mentioned above ([FEED]+[RESTART]).

# 8 SYSTEM MODE

## 8.1 OUTLINE OF SYSTEM MODE

The printer enters the system mode when the following operation is performed when the printer power is off.
- Turn on the printer while holding down the [FEED] and [PAUSE] keys at the same time.
- Turn on the printer while holding down the [MODE] key.

The system mode is intended for performing self-test, parameter setting, and other settings.
When the top menu is displayed, the firmware version is shown on the right side of the title.

The language displayed on the panel is Japanese when Japanese is selected for the LCD language parameter, and English when English, German, French, Dutch, Spanish, Italian, Portuguese or Chinese is selected.

The key operations for the system mode are described below.

Key operations follow Section 7.1 LIST BOX WITH SCROLLBAR.

| Display |
|---|
| SYSTEM MODE      V1.0 |
| <1>DIAG. |
| <2>PARAMETER SET |
| <3>ADJUST SET |
| <4>TEST PRINT |

Top menu for QM/CN/QQ model

| English |
|---|
| <1>DIAG. |
| <2>PARAMETER SET |
| <3>ADJUST SET |
| <4>TEST PRINT |
| <5>SENSOR ADJUST |
| <6>RAM CLEAR |
| <7>INTERFACE |
| <8>BASIC |
| <9>FOR FACTORY |
| <10>RFID |
| <11>RTC |
| <12>Z-MODE |
| <13>USB MEMORY |
| <14>RESET |

| DIAG. | Used to perform self diagnosis, print out the result, check for the print head broken elements. |
|---|---|
| PARAMETER SET | Used to set the parameters for each printer function. |
| ADJUST SET | Used to fine adjust the printer mechanism position and sensor. |
| TEST PRINT | Used to conduct test print by printing slant lines, characters and barcodes. |
| SENSOR ADJUST | Used to display the ambient temaprature and print head temparature, and adjust each level of the media sensor. |
| RAM CLEAR | Used to clear the maintenance counter and parameters. |
| INTERFACE | Used to set the parameters of the interface such as network, USB, RS232C and parallel. |
| BASIC | Used to set the function of the BASIC program when it is loaded printer. |
| FOR FACTORY | Used to adjust the printer before shipment. |
| RFID | Used to set RFID-related parameters. |
| RTC | Used to set the date & time of the real time clock, enable or disable the low battery check, and choose a real time renewal timing. |
| Z-MODE | Same as BASIC. |
| USB MEMORY | Used to copy data to/from USB memory. |
| RESET | Used to reset the printer. |

## 8.2 REFLECTING THE SYSTEM MODE SETTINGS IN THE PRINTER

The settings configured in the system mode or user system mode are saved in the printer at the following timing, depending on the items to be saved.

- Periodic save at 20-msec. interval
- When Reset menu in the system mode or user system mode is performed

The changes in the settings, with a partial exception, take effect at a power on time or after a reset.

## 8.3  DIAG

The main firmware version is displayed on the right side of the title.

Contents of DIAG. menu

| MENU  ITEM | Display pattern and key operation |
|---|---|
| SYSTEM  MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     <1>DIAG. | |
|         MAINTENANCE  CONT | |
|         AUTO  DIAGNOSTIC | |
|         HEAD  CHECK | 7.3 INFORMATION DISPLAY |

### 8.3.1  MAINTENANCE  CONT

This section describes how to print out the maintenance counter data.
The following table shows the menu structure from the top menu of the system mode to MAINTENAN
CE  CONT.

| MENU  ITEM | Display pattern and key operation |
|---|---|
| SYSTEM  MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     <1>DIAG. | |
|         MAINTENANCE  CONT | |
|           PRINT  TYPE | |
|             TRANSFER | |
|             DIRECT | |
|           CUT  TYPE | |
|             OFF | |
|             ON | |
|           CHECKING  &  PRINT | 7.3 INFORMATION DISPLAY |

When an error occurs while printing, the error message is displayed, the ERROR LED turns on, and the
ONLINE LED turns off.   Though the error can be cleared by presing [ENTER], [CANCEL] or [MODE] key, the
printer does not print the erroneous label.

NOTE:
For the B-EX4D2, the direct thermal mode (DIRECT) has been set as default, it is not necessary to select the
print type.   Even if the thermal transfer mode (TRANSFER) is selected, it will be automatically changed to the
direct thermal mode when the [ENTER] key is pressed.

Menu operation example

| Display | Procedure |
|---|---|
| | Turn on the printer while holding down [FEED] and [PAUSE] keys at the same time.<br>SYSTEM MODE menus are displayed. |
| SYSTEM MODE V1.0<br><1>DIAG.<br><2>PARAMETER SET<br><3>ADJUST SET<br><4>TEST PRINT | Select <1>DIAG. and press [ENTER] key.<br>Submenus of <1>DIAG. are displayed. |
| <1>DIAG. V1.0<br>MAINTENANCE CONT<br>AUTO DIAGNOSTIC<br>HEAD CHECK | Select MAINTENANCE CONT and press [ENTER] key.<br>Submenus of MAINTENANCE CONT are displayed. |
| MAINTENANCE CONT<br>PRINT TYPE TRANSFER<br>CUT TYPE OFF<br>CHECKING & PRINT | Select PRINT TYPE and press [ENTER] key.<br>PRINT TYPE menu is displayed. |
| PRINT TYPE<br>TRANSFER<br>DIRECT | Select either print method.<br>When [ENTER] key is pressed, the display returns to MAINTENANCE CONT menu. |
| MAINTENANCE CONT<br>PRINT TYPE TRANSFR<br>CUT TYPE OFF<br>CHECKING & PRINT | Press [DOWN] key, select CUT TYPE, and press [ENTER] key.<br>CUT TYPE menu is displayed. |
| CUT TYPE<br>OFF<br>ON | Select OFF or ON for CUT TYPE.<br>When [ENTER] key is pressed, the display returns to MAINTENANCE CONT menu. |
| MAINTENANCE CONT<br>PRINT TYPE TRANSFR<br>CUT TYPE OFF<br>CHECKING & PRINT | Press [DOWN] key, select CHECKING & PRINT, and press [ENTER] key.<br>The maintenance counter and self-diagnosis result are printed. |
| While printing … ||
| CHECKING & PRINT<br><br>PRINTING | "PRINTING" is displayed. |
| When the printing normally ends: ||
| MAINTENANCE CONT<br>PRINT TYPE TRANSFR<br>CUT TYPE OFF<br>CHECKING & PRINT | The display returns to MAINTENANCE CONT menu. |
| When a print error occurs: ||
| | The printer stops printing displaying the error message.<br>The ERROR LED turns on and the ONLINE LED turns off.<br>The display returns to MAINTENANCE CONT menu when [ENTER] or [CANCEL] key is pressed. At this time, the ERROR LED turns off and the ONLINE LED turns on.<br>Note that the printer does not automatically re-print the erroneous label after recovery from the error. |

## 8.3.1.1 COUNTER PARAMETER PRINT CONTENTS

```
<< COUNTER >>                              << USB >>
TOTAL FEED    0.0km        [QM]            SERIAL NUMBER      [DISABLE]
FEED          0.0km                                           [XXXXXXXXXXXX]
FEED1         0.0km                        << RS-232C >>
FEED2         0.0km                        SPEED              [9600]
FEED3         0.0km                        DATA LENGTH        [8]
FEED4         0.0km                        STOP BIT           [1]
PRINT         0.0km                        PARITY             [EVEN]
PRINT1        0.0km                        CONTROL            [XON+READY AUTO]
PRINT2        0.0km                        << CENTRO >>
PRINT3        0.0km                        ACK/BUSY           [TYPE1]
PRINT4        0.0km                        INPUT PRIME        [ON]
CUT           0                            PLUG & PLAY        [OFF]
HEAD U/D      0                            << LAN/WLAN >>
RIBBON        0h                           LAN/WLAN           [OFF]
SOLENOID      0h                           SNMP               [OFF]
232C ERR      0                            PRTR IP ADDRESS    [192.168.010.020]
SYSTEM ERR    0                            GATE IP ADDRESS    [000.000.000.000]
POWER FAIL    0                            SUBNET MASK        [255.255.255.000]
<< ADJUST >>                               SOCKET PORT        [OFF] [08000]
[PC]                  [KEY]                DHCP               [OFF]
FEED     +0.0mm    FEED     +0.0mm         DHCP CLIENT ID     [FFFFFFFFFFFFFFFFFFFFF]
CUT      +0.0mm    CUT      +0.0mm                            [FFFFFFFFFFFFFFFFFFFFF]
BACK     +0.0mm    BACK     +0.0mm                            [FFFFFFFFFFFFFFFFFFFFF]
TONE(T)  +0step    TONE(T)  +0step                            [FFFFFFFFFFFFFFFFFFFFF]
TONE(D)  +0step    TONE(D)  +0step                            [FFFFFFFFFFFFFFFFFFFFF]
RBN(FW)  +0        RBN(FW)  +0                                [FFFFFFFFFFFFFFFFFFFFF]
RBN(BK)  +0        RBN(BK)  +0                                [FFFFFFFFF]
X ADJ.   +0.0mm                            DHCP HOST NAME     [ABCDEFGHIJKLMNOPQRST]
THRESHOLD(R) 0.0V                                             [UVWXYZ123456]
THRESHOLD(T) 0.0V                          WLAN STANDARD      [11b/g]
HD ADJ.  +0msec *3                         WLAN MODE          [INFRASTRUCTURE]
<< PARAMETER SETTINGS >>                   ESS ID             [                 ]
MEDIA LOAD          [STD]                                     [                 ]
FORWARD WAIT        [ON] +0.0mm  [MODE1]   ENCRYPT            [OFF]
HU CUT/RWD.         [OFF]                   WPA MODE           [OFF]
RIBBON SAVE         [TAG]                   AUTH               [OPEN SYSTEM]
PRE PEEL OFF        [OFF]                   DEFAULT KEY        [1]
BACK SPEED          [STD]                   802.1X SUPPLICANT  [OFF]
TYPE OF RIBBON      [CSO] *1                802.11b CHANNEL    [01]
AUTO CALIB          [OFF]                   802.11b BAUD RATE  [11M]
FONT                [PC-850]  [0]           802.11g CHANNEL    [01]
CODE                [AUTO]                  802.11g BAUD RATE  [54M]
PEEL OFF STATUS     [ON]                    WINS               [OFF]
USB I/F STATUS      [OFF]                   WINS IP ADDRESS    [000.000.000.000]
FEED KEY            [FEED]                  LPR                [OFF]
KANJI               [TYPE1]                 << RFID >>
EURO CODE           [B0]                    MODULE TYPE        [NONE]
AUTO HD CHK         [OFF]                   TAG TYPE           [NONE          ]
WEB PRINTER         [OFF]                   RF CHANNEL         [AUTO]
RIBBON NEAR END     [OFF]                   ADJUST RETRY       [+00mm]
EX.I/O MODE         [TYPE1]                 ISSUE RETRY        [    3labels]
LBL/RBN END         [TYPE1]                 READ RETRY         [   5times] [4.0sec]
MAXI CODE SPEC.     [TYPE1]                 WRITE RETRY        [   5times] [4.0sec]
XML                 [STD]                   POWER LEVEL        [    0]
THRESHOLD SEL(R)    [MANUAL SET]           Q VALUE            [    0]
THRESHOLD SEL(T)    [MANUAL SET]           AGC THRESHOLD      [    0]
ENERGY TYPE(T)      [Semi resin1]          WRITE AGC          [    0]
ENERGY TYPE(D)      [Standard]             RETRY MIN AGC      [    0]
POWER SAVE TIME     [ 15min]               TAG CHECK          [PASSWORD] [ON]  [ON]
BASIC               [OFF]                   MULTI WRITE        [OFF]
BASIC TRACE         [OFF]                   CALIB. MODE        [OFF] *2
<< PANEL >>                                 CALIB. AGC         [    0] *2
MESSAGE             [ENGLISH]              CALIB. POSITION    [+000.0mm] *2
MACHINE NAME        [ON]                    ANTENNA POSITION   [FRONT] *2
PRINT PAGE          [ON]                    WRITE OK TAGS      9999999
IP ADDRESS          [ON]                    VOID PRINT TAGS    9999999
CONTRAST            [40]                    << RTC >>
SYSTEM PASSWORD     [OFF]                   BATTERY CHECK      [ON]
<< STORAGE AREA >>                          RENEWAL            [BATCH]
TTF AREA            [    0KB]
EXT CHR AREA        [    0KB]
BASIC AREA          [    0KB]
PC SAVE AREA        [    0KB]
```

*1: B-EX4T2, B-EX6T2, and B-EX4D2 only

*2: Supported from firmware version of C1.2 for the
    B-EX4T1-G/T-QM/CN.

*3: Supported from firmware version of V2.0B for the
    B-EX4T1-TS25-R.

Print condition:

| Label length | | 490 mm |
|---|---|---|
| Print method | | User setting |
| Sensor type | | None |
| Speed | (203 dpi) B-EX4T1-G, B-EX4T2-G, B-EX6T2-G, B-EX4D2-G | 6 ips |
| | (300 dpi/305 dpi) B-EX4T1-T, B-EX4T2-T, B-EX6T2-T | 5 ips |
| | (600 dpi) B-EX4T2-H | 3 ips |
| Print count | | 1 |
| Issue mode | | User setting |
| Other | | No rewinder motor activated |

<< COUNTER >>

| Item | Content | Range |
|---|---|---|
| Counting condition | | |

| Item | Content | Range |
|---|---|---|
| TOTAL FEED | Total label distance covered (cannot be cleared) | 0.0 to 3200.0 km |
| Counted when the paper feed motor are driven to feed a paper or print. (Reverse feed is also counted.) When the power is turned off, the label distance of 50.0 cm or less may be rounded down when backed up. | | |
| FEED | Label distance covered | 0.0 to 3200.0 km |
| Counted when the paper feed motor are driven to feed a paper or print. (Reverse feed is also counted.) When the power is off, the label distance of 50.0 cm or less may be rounded down when backed up. | | |
| FEED1 to FEED4 | History of label distances covered | 0.0 to 3200.0 km |
| History of the last 4 label distances. | | |
| PRINT | Print distance | 0.0 to 200.0 km |
| Counted while printing. (Reverse feed is not counted.) B-EX4T1-G/B-EX4T2-G/B-EX6T2-G/B-EX4D2-G:  When the power is turned off, the print distance of 8.2 m or less is rounded down when backed up. B-EX4T1-T/B-EX4T2-T/B-EX6T2-T: When the power is turned off, the print distance of 5.6 m or less is rounded down when backed up. B-EX4T2-H: When the power is turned off, the print distance of 2.8 m or less is rounded down when backed up. | | |
| PRINT1 to PRINT4 | History of print distances | 0.0 to 3200.0 km |
| History of the last 4 print distances. | | |
| CUT | Cut count | 0 to 1000000 |
| Every cut operation is counted. The cut count is saved every 4 cut operation. | | |
| HEAD U/D | Head up/down count | 0 to 2000000 |
| The number of times the print head moves up and down with the solenoid for ribbon save is counted.   (A set of up and down is counted as one.) The head up/down count is saved every 4 head up/down operation. | | |
| RIBBON | Ribbon motor drive time | 0 to 2000 hours |
| Note: The counter value for the B-EX4D2 is indefinite. Counted when the ribbon motor is driven while paper feed or printing. (Reverse feed is also counted.) When the power is turned off, drive time of 10 seconds or less is rounded down when backed up. | | |
| SOLENOID | Head-up solenoid drive time | 0 to 1000 hours |
| Counted when the ribbon saving operation is performed. When the power is turned off, drive time of 10 seconds or less is rounded down when backed up. | | |
| 232C ERR | RS-232C hardware error count | 0 to 255 |
| Counted when a parity error, overrun error or framing error occurs. | | |
| SYSTEM ERR | System error count | 0 to 15 |

| | | |
|---|---|---|
| Counted when a system error occurs. | | |
| POWER FAIL | Momentary power interruption count | 0 to 15 |
| Counted when a momentary power interruption occurs. | | |

<< ADJUST >>

| Item | Description | Remarks |
|---|---|---|
| [PC] FEED | Feed amount fine adjustment | -50.0mm to +50.0mm |
| CUT | Cut position (or strip position) fine adjustment | -50.0mm to +50.0mm |
| BACK | Back feed fine adjustment | -9.9mm to +9.9mm |
| TONE (T) | Print density fine adjustment (Thermal transfer print mode) | -10 to +10 step |
| TONE (D) | Print density fine adjustment (Direct thermal print mode) | -10 to +10 step |
| RBN (FW) | Ribbon motor drive voltage fine adjustment (Take-up) | -15 to +10 step |
| RBN (BK) | Ribbon motor drive voltage fine adjustment (Back tension) | -15 to +10 step |
| [KEY] FEED | Feed amount fine adjustment | -50.0mm to +50.0mm |
| CUT | Cut position (or strip position) fine adjustment | -50.0mm to +50.0mm |
| BACK | Back feed fine adjustment | -9.9mm to +9.9mm |
| TONE (T) | Print density fine adjustment (Thermal transfer print mode) | -20 to +10 step |
| TONE (D) | Print density fine adjustment (Direct thermal print mode) | -20 to +10 step |
| RBN (FW) | Ribbon motor drive voltage fine adjustment (Take-up) | -15 to +10 step |
| RBN (BK) | Ribbon motor drive voltage fine adjustment (Back tension) | -15 to +10 step |
| X ADJ. | X-coordinate fine adjustment | -99.5mm to +99.5mm |
| THRESHOLD<R> | Threshold fine adjustment for reflective sensor | 0.0V to 4.0V |
| THRESHOLD<T> | Threshold fine adjustment for transmissive sensor | 0.0V to 4.0V |
| HDDWNADJ | Head down timing fine adjustment<br>* Supported from firmware version of V2.0B for the B-EX4T1-TS25-R. | -30msec. to +30msec. |

<< PARAMETER SETTINGS >>

| Item | Description | Printed value | |
|------|-------------|---------------|---|
| MEDIA LOAD | Media loading<br><br>**NOTE**: Even if the "ECO+Bfeed" is selected for the B-EX4T2, B-EX6T2, or B-EX4D2, the setting and the printer behavior will be automatically changed to "ECO". | OFF | Disabled |
| | | STD | Feeds the detected gap/mark to print start position. |
| | | ECO | Feeds gap/mark between print head and sensor to print start position. |
| | | ECO+BFeed | Back feed follows ECO printer behavior. |
| FORWARD WAIT | Forward feed standby after issue | ON | Performed<br>(A fine adjustment value for the stop position is also printed.) |
| | | OFF | Not performed |
| FW/BK ACT. | Forward feed standby action | MODE1 | Stops after 13.7-mm forward feed. |
| | | MODE2 | Stops after 6-mm back feed and 3-mm forward feed. (Only when the cut mode, thermal transfer, and feed gap sensor is selected.) In other cases, the printer stops after 13.7-mm forward feed. |
| HU CUT/RWD. | Head-up operation in cut issue mode, or use of the Rewinder<br><br>**NOTE**: Since head-up function is not available to the B-EX4T2, B-EX6T2, and B-EX4D2, this parameter is to choose whether to use the Rewinder. The head-up operation is fixed to OFF. | ON | Head-up operation is performed, or the rewinder is used. |
| | | OFF | Head-up operation is not performed, or the rewinder is not used. |
| RBN SAVE | Use of ribbon saving module<br>**NOTE**: Even if the "TAG" or LABEL" is selected for the B-EX4T2, B-EX6T2, or B-EX4D2, the setting and the printer behavior will be automatically changed to "OFF".<br><br>*Supported only by the B-EX4T1-TS25-R V2.0 or later<br>The difference between "ON:TAG" and "ON:TAG2", and between "ON:LBL" and "ON:LBL2", respectively, is the distance of non-print area where a ribbon save is performed. (In the case of 8 ips or faster) | ON:TAG | Used.<br>Head lever position: "TAG" |
| | | ON:LABEL | Used.<br>Head lever position: "LABEL". |
| | | ON:TAG2 * | Used.<br>Head lever position: "TAG" |
| | | ON:LBL2 * | Used.<br>Head lever position: "LABEL". |
| | | OFF | Not used |
| PRE PEEL OFF | Pre-peel-off process setting | ON | Pre-peel-off is performed. |
| | | OFF | Pre-peel-off is not performed. |
| BACK SPEED | Back feed speed setting | STD | 3 ips |
| | | LOW | 2 ips |
| TYPE OF RIBBON | Ribbon roll direction<br>**NOTE**: This parameter is available only to the B-EX4T2/B-EX6T2 | CSO | Outside wound |
| | | CSI | Inside wound |

| AUTO CALIB | Auto calibration setting<br>**NOTE**: When the "ON TRANS.+Bfeed", "ON REFLECT+Bfeed" or "ON ALL+B-feed" is selected for the B-EX4T2, B-EX6T2, or B-EX4D2, the setting and the printer behavior will be automatically changed as follows.<br>ON TRANS.+Bfeed<br>→ON TRANS.<br>ON REFLECT+Bfeed<br>→ON REFLECT<br>ON ALL+Bfeed<br>→ON ALL | OFF | Auto calibration is not performed. |
| --- | --- | --- | --- |
| | | ON TRANS. | Auto calibration is performed with transmissive sensor. |
| | | ON REFLECT | Auto calibration is performed with reflective sensor. |
| | | ON ALL | Auto calibration is performed with both sensors. |
| | | ON TRANS+Bfeed | Back feed follows ON TRANS printer behavior. |
| | | ON REFLECT+Bfeed | Back feed follows ON REFLECT printer behavior |
| | | ON ALL+Bfeed | Back feed follows ON ALL printer behavior. |
| FONT | Character code selection | PC-850 | PC-850 |
| | | PC-852 | PC-852 |
| | | PC-857 | PC-857 |
| | | PC-8 | PC-8 |
| | | PC-851 | PC-851 |
| | | PC-855 | PC-855 |
| | | PC-1250 | PC-1250 |
| | | PC-1251 | PC-1251 |
| | | PC-1252 | PC-1252 |
| | | PC-1253 | PC-1253 |
| | | PC-1254 | PC-1254 |
| | | PC-1257 | PC-1257 |
| | | LATIN9 | LATIN9 |
| | | PC-866 | PC-866 |
| | | Arabic | Arabic |
| | | UTF-8 | UTF-8 |
| | Font "0" selection | O | No slash used |
| | | Ø | Slash used |
| CODE | Control code type | AUTO | Automatic selection |
| | | ESC LF NUL | ESC LF NUL method |
| | | { \| } | { \| } method |
| | | ×× ○○ | Any code (Described in hex. code) |
| PEEL OFF STATUS | Peel-off wait status | ON | Transmitted |
| | | OFF | Not transmitted |
| USB I/F STATUS | USB interface status | ON | Sends |
| | | OFF | Not send |
| FEED KEY | [FEED] key function setting | FEED | One label is fed. |
| | | PRINT | Data in the image buffer is printed on one label. |
| KANJI | Kanji code type | TYPE1 | For WINDOWS codes |
| | | TYPE2 | For original codes |
| EURO CODE | Euro code setting | | |
| AUTO HD CHK | Automatic broken dots check setting | ON | Automatic broken dots check is performed. |
| | | OFF | Automatic broken dots check is not performed. |
| WEB PRINTER | Web printer function setting | ON INTERNAL | Enabled. (Internal memory is used.) |

| | | ON EXTERNAL | Enabled. (External memory is used.) |
|---|---|---|---|
| | | OFF | Disabled. |
| RIBBON NEAR END | Ribbon near end detection setting | 30m | Ribbon near end state is detected when the remaining ribbon length is approximately 30 m. |
| | | 70m | Ribbon near end state is detected when the remaining ribbon length is approximately 70 m. |
| | | OFF | Ribbon near end state is not detected. |
| EX.I/O MODE | Expansion I/O operation mode | TYPE1 | Standard mode. |
| | | TYPE2 | In-line mode. |
| LBL/RBN END | Label end/ribbon end process setting | TYPE1 | When a label end or ribbon end state is detected, the printer stops immediately. |
| | | TYPE2 | When a label end or ribbon end state is detected, the printer prints the current label as far as possible, and then stops. |
| MAXI CODE SPEC. | MaxiCode specification setting | TYPE1 | Compatible with the current version |
| | | TYPE2 | Special specification |
| XML | XML function setting | OFF | Disabled. |
| | | STD | Standard specification. |
| | | ORACLE | Specification for Oracle |
| | | SAP | Specification for SAP |
| | | STD EXTERNAL | Standard specification (External memory is used) |
| | | ORACLE EXTERNAL | Specification for Oracle (External memory is used) |
| | | SAP EXTERNAL | Specification for SAP (External memory is used) |
| THRESHOLD SEL(R) | Threshold value for reflective sensor | MANUAL SET | Manually set value is used. |
| | | COMMAND SET | Command specified value is used. |
| THRESHOLD SEL (T) | Threshold value for transmissive sensor | MANUAL SET | Manually set value is used. |
| | | COMMAND SET | Command specified value is used. |
| ENERGY TYPE(T) | Energy control for thermal transfer print<br><For the B-EX4T1-G/T><br>(*1) "Resin3" shall not be selected for the B-EX4T1-T model. | Semi resin1 | Semi resin 1 |
| | | Semi resin2 | Semi resin 2 |
| | | Resin1 | Resin 1 |
| | | Resin2 | Resin 2 |
| | | Resin3 (*1) | Resin 3 (*1) |
| | | Reserve2 | Reserved. |
| | | Reserve3 | Reserved. |
| | | Reserve4 | Reserved. |
| | | Reserve5 | Reserved. |
| | | Reserve6 | Reserved. |
| | <For the B-EX4T2-G/T Firmware Version C1.0C or before and B-EX6T2-G/T> | WAX1 | Wax 1 |
| | | WAX2 | Wax 2 |
| | | Semi resn1 | Semi resin 1 |
| | | Semi resn2 | Semi resin 2 |

| | | | |
|---|---|---|---|
| | | Resin1 | Resin 1 |
| | | Reserve1 | Reserved. |
| | | Reserve2 | Reserved. |
| | | Reserve3 | Reserved. |
| | | Reserve4 | Reserved. |
| | | Reserve5 | Reserved. |
| | <For the B-EX4T2-G/T Firmware Version C1.0D> | WAX1 | Wax 1 |
| | | WAX2 | Wax 2 |
| | | Semi resn1 | Semi resin 1 |
| | | Semi resn2 | Semi resin 2 |
| | | Resin1 | Resin 1 |
| | | Wax3 | Wax 3 |
| | | Semi resn3 | Semi resin 3 |
| | | Reserve1 | Reserved. |
| | | Reserve2 | Reserved. |
| | | Reserve3 | Reserved. |
| | <For the B-EX4T2-G/T Firmware Version C1.0E or later and B-EX4D2> Note: Since the B-EX4D2 is a direct thermal printer, these parameters are displayed but not used for actual printing. | WAX1 | Wax 1 |
| | | WAX2 | Wax 2 |
| | | Semi resn1 | Semi resin 1 |
| | | Semi resn2 | Semi resin 2 |
| | | Resin1 | Resin 1 |
| | | Wax3 | Wax 3 |
| | | Semi resn3 | Semi resin 3 |
| | | Resin2 | Resin 2 |
| | | Reserve1 | Reserved. |
| | | Reserve2 | Reserved. |
| | <For the B-EX4T2-H> | Resin1 | Resin 1 |
| | | Resin2 | Resin 2 |
| | | Reserve1 | Reserved. |
| | | Reserve2 | Reserved. |
| | | Reserve3 | Reserved. |
| | | Reserve4 | Reserved. |
| | | Reserve5 | Reserved. |
| | | Reserve6 | Reserved. |
| | | Reserve7 | Reserved. |
| | | Reserve8 | Reserved. |
| ENERGY TYPE(D) | Energy control for direct thermal print | Standard | Standard |
| | | Reserve1 | Reserved. |
| | | Reserve2 | Reserved. |
| | | Reserve3 | Reserved. |
| | | Reserve4 | Reserved. |
| | | Reserve5 | Reserved. |
| | | Reserve6 | Reserved. |
| | | Reserve7 | Reserved. |
| | | Reserve8 | Reserved. |
| | | Reserve9 | Reserved. |
| POWER SAVE TIME | Length of time until the printer enters sleep mode | | |
| BASIC | Basic interpreter setting | ON | Basic interpreter is enabled. |
| | | OFF | Basic interpreter is disabled. |
| BASIC TRACE | Basic interpreter trace setting | ON | Trace is enabled. |
| | | OFF | Trace is disabled. |

<< PANEL >>

| Item | Description | Printed value |
|---|---|---|

58

| MESSAGE | Language selection for LCD messages<br>Note: Korean is supported from the following firmware versions:<br>B-EX4T1-G/T-QM/CN: C1.0I<br>B-EX4T2-G/T-QM-CN: C1.0F | ENGLISH | English |
|---|---|---|---|
| | | GERMAN | German |
| | | FRENCH | French |
| | | DUTCH | Dutch |
| | | SPANISH | Spanish |
| | | JAPANESE | Japanese |
| | | ITALIAN | Italian |
| | | PORTUGUESE | Portuguese |
| | | SIMP. CHINESE | Simplified Chinese |
| | | KOREAN | Korean |
| MACHINE NAME | Whether to display the model name | ON | Displayed. |
| | | OFF | Hidden. |
| PRINT PAGE | Whether to display the number of labels printed | ON | Displayed. |
| | | OFF | Hidden. |
| IP ADDRESS | Whether to display IP address | ON | Displayed. |
| | | OFF | Hidden. |
| CONTRAST | LCD contrast | | |
| SYSTEM PASSWORD | Password for system mode | ON | Password is enabled. |
| | | OFF | Password is disabled. |

<< STORAGE AREA >>

| Item | Description | Printed value | |
|---|---|---|---|
| TTF AREA | TrueType Font storage area size | 0KB to 3072KB | （in 128KB units） |
| EXT CHR AREA | Writable character storage area size | 0KB to 3072KB | （in 128KB units） |
| BASIC AREA | Basic file storage area size | 0KB to 3072KB | （in 128KB units） |
| PC SAVE AREA | PC command storage area size | 0KB to 3072KB | （in 128KB units） |

<< USB >>

| Item | Description | Printed value | |
|---|---|---|---|
| SERIAL NUMBER | USB serial number | ENABLE | Enabled. |
| | | DISABLE | Disabled. |
| | USB serial number | | |

<< RS-232C >>

| Item | Description | Printed value | |
|---|---|---|---|
| SPEED | Baud rate | 2400 | 2400 bps |
| | | 4800 | 4800 bps |
| | | 9600 | 9600 bps |
| | | 19200 | 19200 bps |
| | | 38400 | 38400 bps |
| | | 115200 | 115200 bps |
| DATA LENG. | Data length | 7 | 7 bits |
| | | 8 | 8 bits |
| STOP BIT | Stop bit length | 1 | 1 bit |
| | | 2 | 2 bits |
| PARITY | Parity | NONE | None |
| | | ODD | Odd |
| | | EVEN | Even |
| CONTROL | Transmission control method | XON/XOFF | XON/XOFF protocol<br>(No XON output when the power is on, no XOFF output when the power is off) |

| | | READY/BUSY | READY/BUSY (DTR) protocol (No XON output when the power is on, no XOFF output when the power is off) |
|---|---|---|---|
| | | XON+READY AUTO | XON/XOFF + READY/BUSY (DTR) protocol (XON output when the power is on, XOFF output when the power is off) |
| | | XON/XOFF AUTO | XON/XOFF protocol (XON output when the power is on, XOFF output when the power is off) |
| | | READY/BUSY RTS | RTS protocol (No XON output when the power is on, no XOFF output when the power is off) |

<< CENTRO >>

| Item | Description | Printed value | |
|---|---|---|---|
| ACK/BUSY | Centronics ACK/BUSY timing | TYPE1 | The ACK signal is sent to match the rising edge of ACK signal and the falling edge of the BUSY signal. |
| | | TYPE2 | The ACK signal is sent to match the falling edge of ACK signal and the falling edge of the BUSY signal. |
| INPUT PRIME | Reset process when the nInit signal is ON | ON | Reset is performed. |
| | | OFF | Reset is not performed. |
| PLUG & PLAY | Plug-and-play operation | ON | Plug-and-play is enabled. |
| | | OFF | Plug-and-play is disabled. |

<< LAN/WLAN >>

| Item | Description | Printed value | |
|---|---|---|---|
| LAN/WLAN | LAN selection | OFF | Disabled |
| | | AUTO | Auto |
| | | LAN | Wired LAN |
| | | WLAN | Wireless LAN |
| SNMP | SNMP enabled/disable | ON | Enabled |
| | | OFF | Disabled |
| PRTR IP ADDRESS | Printer IP address | ***.***.***.*** | |
| GATE IP ADDRESS | Gateway IP address | ***.***.***.*** | |
| SUBNET MASK | Subnet mask | ***.***.***.*** | |
| SOCKET PORT | Socket communication | ON | Enabled |
| | | OFF | Disabled |
| | Socket communication port number | 0 to 65535 | |
| DHCP | DHCP setting | ON | Enabled |
| | | OFF | Disabled |
| DHCP CLIENT ID | DHCP client ID setting (Hex.) | Max. 64 characters | |
| DHCP HOST NAME | DHCP host name (ASCII) | Max. 32 characters | |
| WLAN STANDARD | Wireless LAN: Standard | 11b/g | 11b/g |
| | | 11b | 11b |
| | | 11g | 11g |
| WLAN MODE | Wireless LAN: Connection setting | INFRASTRUCTURE | Infrastructure mode |
| | | ADHOC | Adhoc mode |

| ESS ID | Wireless LAN: ESS ID | Max. 32 characters | |
|---|---|---|---|
| ENCRYPT | Wireless LAN: Encryption key setting | OFF | OFF |
| | | WEP40 | WEP40 |
| | | WEP104 | WEP104 |
| | | AES | AES |
| | | TKIP | TKIP |
| WPA MODE | Wireless LAN: WPA setting | OFF | OFF |
| | | WPA | WPA |
| | | WPA-PSK | WPA-PSK |
| | | WPA2 | WPA2 |
| | | WPA2-PSK | WPA2-PSK |
| AUTH | Wireless LAN: Authentication method | OPEN | Open system method |
| | | SHARED | Shared key method |
| | | NETWORK EAP | NETWORK EAP |
| DEFAULT KEY | Wireless LAN: Encryption key for sending | 1 to 4 | |
| 802.1X SUPPLICANT | Wireless LAN: Authentication method | OFF | OFF |
| | | EAP-TLS | EAP-TLS |
| | | PEAP | PEAP |
| | | EAP-TTLS | EAP-TTLS |
| | | EAP-FAST | EAP-FAST |
| | | EAP-MD5 | EAP-MD5 |
| | | LEAP | LEAP |
| 802.11b CHANNEL | Wireless LAN: 11b connection channel setting | 01 to 14 | |
| 802.11b BAUD RATE | Wireless LAN: 11b speed setting | 11M | 11M |
| | | 5.5M | 5.5M |
| | | 2M | 2M |
| | | 1M | 1M |
| 802.11g CHANNEL | Wireless LAN: 11g connection channel setting | 01 to 13 | |
| 802.11g BAUD RATE | Wireless LAN: 11g speed setting | 54M | 54M |
| | | 48M | 48M |
| | | 36M | 36M |
| | | 24M | 24M |
| | | 18M | 18M |
| | | 12M | 12M |
| | | 9M | 9M |
| | | 6M | 6M |
| | | 11M | 11M |
| | | 5.5M | 5.5M |
| | | 2M | 2M |
| | | 1M | 1M |
| WINS | WINS enable/disable | ON | Enabled |
| | | OFF | Disabled |
| WINS IP ADDRESS | WINS IP address | ***.***.***.*** | |
| LPR | LPR enable/disable | ON | Enabled |
| | | OFF | Disabled |

<< RFID >>

| Item | Description | Printed value | |
|---|---|---|---|
| MODULE | RFID module type selection | NONE | No RFID kit is installed. |
| | | H1 | B-EX700-RFID-H1-QM-R |
| | | H2 | B-EX700-RFID-H2-R |
| | | U2 | B-EX700-RFID-U2-US/EU-R, B-EX700-RFID-U4-EU/US-R, U4 module preinstall model |
| TAG TYPE | RFID tag type selection | NONE | |
| | | I-Code | 11 |
| | | Tag-it | 12 |
| | | C220 | 13 |
| | | ISO15693 | 14 |
| | | C210 | 15 |
| | | C240 | 16 |
| | | C320 | 17 |
| | | EPC C1 Gen2 | 24 |
| RF CHANNEL | RFID channel setting | 2CH to 8CH | |
| | | AUTO | |
| ADJUST RETRY | RFID adjustment for retry | -99mm to +99mm | |
| ISSUE RETRY | Max number of RFID issue retries | 0 to 255 | |
| READ RETRY | Max number of RFID read retries | 0 to 255 | |
| | RFID read retry time-out | 0 to 9.9 sec. | |
| WRITE RETRY | Max number of RFID write retries | 0 to 255 | |
| | RFID write retry time-out | 0 to 9.9 sec. | |
| POWER LEVEL | RFID wireless power level setting | 9 to 18 | B-EX700-RFID-U2-US/EU-R |
| | | 0 to 18 | B-EX700-RFID-U4-EU/US-R, U4 module preinstall model<br>* Supported from the printer firmware version of C1.0I for the B-EX4T1-G/T-QM/CN and C1.0F for the B-EX4T2-G/T-QM/CN. |
| Q VALUE | RFID module Q value | 0 to 5 | |
| AGC THRESHOLD | RFID AGC threshold setting | 0 to15 | |
| WRITE AGC | AGC threshold for data write | 0 to15 | |
| RETRY MIN AGC | AGC threshold lower limit for retry | 0 to15 | |
| TAG CHECK | RFID error tag detection | OFF | Detection is disabled. |
| | | ON (ID) | RFID error tag detection for ID area data |

| | | ON (ACCESS PASSWORD) | When PASS is selected, the following settings are subsequently displayed: Password setting to protect error tag detection ON: Enabled OFF: Disabled Automatic unlock function setting ON: Enabled OFF: Disabled |
|---|---|---|---|
| CALIB. MODE *(1) | RFID calibration mode | OFF | Disabled |
| | | ON | Enabled |
| CALIB. AGC *(1) | Optimum AGC value obtained through RFID calibration | 0 to 15 | |
| CALIB. POSITION (*1) | Distance to the optimum read/write position obtained through RFID calibration | -999.9mm to +999.9mm | |
| ANTENNA POSITION (*1) | Position of the RF antenna and the wave director | FRONT | Front |
| | | CENTER | Center |
| | | REAR | Rear |
| MULTI WRITE | Hibiki tag multi-word write | ON | Enabled |
| | | OFF | Disabled |
| WRITE OK TAGS | Count of RFID success label write issue | 0 to 9999999 | |
| VOID PRINT TAGS | Count of RFID failure label write issue | 0 to 9999999 | |

*1: Supported from the firmware version of C1.2 for the B-EX4T1-G/T-QM/CN.

<< RTC >>

| Item | Description | Printed value | |
|---|---|---|---|
| BATTERY CHECK | Battery check | ON | Enabled |
| | | OFF | Disabled |
| RENEWAL | Time update timing | BATCH | per batch |
| | | PAGE | per page |

## 8.3.2 AUTO DIAGNOSTIC

The procedure for printing the self-diagnosis result is the same as that for the maintenance counter data. 8.3.1 MAINTENANCE CONT.

The following table shows the menu structure from top menu of the system mode to AUTO DIAGNOSTIC.

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <1>DIAG. | | | |
| | | AUTO DIAGNOSTIC | | |
| | | | PRINT TYPE | |
| | | | | TRANSFER |
| | | | | DIRECT |
| | | | CUT TYPE | |
| | | | | OFF |
| | | | | ON |
| | | | CHECKING & PRINT | 7.3 INFORMATION DISPLAY |

When an error occurs while printing, the error message is displayed, the ERROR LED turns on, and the ONLINE LED turns off. Though the error can be cleared by presing [ENTER], [CANCEL] or [MODE] key, the printer does not print the erroneous label.

NOTE:
For the B-EX4D2, the direct thermal mode (DIRECT) has been set as default, it is not necessary to select the print type. Even if the thermal transfer mode (TRANSFER) is selected, it will be automatically changed to the direct thermal mode when the [ENTER] key is pressed.

## 8.3.2.1 AUTO SELF-DIAGNOSIS PRINTOUT

[B-EX4T1-TS25-R V2.0 or later]

```
PROGRAM B-EX4T1-T
   MAIN   XXXXXXXXX V1.0A:1A00
   BOOT   XXXXXXXXX V1.0 :8500
   WMON XXXXXXXXX V1.0 :6100
FONT      5600
KANJI     NONE   :0000
          NONE   :0000
EEPROM    256B
SDRAM     32MB
SENSOR1   00000000,00000111
SENSOR2   [H]23° C [A]22° C
          [R]4.2V [T]2.5V [E]0.6V
PE LV.    [R]1.8V [T]2.5V
M THRE.   [R]1.8V [T]2.5V
HEAD      [RANK]7            305DPI
LAN MAC   11-22-33-44-55-66
EXP.I/O   NG
EX.232C   NG
RFID      OK  #00RV972  (EU0) R01
WLAN      OK Ver1.1.3
 MAC      00-11-22-33-44-55
RTC       NG
USB MEMORY NG
BASIC M Z-EX4-MV10F. V1.0F:7479
BASIC S Z-EX4-SV10E. V1.0E:AD36
```

```
PROGRAM B-EX4T1-T
   MAIN   XXXXXXXXX V1.0A:1A00
   BOOT   XXXXXXXXX V1.0 :8500
   WMON XXXXXXXXX V1.0 :6100
FONT      5600
KANJI     NONE   :0000
          NONE   :0000
EEPROM    256B
SDRAM     32MB
SENSOR1   00000000,00000111
SENSOR2   [H]23° C [A]22° C
          [R]4.2V [T]2.5V [E]0.6V
PE LV.    [R]1.8V [T]2.5V
M THRE.   [R]1.8V [T]2.5V
HEAD      [RANK]7            305DPI
LAN MAC   11-22-33-44-55-66
EXP.I/O   NG
EX.232C   NG
SIO       NG(0111)
RFID      OK  #00RV972  (EU0) R01
WLAN      OK Ver1.1.3
 MAC      00-11-22-33-44-55
RTC       NG
USB MEMORY NG
BASIC M Z-EX4-MV10F. V1.0F:7479
BASIC S Z-EX4-SV10E. V1.0E:AD36
```

Print condition:

| Label length | | 120 mm |
|---|---|---|
| Print method | | Setting by user |
| Sensor type | | None |
| Speed | (203 dpi) B-EX4T1-G, B-EX4T2-G, B-EX6T2-G, B-EX4D2-G | 6 ips |
| | (300 dpi/305 dpi) B-EX4T1-T, B-EX4T2-T, B-EX6T2-T | 5 ips |
| | (600 dpi) B-EX4T2-H | 3 ips |
| Issuing number | | 1 |
| Issuing mode | | User setting |
| Other | | No Rewinder motor activated. |

(*1) "°" (degree) of "xx°C" may not be printed correctly, depend on the type of code page.

(*3) The Basic program file name and system mode program file name are printed.
When the first 4 characters of each program file name are "Z-EX", the checksum will be also printed.

PROGRAM B-EX4T1-G

—————— Model name B-EX

MAIN 15OCT2010 V1.0A:1A00 —————— Checksum
—————— Version
—————— Creation date (Day-Month-Year)
—————— Name    PROGRAM: Program area

BOOT 20SEP2010 V1.0:8500 —————— Checksum
—————— Version
—————— Creation date (Day-Month-Year)
—————— Name    BOOT: Boot area

WMON 25OCT2010 V1.0:6100 —————— Checksum
—————— Version
—————— Creation date (Day-Month-Year)
—————— Name    WMON: (WLAN) HTML area

FONT   5600 —————————————— Checksum of font area

KANJI   NONE:  0000 —————— Checksum of bit map Kanji ROM for Gothic font
—————— NONE:   No Kanji ROM installed
GOTHIC: Bit map Kanji ROM for Gothic font installed

NONE:   0000 —————— Checksum of bit map Kanji ROM for Mincho font
(or Chinese Kanji)
—————— NONE:   No Kanji ROM installed
MINCHO: Bit map Kanji ROM for Mincho font installed
CHINESE: Bit map Kanji ROM for
                              Chinese Kanji installed

EEPROM        256B —————— 256B: The data of checking area can be read/write
correctly.
Alphanumeric character is capacity of EEPROM.
NG: The data of checking area cannot be read/write correctly.
—————— Memory for backup

SDRAM 32MB ———————————— Capacity of SDRAM
—————— Memory for system and drawing

Sensor check details

The value of non-installed sensor is unfixed.

SENSOR1 0 0 0 0 0 0 0 0 , 0 0 0 0 0 0 0 0

Thermal head open sensor
1: The head is closed.
(When the print head is unlocked, no printing performed.)

Thermal head-up sensor
1: The head is lowered.
(When the print head is lifted, no printing performed.)

Cutter home position sensor
0: Home position
1: Outside the home position

Rewinder overflow sensor
0: Normal
1: Overflow

Ribbon take-up motor sensor
0: Outside the slit
1: Inside the slit

Ribbon feed motor sensor
0: Outside the slit
1: Inside the slit

Blank (Fixed to 0)

Strip sensor (Peel-off sensor)
0: Label is not present.
1: Label is present.
(When the strip sensor is not installed, the flag is set to "1".)

Blank (Fixed to 0)

SENSOR2        [H]20˚ C [A]22˚ C

                                         Ambient temperature sensor status
                                         (0 to 86 °C, --°C if it cannot be detected)
                             Thermal head temperature sensor status (0 to 86 °C)

        [R]4.2V [T]2.5V [E]2.7V

                                       Reflective sensor status for detecting
                                       the ribbon end state (0.0 to 5.0 V)
                             Transmissive sensor status (0.0 to 5.0 V)
                       Reflective sensor status (0.0 to 5.0 V)

        NOTE: For the B-EX4D2, the status of the ribbon end sensor is always 0.0V.

PE LV.          [R]1.8V [T]2.5V

                                    PAPER END level of the transmissive sensor (0.0 to 5.0 V)
                       PAPER END level of the reflective sensor (0.0 to 5.0 V)

M THRE.        [R]1.8V [T]2.5V

                                    Manually set threshold for the transmissive sensor (0.0 to 5.0 V)
                       Manually set threshold for the reflective sensor (0.0 to 5.0 V)

HEAD         [RANK] 7        305DPI ——— Mounted print head resolution
                                           (203DPI / 305DPI)
                       Thermal head resistance rank

| | B-EX4T1-G B-EX6T2-G (203dpi) | B-EX4T2-G B-EX4D2-G (203dpi) | B-EX4T1-T (305dpi) | B-EX4T2-T B-EX6T2-T (300dpi) | B-EX4T2-H (600dpi) |
|---|---|---|---|---|---|
| Resistance rank | Average resistance (ohm) | | | | |
| 0 | 704 to 728 | 680 to 710 | 880 to 910 | 850 to 886 | 1700 to 1775 |
| 1 | 729 to 752 | 711 to 740 | 911 to 940 | 887 to 924 | 1776 to 1850 |
| 2 | 753 to 776 | 741 to 770 | 941 to 970 | 925 to 962 | 1851 to 1925 |
| 3 | 777 to 800 | 771 to 800 | 971 to 1000 | 963 to 1000 | 1926 to 2000 |
| 4 | 801 to 824 | 801 to 830 | 1001 to 1030 | 1001 to 1038 | 2001 to 2075 |
| 5 | 825 to 848 | 831 to 860 | 1031 to 1060 | 1039 to 1076 | 2076 to 2150 |
| 6 | 849 to 872 | 861 to 890 | 1061 to 1090 | 1077 to 1114 | 2151 to 2225 |
| 7 | 873 to 896 | 891 to 920 | 1091 to 1120 | 1115 to 1150 | 2226 to 2300 |

LAN MAC        11-22-33-44-55-66

                             MAC Address for wired LAN

Expansion I/O check

EXP.I/O NG
        └──────────── OK: Normal data
                      NG: Abnormal data or the loop-back jig is not connected.
        └──────────────── Expansion I/O

Connect the cable as illustrated below, and then check the high output/high input, low output/low input.



R = 300 Ohms
Connector: FCN-781P024-G/P

Internal serial I/F check

EX.232C NG
        └──────────── OK: Normal data
                      NG: Abnormal data or the loop-back jig is not connected.
        └──────────────── Internal serial interface

External serial I/F check (Supported only by the B-EX4T1-TS25-R V2.0 or later)

SIO    NG (0111)
              └──────────── Bit configuration (x3x2x1x0)
                                x0: Fixed to 1
                                x1: Fixed to 1
                                x2: Fixed to 1
                                x3: Presence of the optional board (0: RS-232C PC board not installed)
                                                                    (1: RS-232C PC board installed)
              └──────────── OK: Normal data
                            NG: Abnormal data or loop-back jig is not connected.
                            External serial interface

RFID module check (U2/U4 module series only)


RFID OK #00RV972 (EU0) R01 ───────── Module revision (U2 series only)

Destination

RFID module version

OK: Normal state

NG: Erroneous state

RFID module

JP: Japan
EU0: Europe
US: North America
CN2: China
AU: Australia
KR2: Korea
TW: Taiwan
IN0: India


RFID OK #10A A0 0 (EU0) R00 ───────── Module revision (U4 series only)

Destination

RFID module version

OK: Normal state

NG: Erroneous state

RFID module

EU0: Europe
US: North America (Prohibited)
AU: Australia (Prohibited)
KR2: Korea
TW: Taiwan (Prohibited)
CN2: China
IN0: India (Prohibited)


Module versions and LCD message

B-EX700-RFID-U2-US-R

| Version | LCD message |
| --- | --- |
| R02 | US, KR2, AU, TW (Use of AU and TW is prohibited.) |

B-EX700-RFID-U2-EU-R

| Version | LCD message |
| --- | --- |
| R11 | EU0, IN0 (Use of IN0 is prohibited.) |

B-EX700-RFID-U2-R

| Version | LCD message |
| --- | --- |
| R00 | JP |

B-EX700-RFID-U4-US-R

| Version | LCD message |
| --- | --- |
| R00 | KR2, CN2 (Use of CN2 is prohibited.) |

B-EX700-RFID-U4-EU-R

| Version | LCD message |
| --- | --- |
| R00 | EU0 |

U4 module preinstall model (B-EX4T1/EX4T2-GS18/TS18-CN-R)

| Version | LCD message |
| --- | --- |
| R00 | CN2, KR2, (Use of KR2 is prohibited.) |

Wireless LAN mount check

WLAN    NG
```
              └──────────── OK: Mounted
                            NG: Not mounted or setting of wireless LAN disabled
       └──────────────────── Wireless LAN
```
MAC    00-11-22-33-44-55
```
   └────────────────────── Wireless LAN MAC address (Printed only when WLAN is mounted.)
```

RTC mount check

RTC    NG
```
           └────────────── OK: Mounted. Print date and time if mounted (YY-MM-DD hh:mm:ss)
                           NG: Not mounted
   └──────────────────────── RTC
```

USB memory mount check

USB MEMORY NG
```
             └──────────── OK: Mounted
                           NG: Not mounted
   └──────────────────────── USB memory
```

BASIC program check

BASIC M NONE
```
         └────────────── NONE: No program installed
                         Version: Program installed
   └───────────────────── BASIC main program
```
BASIC S NONE
```
         └────────────── NONE: No program installed
                         Version: Program installed
   └───────────────────── BASIC system program
```

### 8.3.3 HEAD CHECK

The print head check procedure is the same as that for the maintenance counter data. 8.3.1 MAINTENANCE CONT.

The following table shows the menu structure from the top menu of the system mode to HEAD CHECK.

| MENU ITEM | Display pattern and key operation |
|---|---|
| SYSTEM MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     <1>DIAG. | |
|         HEAD CHECK | 7.3 INFORMATION DISPLAY |

| While checking | |
|---|---|
| HEAD CHECK<br><br>CHECKING | Displays "CHECKING". |
| **In the case of normal end** | |
| HEAD CHECK<br><br>NOMAL END | Displays "NORMAL END" |
| **When broken dots are detected.** | |
| HEAD CHECK<br><br>HEAD ERROR<br>   2/1824 dots<br><br>HEAD CHECK<br><br>HEAD ERROR<br>   2/ 832 dots | The ONLINE LED turns off and the ERROR LED turns on.<br>Displays the number of broken dots in the format of the number of broken dots out of the total number of dots.<br>The total number of dots is right-aligned. |

## 8.4 PARAMETER SET

Contents of the PARAMETER SET menu.

| MENU ITEM | Display pattern and key operation |
|---|---|
| SYSTEM MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     <2>PARAMETER SET | |
|         PRINTER SET | |
|         SOFTWARE SET | |
|         PANEL | |
|         PASSWORD | |

### 8.4.1 PRINTER SET

Contents of PRINTER SET submenu.

| MENU ITEM | Display pattern and key operation |
|---|---|
| SYSTEM MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     <2>PARAMETER SET | |
|       PRINTER SET | |
|         MEDIA LOAD | |
|         FORWARD WAIT | |
|           FORWARD WAIT POS. | 7.2 VALUE SETTING DISPLAY |
|         FW/BK ACT. | 7.1 LIST BOX WITH SCROLLBAR |
|         HU CUT/RWD. | |
|         RBN SAVE | |
|         PRE PEEL OFF | |
|         BACK SPEED | |
|         TYPE OF RIBBON<br>**NOTE**: This parameter is available only to the B-EX4T2 and B-EX6T2. | |

## 8.4.1.1 MEDIA LOAD

This function is enabled only when the sensor type is set to other than "None".

・ OFF          Media loading function is disabled (Same as feed by depression of the [FEED] key)

・ STD          When the [FEED] key is pressed after the printer is tuned on, reset by a batch reset command, or the print head is closed, the printer detects the next gap/black mark and feeds the media from the sensor to the print start position.

・ ECO          When the [FEED] key is pressed after the printer is reset by a batch reset command or the print head is closed, the printer feeds the media to detect the next gap/black mark and stops the media at the print start position.  At this time, the feed length between the detected gap/black mark and the home position of the media nearest from the print head is calculated based on the registered media pitch.

・ ECO+Bfeed   After performing the action of the above-mentioned ECO, the printer feeds the media backward for the label pitch length while raising the print head if the following conditions are satisfied.

NOTE: Since the head-up function is not available to the B-EX4T2, B-EX6T2, and B-EX4D2, the setting and the printer behavior will be automatically changed to "ECO" even if "ECO+Bfeed" is selected for these models.

| Hardware | Optional ribbon saving module (solenoid) is installed. |
|---|---|
| Parameter | RBN SAVE parameter is set to TAG or LABEL. |
| Operation | Media pitch falls between 20mm and 100mm.<br>The previous issue mode was Batch. (The issue mode is not reset by power off or a printer reset.) |
| Caution | Even if the hardware requirement is not satisfied (the optional ribbon saving module is not installed), the printer feeds the media backward when the other requirements are satisfied.  However, this operation is not guaranteed as it is outside of the specification. |

## 8.4.1.2 FORWARD WAIT

・ OFF          Disables the auto forward feed wait
・ ON           Enables the auto forward feed wait

## 8.4.1.3 FORWARD WAIT POS.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 5.0 | -5.0 | 0.1 | Decimal | Exist | 2 | 1 | None | mm |

・ + (Plus)     Increases the forward feed amount.
・ - (Minus)    Decreases the forward feed amount.

NOTES:
1. If the pitch of the media used for the previous issue was less than 20mm, the forward wait will not be activated regardless of the parameter setting
   <Supplement> In the case labels with the different pitch (less than 20mm and 20mm or longer) are alternately placed in one label roll, the forward wait is not activated for the labels with the pitch of less than 20mm. Therefore it stays at the print stop position without being fed backward. Before the next label with the pitch of 20mm or larger is printed, however, it is automatically fed backward along with the previously printed label. This may cause the print data to be printed on the previous label.

2. The media will stay at the forwarded position even if the power is turned off/on, the printer is reset, or the print head is opened/closed.


## 8.4.1.4 FW/BK ACT.

- ・ MODE1      The printer waits for next issue with 13.7-mm media forwarded.
- ・ MODE2      When the thermal transfer method and cut issue are selected, the printer feeds 6-mm media backward, then waits for next issue with 3-mm media forwarded.

        NOTE: Before the printer starts printing (feed), it feeds the media for 3 mm from this position and temporarily stops. The feed speed for this 3-mm distance to the home position is the max. speed that can be accelerated from the previous speed (See the following). After the temporary stop, the printer prints or feeds the media at the specified speed.

            203-dpi/600-dpi model: 6 ips
            300-dpi/305-dpi model: 5 ips

        * Except for the multi-step acceleration area for short-pitch labels, the print speed will be accelerated up to the specified speed when the media has not been forwarded.

## 8.4.1.5 HU CUT/RWD.

Whether or not to activate the head up action in the cut issue or to use the Rewinder in the batch or strip issue is selected.

* The print head may not be raised depending on the rise of the solenoid's temperature.

- ・ OFF      Head up cut is not performed or the Rewinder is not used.
- ・ ON      Head up cut is performed or the Rewinder is used.

NOTE: Since the head-up function is not available to the B-EX4T2, B-EX6T2, and B-EX4D2, this parameter is to choose whether to use the Rewinder or not. The head-up operation is fixed to OFF. .


## 8.4.1.6 RBN SAVE

- ・TAG      Enabled (When the head lever is set to TAG position)
- ・LABEL      Enabled (When the head lever is set to Label position)
- ・OFF      Disabled.
- ・TAG2 [NOTE3]:      Enabled (When the head lever is set to TAG position)
- ・LABEL2 [NOTE3]:  Enabled (When the head lever is set to Label position)

NOTES:
1. If this parameter is set to "Enabled" without the ribbon saving module not installed, the ribbon slacks and a print failure occurs.   Care must be taken when setting this parameter.
Also, the ribbon saving option shall be selected depending on the head lever position.   Incorrect setting may disable the proper ribbon saving function.
2. Even if the "TAG" or LABEL" is selected for the B-EX4T2, B-EX6T2, or B-EX4D2, the setting and the printer behavior will be automatically changed to "OFF" because the head-up function is not available to these models.
3. TAG2 and LABEL2 are supported only by the B-EX4T1-TS25-R V2.0 or later.   The difference between "ON:TAG" and "ON:TAG2", and between "ON:LBL" and "ON:LBL2", respectively, is the distance of non-print area where a ribbon save is performed. (In the case of 8 ips or faster)

### 8.4.1.7 PRE PEEL OFF

・OFF Disables pre peel off
・ON Enables pre peel off

NOTE:
Pre peel off is automatically enabled when the print speed is set to 10 ips or faster for the strip issue.
However, the print speed is corrected depending on the EX I/O parameter setting, as follows.
▪ EXI/O: TYPE 1 (Standard)
203-dpi model: 10 ips
300-dpi/305-dpi model: 8 ips
▪ EX I/O: TYPE 2 (Inline)
Specified speed
Accordingly, when the print speed is set to 8 ips or less, pre peel off is enabled only when this parameter is set to ON.

### 8.4.1.8 BACK SPEED

・STD 3 ips
・LOW 2 ips

### 8.4.1.9 TYPE OF RIBBON

・CSO Outside wound ribbon
・CSI Inside wound ribbon

NOTE: This parameter is available only to the B-EX4T2 and B-EX6T2.

## 8.4.2 SOFTWARE SET

Contents of SOFTWARE SET menu

| MENU ITEM | | | | | Display pattern and key operation |
|---|---|---|---|---|---|
| SYSTEM MODE | | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <2>PARAMETER SET | | | | |
| | | SOFTWARE SET | | | |
| | | | FONT CODE | | |
| | | | ZERO FONT | | |
| | | | CODE | | |
| | | | | MANUAL | 7.2 VALUE SETTING DISPLAY |
| | | | PEEL OFF STATUS | | 7.1 LIST BOX WITH SCROLLBAR |
| | | | USB I/F STATUS | | |
| | | | FEED KEY | | |
| | | | KANJI CODE | | |
| | | | EURO CODE | | 7.2 VALUE SETTING DISPLAY |
| | | | AUTO HD CHK | | 7.1 LIST BOX WITH SCROLLBAR |
| | | | WEB PRINTER | | |
| | | | RBN NEAR END | | |
| | | | EX.I/O | | |
| | | | LBL/RBN END | | |
| | | | MAXI CODE | | |
| | | | XML | | |
| | | | THRESHOLD SELECT | | |
| | | | | REFLECT | |
| | | | | TRANS. | |
| | | | ENERGY TYPE | | |
| | | | | TRANSFER | |
| | | | | DIRECT | |
| | | | PW SAVE TIME | | |

## 8.4.2.1 FONT CODE

・PC-850
・PC-852
・PC-857
・PC-8
・PC-851
・PC-855
・PC-1250
・PC-1251
・PC-1252
・PC-1253
・PC-1254
・PC-1257
・LATIN9
・Arabic
・PC-866
・UTF-8

## 8.4.2.2 ZERO FONT

・0              No slash used
・Ø              Slash used

NOTE: The following fonts do not support a zero with a slash.   Therefore, even if a zero with a slash
is selected, a zero without a slash is used.
[Bit map fonts]
OCR-A, OCR-B, GOTHIC725 Black, Japanese Kanji, Chinese
[Outline fonts]
Price fonts 1, 2, and 3, DUTCH801 Bold, BRUSH738 Regular, GOTHIC725 Black,
True type font

## 8.4.2.3 CODE

・AUTO
・{,|,}
・ESC,LF,NUL
・MANUAL

### 8.4.2.4 MANUAL

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 0xFF | 0x00 | 1 | Hex decimal | None | 2 | 0 | None | h |

・CODE1

・CODE2

・CODE3


### 8.4.2.5 PEEL OFF STATUS

・OFF          Disabled

・ON          Enabled


### 8.4.2.6 USB I/F STATUS

・OFF          Disables sending a response via USB.

・ON          Enables sending a response via USB.

NOTE: Regardless of the setting of this parameter, the status indicating the end of issue is automatically returned. The following are the commands related to the status.

　　　　[WS, WB, or WN command]

　　　　● In the case the USB and other interface cables are connected to the printer:

　　　　　Whether a status is returned or not depends on the setting of this parameter.

　　　　　Example)  When this parameter is set to ON and a WS or WB command is sent to the printer via LAN, the printer returns the status via both LAN and USB.

　　　　● In the case only the USB cable is connected to the printer:

　　　　　A status will be returned regardless of the setting of this parameter.

　　　　[Status-related commands other than WS and WB]

　　　　　Whether a status is returned or not depends on the setting of this parameter.


### 8.4.2.7 FEED KEY

・FEED          Feeds one label.

・PRINT          Prints data in the image buffer


### 8.4.2.8 KANJI CODE

・TYPE1          Windows code

・TYPE2          Original code


### 8.4.2.9 EURO CODE

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 0xFF | 0x20 | 1 | Hex. | None | 2 | 0 | None | h |

### 8.4.2.10 AUTO HD CHK

・OFF            Disables the auto print head check
・ON             Enables the auto print head check


### 8.4.2.11 WEB PRINTER

・OFF            Disables WEB printer function
・ON INT         Enables WEB printer function (Internal memory is used)
・ON EXT         Enables WEB printer function (External memory is used)


### 8.4.2.12 RBN NEAR END

・OFF            Ribbon near end is not detected.
      ・30m         Ribbon near end is detected when the remaining ribbon is 30-m long (Equivalent to ribbon diameter of 38 mm)
      ・70m         Ribbon near end is detected when the remaining ribbon is 70-m long (Equivalent to ribbon diameter of 43 mm)

NOTE: Since a detected remaining ribbon length has some margin of error, use the specified length as a guide.


### 8.4.2.13 EX.I/O

・TYPE1         Standard specification
・TYPE2         In-line specification

## 8.4.2.14 LBL/RBN END

- ・TYPE1      When a label end or ribbon end status is detected, the printer stops immediately.
- ・TYPE2      When a label end or ribbon end status is detected, the printer prints the current label as far as possible, then stops.

TYPE1:

When a label end or ribbon end is detected in the middle of printing, printing is immediately stopped. When the printing is restarted, first the initial feed is performed, then the printer starts printing from the unfinished label.

TYPE2:

TYPE 2 is available only when the ribbon saving function is set to OFF. When the ribbon saving is enabled, TYPE 1 will be automatically performed regardless of the selection.

[Label end]

When a label end is detected in the middle of printing, the printer completes the half-finished label and stops when the next label is at the home position, displaying the error message "NO PAPER    X". (*"X" indicates the remaining number of labels.*) The remaining number of labels = [Specified number of labels] − [The number of finished labels including half-finished one]

If a label end is detected while the specified last label is printed, the position of "X" will be blank.

When the printing is restarted, first the initial feed is performed, and then the printer starts printing from the next label. In case of the label end while the specified last label is printed, only the initial feed is performed, and if the status response is set to ON, an issue end status is sent following a feed end status.

[Ribbon end]

When a ribbon end is detected when the unfinished label length is 30 mm or more, printer prints for 20 mm and stops printing, displaying an error message "NO RIBBON    X". ("X" indicates the remaining number of labels.)

The remaining number labels = [Specified number of labels] − [The number of finished labels] − 1

If a ribbon end is detected while the specified last label is printed, the position of "X" will be blank.

When the printing is restarted, first the initial feed is performed, and then the printer starts printing from the next label. In case of the ribbon end while the specified last label is printed, only the initial feed is performed.

Example of TYPE2

[Case 1]  Specified number of labels = 5,

A label end is detected while the 3rd label is printed.

(1st)(2nd)(3rd)
↑

After issuing 3rd label completely, the printer stops printing, displaying "NO PAPER    2".

When printing is restarted, first the initial feed is performed, then 4th and 5th labels are printed. Finally, all of 5 labels have been finished.

[Case 2]  Specified number of labels = 5,

A ribbon end is detected while the 3rd label is printed.    Unfinished label length is 30 mm or more.

(1st)(2nd)(3rd)
↑

After the 3rd label is printed for 20 mm, the printer stops printing, displaying "NO RIBBON    2".

When printing is restarted, first the initial feed is performed, then 4th and 5th labels are printed. Finally, 1st, 2nd, 4th, and 5th labels have been finished.

[Case 3]  Specified number of labels = 5,

A ribbon end is detected while the 3rd label is printed.    Unfinished label length is less than 30 mm.

(1st)(2nd)(3rd)
↑

After issuing 3rd label completely, the printer stops printing, displaying "NO RIBBON    2".

When printing is restarted, first the initial feed is performed, then 4th and 5th labels are printed. Finally all of 5 labels have been finished.


## 8.4.2.15  MAXI  CODE
・TYPE1              Compatible with the current version
・TYPE2              Special specification

The mode specified by the command may be different from the actual mode, depending on the status of this parameter.    Also, the data transmission method differs partly.

For details, refer to the B-EX Series External Equipment Interface Specification


## 8.4.2.16  XML
・OFF                Disables XML function
・STD                Standard specification
・ORACLE            Specification for Oracle
・SAP                Specification for SAP
・STD EXT            Standard specification (external memory is used)
・ORACLE EXT      Specification for Oracle (external memory is used)
・SAP EXT          Specification for SAP (external memory is used)

## 8.4.2.17 THRESHOLD SELECT
・REFLECT          Reflective sensor
・TRANS.           Transmissive sensor

## 8.4.2.17.1 REFLECT
・MANUAL SET        Threshold set in the threshold mode takes effect.
・COMMAND SET     Threshold set by command takes effect.

## 8.4.2.17.2 TRANS.
・MANUAL SET        Threshold set in the threshold mode takes effect
・COMMAND SET     Threshold set by command takes effect.

## 8.4.2.18 ENERGY TYPE
This parameter is intended to make the printer perform appropriate printing for the supplies to be used. Use of a different supply from the setting may cause poor printing.
For details of the appropriate settings, refer to the Supply Specification.

・TRANSFER
・DIRECT

## 8.4.2.18.1 TRANSFER

<B-EX4T1-G/T>
・Semi resin1          Semi-resin 1
・Semi resin2          Semi-resin 2
・Resin1             Resin 1
・Resin2             Resin 2
・Resin3             Resin 3 ("Resin3" shall not be selected for the B-EX4T1-T model.)
・Reserve2 to Reserve6   Reserved

<B-EX4T2-G/T firmware version C1.0C or before and B-EX6T2-G/T>
・Wax1              Wax 1
・Wax2               Wax 2
・Semi resin1          Semi-resin 1
・Semi resin2           Semi-resin 2
・Resin1             Resin 1
・Reserve1 to Reserve5   Reserved

<B-EX4T2-G/T firmware version C1.0D>
・Wax1              Wax 1
・Wax2               Wax 2
・Semi resin1          Semi-resin 1
・Semi resin2           Semi-resin 2
・Resin1             Resin 1
・Wax3              Wax 3
・Semi resin3          Semi resin 3
・Reserve1 to Reserve3   Reserved

<B-EX4T2-G/T firmware version C1.0E or later, and B-EX4D2-G>

・Wax1      Wax 1

・Wax2      Wax 2

・Semi resin1    Semi-resin 1

・Semi resin2    Semi-resin 2

・Resin1      Resin 1

・Wax3      Wax 3

・Semi resin3    Semi resin 3

・Resin2      Resin 2

・Reserve1 to Reserve2  Reserved

NOTE: Since the B-EX4D2 is a direct thermal printer, this parameter is not used for actual printing.

<B-EX4T2-H>

・Resin1      Resin 1

・Resin2      Resin 2

・Reserve1 to Reserve8  Reserved

### 8.4.2.18.2  DIRECT

・Standard     Standard

・Reserve1 to Reserve9  Reserved

### 8.4.2.19  PW  SAVE  TIME

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 240 | 1 | 1 | Decimal | None | 3 | 0 | None | Min. |

## 8.4.3 PANEL

Contents of PANEL menu

| MENU ITEM | | | | | Display pattern and key operation |
|---|---|---|---|---|---|
| SYSTEM MODE | | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <2>PARAMETER SET | | | | |
| | | PANEL | | | |
| | | | LCD LANGUAGE | | |
| | | | LCDISPLAY | | |
| | | | | MACHINE NAME | |
| | | | | PRINT PAGE | |
| | | | | IP ADDRESS | |
| | | | CONTRAST | | 7.2 VALUE SETTING DISPLAY |

### 8.4.3.1 LCD LANGUAGE
・ENGLISH

・GERMAN

・FRENCH

・DUTCH

・SPANISH

・JAPANESE

・ITALIAN

・PORTUGUESE

・SIMP. CHINESE

・KOREAN


NOTES:
1. In the printer modes other than online, the language displayed on panel is Japanese when JAPANESE is selected, and ENGLISH WHEN ENGLISH, GERMAN, FRENCH, DUTCH, SPANISH, ITALIAN, PORTUGUESE or SIMP. CHINESE is selected.
2. KOREAN is supported from the following printer firmware versions:
   C1.0I for the B-EX4T1-G/T-QM/CN, C1.0F for the B-EX4T2-G/T-QM/CN


### 8.4.3.2 MACHINE NAME
・OFF          Model name is hidden.

・ON          Model name is displayed.


### 8.4.3.3 PRINT PAGE
・OFF          The number of labels printed is hidden.

・ON          The number of labels printed is displayed.


### 8.4.3.4 IP ADDRESS
・OFF          IP address is hidden.

・ON          IP address is displayed.

### 8.4.3.5 CONTRAST

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 50 | 24 | 2 | Decimal | None | 2 | 0 | Enabled | None |

・+ (Plus)       High

・- (Minus)    Low


## 8.4.4 PASSWORD

Menu structure of PASSWORD menu

| MENU ITEM | | | Display pattern and key operation |
|---|---|---|---|
| SYSTEM MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <2>PARAMETER SET | | |
| | | PASSWORD | |
| | |     PASSWORD | 7.2 VALUE SETTING DISPLAY |

PASSWORD

   ・OFF     Password is not set.

   ・ON      Password is set.


PASSWORD

Usable input value for password

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| F | 0 | 1 | Hex. | None | 1 | 0 | None | None |

### 8.4.4.1 System mode and user system mode start screen when password is enabled

When the password is enabled, the password input screen is displayed at the time the system mode or user system mode is started.

Password input for system mode

| Display | Procedure |
|---|---|
| PASSWORD<br><br>0 0 0 0 | Turn on the printer while holding down the [FEED] and [RESTART] keys at the same time.<br>The password input screen is displayed. |
| | Input the password. |
| | The printer enters the system mode. |
| When a wrong password is input or the [CANCEL] key or [MODE] key is pressed | |
| PASSWORD<br><br>1 0 0 0<br><br>Password Invalid | Password invalid message is displayed. |
| A wrong password was entered consecutively for 3 times. | |
| | The printer starts in online mode. |

Password input for user system mode

| Display | Procedure |
|---|---|
| PASSWORD<br><br>0 0 0 0 | Turn on the printer, press the [PAUSE] key to place the printer in pause state.   Then, hold down [RESTART] key or [MODE] key for 3 seconds.<br>The password input screen is displayed. |
| | Input the password. |
| | The printer enters the user system mode. |
| When a wrong password is input or the [CANCEL] key or [MODE] key is pressed | |
| PASSWORD<br><br>1 0 0 0<br><br>Password Invalid | Password invalid message is displayed. |
| A wrong password was entered consecutively for 3 times | |
| PASSWORD INVALID<br>Turn the printer<br>off, then on again.<br>Help▶ | The printer locks. Turn off printer and back to on. |

・ If you forgot the programmed system mode password, disable it with @010 command.

## 8.5 ADJUST SET

Contents of ADJUST SET menu

| MENU ITEM | | | Display pattern and key operation |
|---|---|---|---|
| SYSTEM MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <3>ADJUST SET | | |
| | | FEED ADJ. | 7.2 VALUE SETTING DISPLAY |
| | | CUT ADJ. | |
| | | BACK ADJ. | |
| | | X ADJUST | |
| | | TONE ADJ. (TRANS.) | |
| | | TONE ADJ. (DIRECT) | |
| | | RBN ADJ.<FW> | |
| | | RBN ADJ.<BK> | |
| | | THRESHOLD <REFL.> | |
| | | THRESHOLD <TRANS.> | |

### 8.5.1 FEED ADJ.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|------------|------------|------|---------|------|---------------|---------------|-----------|-----------------|
| 50.0 | -50.0 | 0.1 | Decimal | Exist | 2 | 1 | None | mm |



NOTE:

A value which is larger than the media pitch (FEED ADJ. ≥ Media pitch) must not be set.  If the set fine adjustment value causes the printer to feed the media backward from the print stop position to the next print start position, the printer operation is not guaranteed.

### 8.5.2 CUT ADJ

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 50.0 | -50.0 | 0.1 | Decimal | Exist | 2 | 1 | None | mm |

+0.0 mm

ABC — Cut position

+3.0 mm

ABC — Cut position

-3.0 mm

ABC — Cut position

Paper feed direction

[Procedure for label having label pitch of less than 25.4 mm when the disc cutter is used]

The minimum label pitch of the label which can be cut in normal use is 25.4 mm. When a label having a label pitch of less than 25.4 mm is used (although it is out of specifications), the edge of the label is caught by the edge of the thermal head during a back feed to the home position after cutting the gap area between labels. Therefore, the label may not be fed back to the proper home position. By performing either method below, the problem will be solved.

[Method 1]  Lift the head.

When the following conditions are all met, the cut operation is as follows.

Head lifted → Forward feed to the cut position → Head lowered → Cut →
Head lifted → Reverse feed to the home position → Head lowered

Conditions:  Issue Command, Feed Command, and Eject Command received.
Label pitch of 25.4 mm or less, cut performed, transmissive sensor designated, cut position fine adjustment of ±10.0 mm or less, and issue mode "C"

* The head is lifted/lowered only when the optional ribbon saving module is mounted and the ribbon saving function is set to ON with the parameter setting menu. When the ribbon saving module is not installed, use Method 2 since the print head is not lifted/lowered.

*NOTES:*   *1. If the bottom edge of the last label advances past the feed roller while the print head is lifted during label feed to cut, the sensor may not be able to detect an error even if the label cannot be fed any more.*

  *2. If the head-up solenoid temperature is high when a cut issue is about to be performed with the head lifted, the head may not be lifted.*

[Method 2]  Adjust the cut position fine adjustment value.

When this procedure is used, one or more printed labels are left between the head and the cutter.   Therefore, these labels need to be removed by an issue or a label feed.

(a)  Cut position fine adjustment value calculation

The cut position fine adjustment value can be calculated using the following method. If a back feed to the proper home position cannot be performed using this value, the cut position needs to be adjusted with any value.

$$\text{Cut position fine adjustment value} = (\text{Number of labels left between head and cutter}) \times (\text{Label pitch})$$

$$= \left( \frac{32.8 \text{ mm}}{\text{Label pitch}} \right) \times (\text{Label pitch})$$

\* Any decimal remainders are rounded off.

Ex)  Label pitch: 30.0 mm

$$\text{Cut position fine adjustment value} = \left( \frac{32.8 \text{ mm}}{30.0 \text{ mm}} \right) \times (30.0 \text{ mm})$$

$$= 1 \times 30.0 \text{ mm}$$
$$= +30.0 \text{ mm}$$

（b）Operation example

Issue count: 2, Cut interval = 1

Cut position          Head position
▼                     ▼

| | | | |
|---|---|---|---|
| | | A | B | (1) Idling |

| | A | B | C | (2) Completes printing the first label (A). |

| A | B | C | (3) Feeds the label to the cut position, then cuts the gap in front of label (A). |

| | A | B | C | (4) Back feeds to the home position. |

| A | B | C | (5) Completes printing the second label (B). |

| A | B | C | (6) Feeds the label to the cut position, then cuts the gap in front of label (B). |

| A | | B | C | (7) Back feeds to the home position. |

| A | B | C | (8) To eject label (B), feeds the third label (C). |

| A | B | C | (9) Feeds the label to the cut position, then cuts the gap at the front of label (C). |

| B | | C | (10) Back feed to the home position. |
| A | | | |

[Procedure for label having less than the min. label pitch for each issue speed when the rotary cutter is used]

When the following conditions are all met, the cut operation for the last label to be cut is as follows.

Forward feed to the cut position → Cut while feeding → Feed stops →
Head lifted → Reverse feed to the home position → Head lowered

Conditions:  Issue Command, Feed Command, and Eject Command received.
Label pitch: Less than the min. label pitch for each issue speed,
cut performed, transmissive sensor designated, cut position fine adjustment
of ±10.0 mm or less, and issue mode "C"

* For the Issue Command, this procedure is effective only when the next Issue Command is not received at the last label to be cut.

* The print head is lifted/lowered only when the optional ribbon saving module is mounted and the ribbon saving function is set to ON with the parameter setting menu. When the ribbon saving module is not installed, the print head is not lifted or lowered.

NOTES:  1.  If the bottom edge of the last label advances past the feed roller while the print head is lifted during label feed to cut, the sensor may not be able to detect an error even if the label cannot be fed any more.

2.  If the head-up solenoid temperature is high when a cut issue is about to be performed with the head lifted, the head may not be lifted.

[Strip position fine adjustment]

0.0mm

+3.0mm

-3.0mm

4mm

3mm

2mm

Printing in strip issue mode is stopped at the position where the distance from the middle point of the gap between labels to the end of the strip shaft is 4 mm, since the gap between labels is assumed to be 2 mm. When the print stop position is not proper due to a greater gap, the print stop position should be adjusted using the strip position fine adjust function.

### 8.5.3 BACK ADJ.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|------------|------------|------|---------|------|---------------|---------------|-----------|-----------------|
| 9.9 | -9.9 | 0.1 | Decimal | Exist | 1 | 1 | None | mm |

+0.0mm

Print start position
(Home position after a back feed)

+3.0mm

Print start position
(Home position after a back feed)

-3.0mm

Print start position
(Home position after a back feed)

NOTE:   There may be cases where a label is not returned to the home position depending on the print conditions, even if a back feed, of which length is the same as the forward feed, is performed. In issues where any paper sensor is used, if the label pitch length is almost the same as the distance between the thermal print head and the paper sensors (75.5 mm), a label/tag may not be returned to the home position when operations with a back feed (such as cut issues, strip issues, automatic forward feed standby) are performed.  It may result in an error.  In such cases, to prevent an error from occurring, the back feed length should be increased by performing the back feed fine adjustment in the + direction.

### 8.5.4 X ADJUST

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 99.5 | -99.5 | 0.1 | Decimal | Exist | 2 | 1 | None | mm |

```
        ◄───────  ┌───────┐  ───────►
                  │ X Y Z │
                  └───────┘
        −                            +
```

### 8.5.5 TONE ADJ. (TRANS.)

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 10 | -20 | 1 | Decimal | Exist | 2 | 0 | None | Step |

```
+10step        Darker
+9step           ▲
  :              │
+1step           │
+0step         Standard
-1step           │
  :              │
-19step          ▼
-20step        Lighter
```

### 8.5.6 TONE ADJ. (DIRECT)

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 10 | -20 | 1 | Decimal | Exist | 2 | 0 | None | Step |

```
+10step        Darker
+9step           ▲
  :              │
+1step           │
+0step         Standard
-1step           │
  :              │
-19step          ▼
-20step        Lighter
```

### 8.5.7 RBN ADJ.<FW>

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 10 | -15 | 1 | Decimal | Exist | 2 | 0 | None | Step |

The fine adjustment value is not effective for the reverse rotation.
The fine adjustment value for the ribbon take-up motor is limited depending on the print speed.
NOTE: Since the B-EX4D2 is a direct thermal printer, this parameter is displayed but not used for actual printing.

| Print speed | 6 ips or slower | 8 ips | 10 ips or faster |
|---|---|---|---|
| Fine adjustment value | -15 to +10 | -15 to +5 | -15 to 0 |

*1: For the B-EX4T1-TS25-R firmware version V2.0 or later, each time the fine adjustment value is changed by one, the factor changes by 3%, in the case the factor of fine adjustment value "0" is 100%.

| B-EX4T1-TS25-R V2.0 or later | | | |
|---|---|---|---|
| Fine adjustment value | Factor [1] | Fine adjustment value | Factor [1] |
| +10 | 130% | -3 | 91% |
| +9 | 127% | -4 | 88% |
| +8 | 124% | -5 | 85% |
| +7 | 121% | -6 | 82% |
| +6 | 118% | -7 | 79% |
| +5 | 115% | -8 | 76% |
| +4 | 112% | -9 | 73% |
| +3 | 109% | -10 | 70% |
| +2 | 106% | -11 | 67% |
| +1 | 103% | -12 | 64% |
| 0 | 100% | -13 | 61% |
| -1 | 97% | -14 | 58% |
| -2 | 94% | -15 | 55% |

### 8.5.8 RBN ADJ.<BK>

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 10 | -15 | 1 | Decimal | Exist | 2 | 0 | None | Step |

The fine adjustment value is not effective for the reverse rotation.
All fine adjustment values are applicable to every print speed.
NOTE: Since the B-EX4D2 is a direct thermal printer, this parameter is displayed but not used for actual printing.

*1: For the B-EX4T1-TS25-R firmware version V2.0 or later, each time the fine adjustment value is changed by one, the factor changes by 3%, in the case the factor of fine adjustment value "+5" is 100%.

| B-EX4T1-TS25-R V2.0 or later | | | |
|---|---|---|---|
| Fine adjustment value | Factor [*1] | Fine adjustment value | Factor [*1] |
| +10 | 115% | -3 | 76% |
| +9 | 112% | -4 | 73% |
| +8 | 109% | -5 | 70% |
| +7 | 106% | -6 | 67% |
| +6 | 103% | -7 | 64% |
| +5 | 100% | -8 | 61% |
| +4 | 97% | -9 | 58% |
| +3 | 94% | -10 | 55% |
| +2 | 91% | -11 | 52% |
| +1 | 88% | -12 | 49% |
| 0 | 85% | -13 | 46% |
| -1 | 82% | -14 | 43% |
| -2 | 79% | -15 | 40% |

## 8.5.9 THRESHOLD <REFL.>

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 4.0 | 0.0 | 0.1 | Decimal | None | 1 | 1 | None | V |

NOTE: If "0.0 V" is set, the value "0.0 V" is returned to the initial value (1.0 V) when the power is turned OFF then ON.

## 8.5.10 THRESHOLD <TRANS.>

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 4.0 | 0.0 | 0.1 | Decimal | None | 1 | 1 | None | V |

NOTE: If "0.0 V" is set, the value "0.0 V" is returned to the initial value (1.4 V) when the power is turned OFF then ON.

Supplementary explanation

- When the [RESTART] and [FEED] keys are pressed at the same time, the display returns to the system mode menu.
- When the [RESTART] or [FEED] key is held down for 0.5 seconds or more when a fine adjustment value is being set, the printer enters the repeat mode, in which the key is entered repeatedly.
- A changed fine adjustment value is stored in memory by pressing the [PAUSE] key.

- The printer is controlled by the sum of the fine adjustment parameter programmed on the printer and the fine adjustment command from the PC. However, the maximum values for each fine adjustment are as follows:

  Feed fine adjustment ....................................................................±50.0 mm
  Strip position fine adjustment .......................................................±50.0 mm
  Back feed fine adjustment ..............................................................±9.9 mm
  Print density fine adjustment .........................................-20 step to ±10 step
  X-coordinate fine adjustment.........................................................±99.5 mm
  Ribbon motor drive voltage fine adjustment (Take-up) ...........-15 to +10 step
  Ribbon motor drive voltage fine adjustment (Back tension)....-15 to +10 step

- The X-coordinate fine adjustment is performed to fine adjust the X-coordinate of the drawing in the left or right direction. Adjust the X-coordinate in the effective print range. (After the value reaches the coordinate "0", the value remains unchanged even if a subsequent fine adjustment is performed in the negative direction.)
- The X-coordinate fine adjustment is not effective for the self-test results printout (maintenance counter, various parameters, and automatic self-test) and the test print.
- The print density fine adjustment value is +0 step at the time of shipment from the factory.
- The ribbon take-up/back tension motors drive voltage fine adjustment values are the sum of the fine adjustment by the command (from the PC) and the fine adjustment in the system mode (by key operation). The range of fine adjustment is from –15 to +10 for both the ribbon take-up motor and the ribbon back tension motor.
- The print density fine adjustment value is the sum of the fine adjustment by command (from the PC) and the fine adjustment in the system mode (by key operation). The respective max. Fine adjustment values are –20 to +10. The max value for each print speed is as below. When the value exceeds the maximum, it is automatically corrected to the max value.

[Both direct thermal and thermal transfer]

| Speed | B-EX4T1 | | B-EX4T2 | | | B-EX6T2 | | B-EX4D2 |
| --- | --- | --- | --- | --- | --- | --- | --- | --- |
| | 203 dpi | 305 dpi | 203 dpi | 300 dpi | 600 dpi | 203 dpi | 300 dpi | 203 dpi |
| 2 ips | | | | | +10 | | | |
| 3 ips | +10 | +10 | +10 | +10 | +10 | +10 | +10 | +10 |
| 4 ips | | | | | +10 | | | |
| 5 ips | | +10 | | +10 | +10 | | +10 | |
| 6 ips | +10 | | +10 | | +10 | +10 | | +10 |
| 8 ips | | +10 | | +10 | | | +10 | |
| 10 ips | +10 | +10 | +10 | +10 | | +10 | +10 | +10 |
| 12 ips | +10 | +10 | +10 | +10 | | | | +10 |
| 14 ips | +10 | +10 | | | | | | |

## 8.5.11 HDDWNADJ

This is the function to fine adjust the head-down timing.

Fine adjustment of the head-down timing is required to be performed with @008 command, not through key operations on the printer. (For the @008 command, refer to External Equipment Interface Specification for the B-EX Series.)

The factory default is 0 msec., and the adjustment value will not be initialized by a RAM clear.

* This function is supported from the firmware version of V2.0B for the B-EX4T1-TS25-R.

## 8.6 TEST PRINT

Contents of TEST PRINT menu

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <4>TEST PRINT | | | |
| | | PRINT CONDITION | | |
| | | | ISSUE COUNT | |
| | | | PRINT SPEED | |
| | | | SENSOR | |
| | | | PRINT TYPE | |
| | | | ISSUE TYPE | |
| | | | LABEL PITCH | 7.2 VALUE SETTING DISPLAY |
| | | | PAPER FEED | 7.1 LIST BOX WITH SCROLLBAR |
| | | SLANT LINE (1DOT) | | 7.3 INFORMATION DISPLAY |
| | | SLANT LINE (3DOT) | | |
| | | CHARACTERS | | |
| | | BARCODE | | |
| | | NON-PRINTING | | |
| | | FACTORY TEST | | |
| | | AUTO PRINT (TRANS.) | | |
| | | AUTO PRINT (REFL.) | | |

NOTE:   In the case of the B-EX4D2, even if the thermal transfer mode is selected for the PRINT TYPE, it will
be automatically changed to the direct thermal mode when the [ENTER] key is pressed.

### 8.6.1 PRINT CONDITION

This menu enables setting print conditions for test print.


 8.6.1.1 ISSUE COUNT
　・1
　・3
　・5
　・10
　・50
　・100
　・500
　・1000
　・5000

## 8.6.1.2 PRINT SPEED

Selectable printer speed differs depending on the resolution.

| B-EX4T TYPE 1 | | B-EX4T TYPE 2 | | | B-EX6T | | B-EX4D2 |
|---|---|---|---|---|---|---|---|
| 203dpi | 305dpi | 203dpi | 300dpi | 600dpi | 203dpi | 300dpi | 203 dpi |
| 3 ips | 3 ips | 3 ips | 3 ips | 2 ips | 3 ips | 3 ips | 3 ips |
| 6 ips | 5 ips | 6 ips | 5 ips | 3 ips | 6 ips | 5 ips | 6 ips |
| 10 ips | 8 ips | 10 ips | 8 ips | 4 ips | 10 ips | 8 ips | 10 ips |
| 12 ips | 10 ips | 12 ips | 10 ips | 5 ips | | 10 ips | 12 ips |
| 14 ips | 12 ips | | 12 ips | 6 ips | | | |
| | 14 ips | | | | | | |

When the peel-off is selected for the issue mode, the maximum speed is limited to 10 ips.

## 8.6.1.3 SENSOR
・NONE
・TRANS.
・REFLECT
・MANUAL TRANS.
・MANUAL REFL.

## 8.6.1.4 PRINT TYPE
・TRANSFER
・DIRECT

## 8.6.1.5 ISSUE TYPE
・NO CUT
・WITH CUT
・PEEL OFF

## 8.6.1.6 LABEL PITCH

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 999 (*1) 500 (*2) | 5 | 1 | Decimal | None | 3 | 0 | None | mm |

*1: Applicable to the B-EX4T1-T/G, B-EX4T2-T/G and B-EX6T2-T/G.
*2: Applicable to the B-EX4T2-H.

## 8.6.1.7 PAPER FEED
・NO FEED
・FEED

Initial values when turning the power on

| ISSUE COUNT | 1 piece |
|---|---|
| PRINT SPEED | (203 dpi)<br>B-EX4T1-G, B-EX4T2-G, B-EX6T2-G, B-EX4D2-G: 6"/sec. |
| | (300 dpi/305 dpi)<br>B-EX4T1-T, B-EX4T2-T, B-EX6T2-T: 5"/sec. |
| | (600 dpi)<br>B-EX4T2-H: 3"/sec. |
| SENSOR | Transmissive sensor |
| PRT TYPE | B-EX4T1/EX4T2/EX6T2: Thermal transfer<br>B-EX4D2: Direct thermal |
| TYPE | Batch issue |
| LABEL LEN. | 76 mm |
| PAPER | Enabled |

Supplementary explanation:
- Each fine adjustment parameter is effective for test print. However, the X-coordinate fine adjustment is excluded.
- When an error occurs during a test print, the error message is displayed and printing is stopped. The error LED turns on and the online LED turns off.
- The error is cleared by a depression of the [CANCEL] key or [ENTER] key, and the display returns to the test print menu. The error LED turns off and the online LED turns on. Printing is not automatically resumed after the error is cleared.
- The label size greater than the image buffer length cannot be designated. If it is designated, the printer prints data corresponding to the image buffer length then stops, or the printer stops because of an error.
- When the transmissive sensor is selected, the gap between labels shall be 3 mm.

- For the B-EX4T1, the rotary cutter does not support the print speed of 10 ips or faster. When the rotary cutter is mounted (regardless of the cut issue is specified), the print speed is corrected to 8 ips even if 10 ips is selected.
- For B-EX4T1-G, specifying less than 15.0-mm pitch label for 3 ips print speed or less than 30.0-mm pitch label for 6 ips, printing is performed without cut.
- For B-EX4T1-T, specifying less than 15.0-mm pitch label for 3 ips print speed, less than 25.0-mm pitch label for 5 ips, or less than 38.0-mm pitch label for 8 ips, printing is performed without cut.
- In the case of the B-EX4D2, even if the thermal transfer mode is selected for the PRT TYPE, it will be automatically changed to the direct thermal mode.

## 8.6.2 SLANT LINE (1DOT)



1-dot slant line

Magnification of slant line
1-dot slant line（Black area ratio: 16.7%）

## 8.6.3 SLANT LINE (3DOT)



3-dot slant line

Magnification of slant line
3-dot slant line（Black area ratio: 16.7%）

### 8.6.4 CHARACTERS

Gothic + Mincho



Gothic + Chinese

### 8.6.5 BARCODE



### 8.6.6 NON-PRINTING

The printer feeds blank label.

### 8.6.7 FACTORY TEST

### 8.6.8  AUTO PRINT  (TRANS.)

The factory test print is performed on the following conditions.   The parameter settings and the print density fine adjustment value are ignored.

- After each test pattern is printed, the factory test print is performed when the [ENTER] key (or its compatible key) is pressed.
- When the [CANCEL] key (or its compatible key) is pressed, the display returns to the menu.
- Other keys are invalid.

| Print test pattern | Feeding 1 label |
| --- | --- |
| | Printing 3-dot slant lines |
| | Printing barcode |
| | Printing characters |
| Issue count | 5 labels each |
| Print speed | (203 dpi)<br>B-EX4T1-G,  B-EX4T2-G,  B-EX6T2-G,  B-EX4D2-G: 6"/sec. |
| | (300 dpi/305 dpi)<br>B-EX4T1-T, B-EX4T2-T, B-EX6T2-T: 5"/sec. |
| | (600 dpi)<br>B-EX4T2-H: 3"/sec. |
| Sensor type | Transmissive sensor |
| Print method | B-EX4T1/EX4T2/EX6T2: Thermal transfer<br>B-EX4D2: Direct thermal |
| Issue mode | Continuous issue |
| Label pitch | 76 mm |
| Print density fine adjustment value | ±0 |

### 8.6.9  AUTO PRINT (REFL.)

The factory test print is performed on the following conditions.   The parameter settings and the print density fine adjustment value are ignored.

- After each test pattern is printed, the factory test print is performed when the [ENTER] key (or its compatible key) is pressed.
- When the [CANCEL] key (or its compatible key) is pressed, the display returns to the menu.
- Other keys are invalid.

| Print test pattern | Feeding 1 label |
| --- | --- |
| | Printing 3-dot slant lines |
| | Printing barcode |
| | Printing characters |
| Issue piece5 pieces each | 5 labels each |
| Print speed | (203 dpi)<br>B-EX4T1-G,  B-EX4T2-G,  B-EX6T2-G,  B-EX4D2-G: 6"/sec. |
| | (300 dpi/305 dpi)<br>B-EX4T1-T, B-EX4T2-T, B-EX6T2-T: 5"/sec. |
| | (600 dpi)<br>B-EX4T2-H: 3"/sec. |
| Sensor type | Transmissive sensor |
| Print method | B-EX4T1/EX4T2/EX6T2: Thermal transfer<br>B-EX4D2: Direct thermal |
| Issue type | Continuous issue |
| Label pitch | 76 mm |
| Print density fine adjustment value | ±0 |

## 8.7 SENSOR ADJUST

Contents of SENSOR ADJUST menu

| MENU ITEM | | | Display pattern and key operation |
|---|---|---|---|
| SYSTEM MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <<5>SENSOR ADJUST | | |
| | | TEMPERATURE | 7.5   TEMPERATURE DISPLAY |
| | | REFLECT | 7.4 SENSOR ADJUSTMENT DISPLAY |
| | | TRANS. | |
| | | PE REFL./TRANS. | |
| | | RIBBON | |

### 8.7.1 TEMPERATURE

The ambient temperature and print head temperature are displayed.

Only when the temperature is below zero, the symbol of minus (-) is displayed.

The display is updated every 200 msec.

The range of each temperature is below.

| Ambient temperature | -20 to 100 |
|---|---|
| Print head temperature | -20 to 100 |

### 8.7.2 REFLECT

The sensor level of the reflective sensor is registered.

Place the tag paper to be used on the reflective sensor so that the sensor can detect a print area.

The display of the currently detected value is updated every 200 msec.

Hold down the [ENTER] key for 3 seconds or more.

When the registration of the "print area level" is completed, "Adjustment Complete" is displayed and an asterisk (*) is shown on the right side of the voltage.

If the adjustment failed due to sensor failure, "SENSOR ERROR" is displayed and the ERROR LED turns on.

The ERROR LED turns off when the upper hierarchy menu is displayed.

The setting range is as below.

| Reflective sensor | 0.0V to 5.0 V |
|---|---|

### 8.7.3 TRANS.

The sensor level of the transmissive sensor is registered.

Remove some labels and place the backing paper so that the Transmissive sensor can detect it.

The display of the currently detected value is updated every 200 msec.

Hold down the [ENTER] key for 3 seconds or more.

When the registration of the "label gap level" is completed, "Adjustment Complete" is displayed and an asterisk (*) is shown on the right side of the voltage.

If the adjustment failed due to sensor failure, "SENSOR ERROR" is displayed and the ERROR LED turns on.

The ERROR LED turns off when the upper hierarchy menu is displayed.

The setting range is as below.

| Transmissive sensor | 0.0V to 5.0 V |
|---|---|

### 8.7.4  PE  REFL./TRANS.

Paper end level of the transmissive sensor and the reflective sensor is registered.

Remove any media from the media sensor.

The display of the currently detected value is updated every 200 msec.

Hold down the [ENTER] key for 3 seconds or more.

When the registration of the "paper end level" is completed, "Adjustment Complete" is displayed and an asterisk (*) is shown on the right side of the voltage.

If the adjustment failed due to sensor failure, "SENSOR ERROR" is displayed and the ERROR LED turns on. The ERROR LED turns off when the upper hierarchy menu is displayed.

The setting range is as below.

| Reflective sensor | 0.0V to 5.0 V |
|---|---|
| Transmissive sensor | 0.0V to 5.0 V |


### 8.7.5  RIBBON

Ribbon level is registered.

Set the ribbon so that the ribbon end sensor can detect a ribbon area.

The display of the currently detected value is updated every 200 msec.

Hold down the [ENTER] key for 3 seconds or more.

When the registration of the "ribbon level" is completed, "Adjustment Complete" is displayed and an asterisk (*) is shown on the right side of the voltage.

If the adjustment failed due to sensor failure, "SENSOR ERROR" is displayed and the ERROR LED turns on. The ERROR LED turns off when the upper hierarchy menu is displayed.

The setting range is as below.

| Ribbon end sensor | 0.0V to 5.0 V |
|---|---|

NOTE: In the case of the B-EX4D2, the status of the ribbon end sensor is always 0.0V.

## 8.8 RAM CLEAR

Contents of RAM CLEAR menu

<B-EX4T1, B-EX4T2, B-EX6T2>

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <6>RAM CLEAR | | | |
| | | NO RAM CLEAR | | |
| | | MAINTE.CNT CLEAR | | |
| | | | ALL COUNTER | |
| | | | FEED | |
| | | | PRINT | |
| | | | CUT | |
| | | | OTHER | |
| | | PARAMETER CLEAR | | |
| | | | QM TYPE | |
| | | | JA TYPE | |
| | | | CN TYPE | |

<B-EX4D2>

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <6>RAM CLEAR | | | |
| | | NO RAM CLEAR | | |
| | | MAINTE.CNT CLEAR | | |
| | | | ALL COUNTER | |
| | | | FEED | |
| | | | PRINT | |
| | | | CUT | |
| | | | OTHER | |
| | | PARAMETER CLEAR | | |
| | | | QQ TYPE | |
| | | | QM TYPE | |
| | | | CN TYPE | |

### 8.8.1 NO RAM CLEAR

This option is provided for users who access this menu by mistake, and intended to exit from the RAM clear menu without performing any RAM clear.

### 8.8.2 MAINTE.CNT CLEAR

The maintenance counter, including label distance covered, is cleared.

Initial value after maintenance counter clear

| Item | Initial value |
|---|---|
| Label distance covered | 0 km |
| Print distance | 0 km |
| Cut count | 0 |
| Head up/down count | 0 |
| Ribbon motor drive time | 0 hours |
| Head-up solenoid driver time | 0 hours |
| RS-232C hardware error count | 0 |
| System error count | 0 |
| Momentary power interruption count | 0 |

| Display | |
|---|---|
| ALL COUNTER<br><br>CLEAR... | While clearing |
| ALL COUNTER<br><br>COMPLETED<br>Turn off the printer | After the maintenance counter clear is completed |

Turn off the printer when "COMPLETED. Turn off the printer" is displayed after the RAM clear is completed.

### 8.8.3 PARAMETER CLEAR

The parameters settings are cleared.

Destination is selectable for parameter clear. The destination code printed on the top right corner of the maintenance counter printout shows which destination was selected for the parameter clear.

| Display | |
|---|---|
| QM TYPE<br><br>CLEAR... | While clearing |
| QM TYPE<br><br>COMPLETED<br>Turn off the printer | After the parameter clear is completed |

Initial values after clearing the parameters

| Function | QM | QQ | CN |
|---|---|---|---|
| Media Load | OFF | OFF | OFF |
| Forward wait | OFF | OFF | OFF |
| Auto forward/reverse wait fine adjustment value | 0.0mm | 0.0mm | 0.0mm |
| Wait movement | MODE1 | MODE1 | MODE1 |
| HU CUT/RWD. | OFF | OFF | OFF |
| Ribbon save | OFF | OFF | OFF |
| Pre peel-off process | OFF | OFF | OFF |
| Back feed | STD | STD | STD |
| Type of ribbon<br>* This is available only to the<br>B-EX4T2 and B-EX6T2. | CSO | CSO | CSO |

Parameter setting/Software control setting

| Function | QM | QQ | CN |
|---|---|---|---|
| Character code | PC-850 | PC-850 | PC-850 |
| 0 character type | None slash | None slash | None slash |
| Control code | AUTO | AUTO | AUTO |
| Control code (CODE1) | 0x1b | 0x1b | 0x1b |
| Control code (CODE2) | 0x0a | 0x0a | 0x0a |
| Control code (CODE3) | 0x00 | 0x00 | 0x00 |
| Peel-off wait status | OFF | OFF | OFF |
| USB STATUS | OFF | OFF | OFF |
| FEED Key | FEED | FEED | FEED |
| Kanji special code | TYPE1 | TYPE1 | TYPE1 |
| Euro code | 0xb0 | 0xb0 | 0xb0 |
| Auto broken dot check | OFF | OFF | OFF |
| WEB printer | OFF | OFF | OFF |
| Ribbon near end | OFF | OFF | OFF |
| Expansion I/O mode | TYPE1 | TYPE1 | TYPE1 |
| Paper/ribbon end | TYPE1 | TYPE1 | TYPE1 |
| MaxiCode specification | TYPE1 | TYPE1 | TYPE1 |
| XML | STD | STD | STD |
| Threshold selection (Reflective sensor) | Command | Command | Command |
| Threshold selection (Transmissive sensor) | Command | Command | Command |
| Print control (Thermal transfer) B-EX4T1-G/T | Semi resin1 | --- | Semi resin1 |
| Print control (Thermal transfer) B-EX4T2-G/T, B-EX4D2-G, and B-EX6T2-G/T | Wax1 | Wax1 | Wax1 |
| Print control (Thermal transfer) B-EX4T2-H | Resin1 | --- | Resin1 |
| Print control (Direct Thermal) | Standard | Standard | Standard |
| Length of time to power save mode | 15 minutes | 15 minutes | 15 minutes |

Parameter setting/LCD display

| Function | QM | QQ | CN | | |
|---|---|---|---|---|---|
| LCD display language | English | English | B-EX4T1 | C1.0C: | English |
| | | | | C1.0D or later: | Chinese |
| | | | B-EX4T2 B-EX6T2 | Chinese | |
| LCD detail display: model name | ON | ON | ON | | |
| LCD detail display: print number | ON | ON | ON | | |
| LCD detail display: IP address | OFF | OFF | OFF | | |
| Contrast adjustment | 40 | 40 | 40 | | |

Parameter setting/Password setting

| Function | QM | QQ | CN |
|---|---|---|---|
| Password enable/disable | Not cleared | Not cleared | Not cleared |
| Password value | Not cleared | Not cleared | Not cleared |

Fine adjustment value setting

| Function | QM | QQ | CN |
|---|---|---|---|
| Feed amount | 0.0mm | 0.0mm | 0.0mm |
| Cut position | 0.0mm | 0.0mm | 0.0mm |
| Back feed | 0.0mm | 0.0mm | 0.0mm |
| X-coordinate | 0.0mm | 0.0mm | 0.0mm |
| Print density (Thermal transfer) | 0step | 0step | 0step |
| Print density (Direct thermal) | 0step | 0step | 0step |
| Ribbon (take-up motor) | 0step | 0step | 0step |
| Ribbon (feed motor) | +5step | +5step | 0step |
| Reflective sensor | 1.0V | 1.0V | 1.0V |
| Transmissive sensor | 1.4V | 1.4V | 1.4V |
| Head down timing (B-EX4T1-TS25-R V2.0B or later) | --- | --- | --- |

Interface setting/Network

| Function | QM | QQ | CN |
|---|---|---|---|
| Wire/Wireless LAN selection | AUTO | AUTO | AUTO |
| SNMP | ON | ON | ON |
| IP address | Not cleared | Not cleared | Not cleared |
| Gateway | Not cleared | Not cleared | Not cleared |
| Subnet mask | Not cleared | Not cleared | Not cleared |
| Socket port | Not cleared | Not cleared | Not cleared |
| Port number | Not cleared | Not cleared | Not cleared |
| DHCP | OFF | OFF | OFF |
| DHCP client ID | Not cleared | Not cleared | Not cleared |
| DHCP host name | Not cleared | Not cleared | Not cleared |
| Wireless LAN standard | 802.11b/g | 802.11b/g | 802.11b/g |
| Wireless LAN connection mode | INFRA | INFRA | INFRA |
| Encryption | OFF | OFF | OFF |
| WPA authentication | OFF | OFF | OFF |
| Authentication | OFF | OFF | OFF |
| WEP default Key | 1 | 1 | 1 |
| 802.11b channel | 1 | 1 | 1 |
| 802.11b send rate | 11M | 11M | 11M |
| 802.11g channel | 1 | 1 | 1 |
| 802.11g send rate | 54M | 54M | 54M |
| WINS | OFF | OFF | OFF |
| WINS address | 0,0,0,0 | 0,0,0,0 | 0,0,0,0 |
| LPR | ON | ON | ON |

INTERFACE setting/USB

| Function | QM | QQ | CN |
|---|---|---|---|
| USB serial ID | OFF | OFF | OFF |

INTERFACE setting/RS-232C

| Function | QM | QQ | CN |
|---|---|---|---|
| Communication speed | 9600bps | 9600bps | 9600bps |
| Data length | 8bit | 8bit | 8bit |
| Stop bit | 1bit | 1bit | 1bit |
| Parity | NONE | NONE | NONE |
| Flow control | XON+READY AUTO | XON+READY AUTO | XON+READY AUTO |

INTERFACE setting/Centro

| Function | QM | QQ | CN |
|---|---|---|---|
| ACK/BYSY | TYPE1 | TYPE1 | TYPE1 |
| Input prime | ON | ON | ON |
| Plug and play | OFF | OFF | OFF |

BASIC setting

| Function | QM | QQ | CN |
|---|---|---|---|
| Basic function | OFF | OFF | OFF |
| Trace function | OFF | OFF | OFF |

RFID setting

| Function | QM | QQ | CN |
|---|---|---|---|
| Module setting | NONE | NONE | NONE |
| Tag type setting | NONE | NONE | NONE |
| Error tag detection | Not cleared | Not cleared | Not cleared |
| Access password | Not cleared | Not cleared | Not cleared |
| Password protection enable/disable | Not cleared | Not cleared | Not cleared |
| Password protection | Not cleared | Not cleared | Not cleared |
| Auto un-lock | Not cleared | Not cleared | Not cleared |
| Issue retry number | 3 | 3 | 3 |
| Read retry count | 5 | 5 | 5 |
| Read retry time | 4.0 second | 4.0 second | 4.0 second |
| Write retry count | 5 | 5 | 5 |
| Write retry time | 2.0 second | 2.0 second | 2.0 second |
| Write retry position | 0mm | 0mm | 0mm |
| Wireless output level | 251 | 251 | 251 |
| AGC threshold | 0 | 0 | 0 |
| Channel | AUTO | AUTO | AUTO |
| Q value | 0 | 0 | 0 |
| AGC threshold | 0 | 0 | 0 |
| AGC threshold Min. | 0 | 0 | 0 |
| Multi word write | OFF | OFF | OFF |
| RFID calibration [1] | OFF | --- | OFF |
| AGC value [1] | 0 | --- | 0 |
| Read/write position [1] | +0.0 mm | --- | +0.0 mm |
| Antenna position [1] | FRONT | --- | FRONT |
| RFID write success label issue number | Not cleared | Not cleared | Not cleared |
| RFID write failure label issue number | Not cleared | Not cleared | Not cleared |

*1: Supported from the firmware version of C1.0I for the B-EX4T1-G/T-QM/CN.

RTC setting

| Function | QM | QQ | CN |
|---|---|---|---|
| Battery check | Not cleared | Not cleared | Not cleared |
| Overwrite for printing | Not cleared | Not cleared | Not cleared |

Z-MODE

| Function | QM | QQ | CN |
|---|---|---|---|
| Z-MODE | OFF | OFF | OFF |

User system mode

Auto calibration

| Function | QM | QQ | CN |
|---|---|---|---|
| Auto calibration | OFF | OFF | OFF |

Settings programmed not in the system mode/user system mode

| Function | QM | | QQ | | CN | |
|---|---|---|---|---|---|---|
| Print speed | B-EX4T1-G<br>B-EX4T2-G<br>B-EX6T2-G | 6 ips | B-EX4D2-G | 6 ips | B-EX4T1-G<br>B-EX4T2-G<br>B-EX6T2-G | 6 ips |
| | B-EX4T1-T<br>B-EX4T2-T<br>B-EX6T2-T | 5 ips | | | B-EX4T1-T<br>B-EX4T2-T<br>B-EX6T2-T | 5 ips |
| | B-EX4T2-H | 3 ips | | | B-EX4T2-H | 3 ips |
| Sensor | Transmissive | | Transmissive | | Transmissive | |
| Print method | Thermal transfer | | Direct thermal | | Thermal transfer | |
| Issue mode | Batch | | Batch | | Batch | |
| Rotation | Bottom first | | Bottom first | | Bottom first | |
| Label pitch | 76.2mm | | 76.2mm | | 76.2mm | |
| Effective print length | 74.2 mm | | 74.2 mm | | 74.2 mm | |
| Effective print width | B-EX4T1<br>B-EX4T2 | 104 mm | 104 mm | | B-EX4T1<br>B-EX4T2 | 104 mm |
| | B-EX6T2 | 152 mm | | | B-EX6T2 | 152 mm |

## 8.9 INTERFACE

Contents of INTERFACE menu

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <7>INTERFACE | | | |
| | | NETWORK | | |
| | | | LAN/WLAN | |
| | | | SNMP | |
| | | | SETTING | |
| | | USB | | |
| | | RS-232C | | |
| | | CENTRO. | | |

## 8.9.1 NETWORK

Menu structure of NETWORK

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <7>INTERFACE | | | |
| | | NETWORK | | |
| | | | LAN/WLAN | |
| | | | SNMP | |
| | | | SETTING | |

The general network setting is selected.

### 8.9.1.1 LAN/WLAN
・OFF
・ON (AUTO)
・ON (LAN)
・ON (WLAN)

### 8.9.1.2 SNMP
・OFF
・ON

### 8.9.1.3  SETTING

| MENU  ITEM | | | | | Display pattern and key operation |
|---|---|---|---|---|---|
| SYSTEM  MODE | | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <7>INTERFACE | | | | |
| | | NETWORK | | | |
| | | | SETTING | | |
| | | | | BASIC  INFORMATION | 7.3 INFORMATION DISPLAY |
| | | | | IP  ADDRESS | 7.2 VALUE SETTING DISPLAY |
| | | | | GATEWAY  ADDRESS | |
| | | | | SUBNET  MASK | |
| | | | | SOCKET  PORT | 7.1 LIST BOX WITH SCROLLBAR |
| | | | | PORT  NUMBER | 7.2 VALUE SETTING DISPLAY |
| | | | | DHCP | 7.1 LIST BOX WITH SCROLLBAR |
| | | | | DHCP  CLIENT  ID | |
| | | | | ASCII | 7.2 VALUE SETTING DISPLAY |
| | | | | HEX | |
| | | | | DHCP  HOST  NAME | |
| | | | | WLAN  STANDARD | 7.1 LIST BOX WITH SCROLLBAR |
| | | | | WLAN  MODE | |
| | | | | DEFAULT  KEY | 7.2 VALUE SETTING DISPLAY |
| | | | | 802.11b  CHANNEL | |
| | | | | 802.11b  BAUD | 7.1 LIST BOX WITH SCROLLBAR |
| | | | | 802.11g  CHANNEL | 7.2 VALUE SETTING DISPLAY |
| | | | | 802.11g  BAUD | 7.1 LIST BOX WITH SCROLLBAR |
| | | | | WINS | |
| | | | | WINS  ADDRESS | 7.2 VALUE SETTING DISPLAY |
| | | | | LPR | 7.1 LIST BOX WITH SCROLLBAR |

### 8.9.1.3.1  BASIC  INFORMATION

The following information is displayed.

・ IP address

・ Gateway

・ Subnet mask

・ Socket port status

・ Socket port number

### 8.9.1.3.2  IP  ADDRESS

IP address is displayed and set.

### 8.9.1.3.3  GATEWAY  ADDRESS

Gateway address is displayed and set.

### 8.9.1.3.4  SUBNET  MASK

Subnet mask is displayed and set.

### 8.9.1.3.5  SOCKET  PORT
・ OFF
・ ON

### 8.9.1.3.6  PORT  NUMBER
Socket port number is displayed and set.

### 8.9.1.3.7  DHCP
・ OFF
・ ON

### 8.9.1.3.8  DHCP  CLIENT  ID
・ASCII          DHCP client ID is entered with ASCII code.
・HEX            DHCP client ID is entered with hex. code.

### 8.9.1.3.8.1  ASCII
Input DHCP client ID with ASCII code.
64 characters (00 to 63)

### 8.9.1.3.8.2  HEX
Input DHCP client ID with hexadecimal code.
64 characters (00 to 63)

### 8.9.1.3.9  DHCP  HOST  NAME
Input DHCP host name with ASCII code.
32 characters (00 to 31)

### 8.9.1.3.10  WLAN  STANDARD
・ 11b/g
・ 11b
・ 11g

### 8.9.1.3.11 WLAN MODE

Combination between the wireless LAN connection mode and authentication

| | | | |
|---|---|---|---|
| ADHOC | OPEN | | OFF |
| | | | WEP40 |
| | | | WEP104 |
| INFRA | OPEN | | OFF |
| | | | WEP40 |
| | | | WEP104 |
| | SHARED | | WEP40 |
| | | | WEP104 |
| | 802.1x | OPEN | TLS | WEP40 |
| | | | | WEP104 |
| | | | TTLS | WEP40 |
| | | | | WEP104 |
| | | | LEAP | WEP40 |
| | | | | WEP104 |
| | | | PEAP | WEP40 |
| | | | | WEP104 |
| | | | MD5 | WEP40 |
| | | | | WEP104 |
| | | | EAP-FAST | WEP40 |
| | | | | WEP104 |
| | | SHARED KEY | EAP-MD5 | WEP40 |
| | | | | WEP104 |
| | | NETWORK EAP | WEP40 |
| | | | WEP104 |
| | WPA | OPEN | TLS |
| | | | TTLS |
| | | | LEAP |
| | | | PEAP |
| | | | EAP-FAST |
| | | NETWORK EAP | |
| | WPA-PSK | | |
| | WPA2 | OPEN | TLS |
| | | | TTLS |
| | | | LEAP |
| | | | PEAP |
| | | | EAP-FAST |
| | | NETWORK EAP | |
| | WPA2-PSK | | |

### 8.9.1.3.12 DEFAULT KEY

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 4 | 1 | 1 | Decimal | None | 1 | 0 | None | None |

### 8.9.1.3.13 802.11b CHANNEL

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 14 | 1 | 1 | Decimal | None | 2 | 0 | None | None |

### 8.9.1.3.14 802.11b BAUD
・11M

・5.5M

・2M

・1M

### 8.9.1.3.15 802.11g CHANNEL

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 13 | 1 | 1 | Decimal | None | 1 | 0 | None | None |

### 8.9.1.3.16 802.11g BAUD
・54M

・48M

・36M

・24M

・18M

・12M

・9M

・6M

・11M

・5.5M

・2M

・1M

### 8.9.1.3.17 WINS
・OFF

・ON (MANUAL)

・ON (DHCP)

### 8.9.1.3.18  WINS  ADDRESS
WINS Address is displayed and set.

### 8.9.1.3.19  LPR
・OFF

・ON

## 8.9.2  USB

Menu  structure  of  USB

| MENU  ITEM | Display pattern and key operation |
|---|---|
| SYSTEM  MODE | 7.1 LIST BOX WITH SCROLLBAR |
|         &lt;7&gt;INTERFACE | |
|                 USB | |

### 8.9.2.1  USB  SERIAL  ID
・OFF

・ON

**8.9.3 RS-232C**

Menu structure of RS-232C

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <7>INTERFACE | | | |
| | | RS-232C | | |
| | | | SPEED | |
| | | | DATA LENGTH | |
| | | | STOP BIT | |
| | | | PARITY | |
| | | | CONTROL | |

8.9.3.1 SPEED
- ・ 2400 bps
- ・ 4800 bps
- ・ 9600 bps
- ・ 19200 bps
- ・ 38400 bps
- ・ 115200 bps

8.9.3.2 DATA LENGTH
- ・ 8 bits
- ・ 7 bits

8.9.3.3 STOP BIT
- ・ 1 bit
- ・ 2 bits

8.9.3.4 PARITY
- ・ NONE
- ・ EVEN
- ・ ODD

8.9.3.5 CONTROL
- ・ XON+READY AUTO      (Outputs XON at power on, XOFF at power off)
- ・ XON+XOFF AUTO       (Outputs XON at power on, XOFF at power off)
- ・ READY/BUSY RTS      (Outputs no XON/OFF at power on/off)
- ・ XON+XOFF            (Outputs no XON/OFF at power on/off)
- ・ READY/BUSY          (Outputs no XON/OFF at power on/off)

### 8.9.4 CENTRO.

Menu structure of CENTRO.

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <7>INTERFACE | | | |
| | | CENTRO. | | |
| | | | ACK/BUSY | |
| | | | INPUT PRIME | |
| | | | PLUG & PLAY | |

8.9.4.1 ACK/BUSY
・TYPE1
・TYPE2

8.9.4.2 INPUT PRIME
・OFF
・ON

8.9.4.3 PLUG & PLAY
・OFF
・ON
NOTE:   Plug & play function of USB is always enabled regardless of this setting.

## 8.10  BASIC

Contents  of  BASIC  menu

| MENU  ITEM | | | Display pattern and key operation |
|---|---|---|---|
| SYSTEM  MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <8>BASIC | | |
| | | BASIC | |
| | | FILE  MAINTENANCE | 7.3  INFORMATION  DISPLAY |
| | | TRACE | 7.1  LIST  BOX  WITH  SCROLLBAR |
| | | EXPAND  MODE | |

### 8.10.1  BASIC

・OFF

・ON

### 8.10.2  FILE  MAINTENANCE

The  block  number  and  BASIC  program  file  name  (up  to  12  characters)  stored  in  the  BASIC  program storage  area  are  displayed.    If  the  file  name  exceeds  12  characters,  the  overflowing  characters  are  not displayed.

When no file is stored, a hyphen (-) is displayed in place of the file name.

### 8.10.3  TRACE

・OFF

・ON

### 8.10.4  EXPAND  MODE

The printer switches the mode to execute the BASIC program.

## 8.11 FOR FACTORY

Contents of FOR FACTORY menu

| MENU ITEM | | | Display pattern and key operation |
|---|---|---|---|
| SYSTEM MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <9>FOR FACTORY | | |
| | | HEAD UP ADJUST | |
| | | PANEL TEST | |
| | | KEY TEST | |

### 8.11.1 HEAD UP ADJUST

The head-up solenoid is turned on for 10 seconds.

### 8.11.2 PANEL TEST

The test is performed in the following order.

The display language is English regardless of the language selected for LCD Language parameter.

| Backlight test | LCD BACK LIGHT ON<br><br>PRESS ANY KEY | ONLINE LED turns on.<br>ERROR LED turns on.<br>Backlight turns on. |
|---|---|---|
| | | Press any key. |
| | LCD BACK LIGHT OFF<br><br>PRESS ANY KEY | ONLINE LED turns on.<br>ERROR LED turns on.<br>Backlight turns off. |
| | | Press any key. |
| Missing dot test | PRESS ANY KEY | ONLINE LED turns on.<br>ERROR LED turns on.<br>Backlight turns on.<br>A 1-dot box is displayed along the ends of the LCD. |
| | | Press any key. |
| | | ONLINE LED turns on.<br>ERROR LED turns on.<br>Backlight turns on.<br>All LCD dots are on. |
| | | Press any key. |
| | | ONLINE LED turns on.<br>ERROR LED turns on.<br>Backlight turns on.<br>All LCD dots are off. |
| | | Press any key. |
| | | ONLINE LED turns on.<br>ERROR LED turns on.<br>Backlight turns on.<br>1-dot check pattern is displayed. The upper left corner dot is black. |
| | | Press any key. |

| | | ONLINE LED turns on. |
|---|---|---|
| | | ERROR LED turns on. |
| | | Backlight turns on. |
| | | 1-dot check pattern is displayed.  The upper left corner dot is white. |
| | | Press any key. |
| Character display test | ABCDEFGHIJKLMNOPQRSTU<br>12345678901234567890 1<br>abcdefghijklmnopqustu<br>09876543210987654321 0<br>ZYXWVUTSRQPONMLKJIHGF | ONLINE LED turns on. |
| | | ERROR LED turns on. |
| | | Backlight turns on. |
| | | Character display |
| | | Press any key. |
| Contrast test | CONTRAST TEST<br><br>24 | ONLINE LED turns on. |
| | | ERROR LED turns on. |
| | | Backlight turns on. |
| | | Displays with the minimum contrast. |
| | | Press any key. |
| | CONTRAST TEST<br><br>40 | ONLINE LED turns on. |
| | | ERROR LED turns on. |
| | | Backlight turns on. |
| | | Displays with the default contrast. |
| | | Press any key. |
| | CONTRAST TEST<br><br>50 | ONLINE LED turns on. |
| | | ERROR LED turns on. |
| | | Backlight turns on. |
| | | Displays with the maximum contrast. |
| | | Press any key. |
| End display | LCD/LED TEST COMPLETE<br><br>PRESS ENTER KEY | ONLINE LED turns on. |
| | | ERROR LED turns off. |
| | | Backlight turns on. |
| | | Returns to the upper hierarchy display when the [ENTER] or [CANCEL] key is pressed. |

### 8.11.3  KEY  TEST

The test is performed in the following order.

The display language is English regardless of the language selected for LCD Language parameter.

When an expected key is not pressed, the printer waits until that key is pressed.

If the key test does not proceed to the next test even after the expected key is pressed, the key may be broken.   In this case, turn off the printer.

| FEED KEY PRESS TEST | PRESS FEED KEY | |
|---|---|---|
| | | Press the [FEED] key. |
| RESTART KEY PRESS TEST | PRESS RESTART KEY | |
| | | Press the [RESTART] key. |

| PAUSE KEY PRESS TEST | PRESS PAUSE KEY | |
|---|---|---|
| | | Press the [PAUSE] key. |
| UP KEY PRESS TEST | PRESS UP KEY | |
| | | Press the [UP] key. |
| RIGHT KEY PRESS TEST | PRESS RIGHT KEY | |
| | | Press the [RIGHT] key. |
| DOWN KEY PRESS TEST | PRESS DOWN KEY | |
| | | Press the [DOWN] key. |
| LEFT KEY PRESS TEST | PRESS LEFT KEY | |
| | | Press the [LEFT] key. |
| MODE KEY PRESS TEST | PRESS MODE KEY | |
| | | Press the [MODE] key. |
| CANCEL KEY PRESS TEST | PRESS CANCEL KEY | |
| | | Press the [CANCEL] key. |
| ENTER KEY PRESS TEST | PRESS ENTER KEY | |
| | | Press the [ENTER] key. |
| END DISPLAY | KEY TEST COMPLETE<br><br>PRESS ENTER KEY | |
| | | Returns to the upper hierarchy display when the [ENTER] or [CANCEL] key is pressed. |

## 8.12 RFID

Contents of RFID menu

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <10>RFID | | | |
| | | TEST | | |
| | | | ID READ | 7.3 INFORMATION DISPLAY |
| | | MODULE | | 7.1 LIST BOX WITH SCROLLBAR |
| | | | MODULE TYPE | |
| | | | COUNTRY | |
| | | | TAG | |
| | | | RF CHANNEL | |
| | | RETRY | | |
| | | | ADJ RETRY POSITION | 7.2 VALUE SETTING DISPLAY |
| | | | ISSUE RETRY LABELS | |
| | | | READ RETRY | |
| | | | WRITE RETRY | |
| | | UHF SETTING | | 7.1 LIST BOX WITH SCROLLBAR |
| | | | POWER LEVEL | 7.2 VALUE SETTING DISPLAY |
| | | | Q VALUE | |
| | | | AGC THRESHOLD | |
| | | | WRITE AGC THRESHOLD | |
| | | | WRITE RETRY MIN AGC | |
| | | | CALIB. MODE [1] | |
| | | | CALIB. AGC [1] | |
| | | | CALIB. POSITION [1] | |
| | | | ANTENNA POSITION [1] | |
| | | Other | | 7.1 LIST BOX WITH SCROLLBAR |
| | | | TAG CHECK | |
| | | | MULTI WRITE | |
| | | | CARRIER SENSE | |

*1: Supported from firmware version of C1.2 for the B-EX4T1-G/T-QM/CN.

### 8.12.1 TEST

The following information related to the read test displayed.

・ID READ

### 8.12.1.1  ID READ

The printer enters the read test mode, and a read test is performed each time the [ENTER] key is pressed.
When the data of a tag can be read, it is displayed on the LCD.

When the read test failed, the following message is displayed on the LCD.

| Error message | Error description |
|---|---|
| MODULE TYPE ERROR | RFID module type has been set to NONE or a communication cannot be established. |
| COUNTRY CONFIG ERROR | Country code has not been set. |
| READ ERROR<br>Confirm Setting or<br>set other Tag. | The type of the tag to be read and one selected by the RFID tag type selection do not match. |
| NOT AVAILABLE | Not supported. |
| NO RESPONSE | No response from the tag |
| READ TIMEOUT<br>Set a RF-Tag on Ant. | Timeout |
| UNKNOWN ERROR | Other errors |

Only the tags selected for the RFID tag type can be read.
If the type of the tag to be read and one selected by the RFID tag type selection do not match, the read test results in an error.   Therefore, RFID tag type shall be selected before the read test is started.

・Display example



(1) The number tag being read/The total number of tags read
   （Mostly, only 1 tag is read.）
(2) For the UHF module, AGC value of the read tag is displayed with decimal number.
(3) Data displayed on 3rd and 4th lines are expressed with hex. code.
   The displayed data differs depending on the module type.
      B-EX700-RFID-H1-QM-R: Tag ID
      B-EX700-RFID-U2-R/US/EU-R, B-EX700-RFID-U4-EU/US-R, U4 module preinstall model
      (B-EX4T1/EX4T2-GS18/TS18-CN-R): EPC code of EPC area

・In the case of 32 digits or more data, only the first 32 digits are displayed.   When data is less than 32
  digits, the vacant digits will be filled with spaces.
・If more than one tag is read at one time, especially when short-pitch tags are used, pressing the [UP] or
  [DOWN] key shows the other tags' data.

### 8.12.2 MODULE

The following information related to the module setting is displayed.
・MODULE TYPE
・COUNTRY
・TAG
・RF CHANNEL

#### 8.12.2.1 MODULE TYPE

・NONE          No RFID module is installed.
・H1            B-EX700-RFID-H1-QM-R
・H2            B-EX700-RFID-H2-R
・U2            B-EX700-RFID-U2-EU-R (Europe, India)
                    B-EX700-RFID-U2-US-R (North America, Australia, Taiwan, Korea)
                    B-EX700-RFID-U4-EU-R (Europe)
                    B-EX700-RFID-U4-US-R (Korea)
                    U4 module preinstall model (B-EX4T1/EX4T2-GS18/TS18-CN-R) (China)

NOTE: This setting will become effective after the printer power is turned off, and back to on.

#### 8.12.2.2 COUNTRY

The country code of the currently installed module is displayed.
If the module type is set to other than "U2", "INVALID" is displayed.
It is possible to change the country setting when the module type is set to "U2" and the actually installed module type is U2-US or U2-EU. However, this menu is password-protected because changing the country setting causes the output frequency to change.

The following message is displayed depending on the module type setting, the mounted module type, and the module mount condition.

| Module Type parameter | Module type and status | | Message |
|---|---|---|---|
| NONE | No module installed. | | NONE |
| H1/H2 | B-EX700-RFID-H1-QM-R B-EX700-RFID-H2-R | | INVALID |
| U2 | No module installed. | | No RFID Module |
| | B-EX700-RFID-U2-EU-R B-EX700-RFID-U2-US-R | Country setting done. *1 | [ENTER] for Setting |
| | B-EX700-RFID-U4-EU-R B-EX700-RFID-U4-US-R U4 module preinstall model | No country setting done | Need Setting for use [ENTER] for Setting |
| | B-EX700-RFID-U2-R | | Cannot change COUNTRY Setting. |

*1: Selectable country codes differ depending on the RFID module type. Multiple country codes may be displayed when setting a country code, but be sure to select the country where the RFID module is used. Setting a different country code is prohibited.
For the selectable country codes, refer to Module version and LCD message in Section 8.3.1.1.

### 8.12.2.3 TAG

Selectable tag types vary according to the module setting.

The number in the table indicates the scroll line number.

|            | NONE | H1 | H2 | U2 (*1) |
|------------|------|----|----|---------|
| NONE       | 1    | 1  | 1  | 1       |
| I-Code     | 2    | 2  |    |         |
| Tag-It     | 3    | 3  |    |         |
| C220       | 4    | 4  |    |         |
| ISO15693   | 5    | 5  | 2  |         |
| C210       | 6    | 6  |    |         |
| C240       | 7    | 7  |    |         |
| C320       | 8    | 8  |    |         |
| EPC C1 Gen2| 9    |    |    | 2       |

*1: U4 and U4 module preinstall models are included.

### 8.12.2.4 RF CHANNEL

A channel used for RFID tag write is set.

When a channel is chosen from 2CH to 8CH, that channel will be continuously used.

When the channel is set to AUTO, an available channel is searched in the following order:

(2CH → 8CH → 6CH → 4CH → 3CH → 7CH → 5CH → 2CH)

Though this setting is applicable to all models, it works effectively only for the B-EX700-RFID-U2-R（UHF for Japan）.

・AUTO
・2CH
・3CH
・4CH
・5CH
・6CH
・7CH
・8CH

### 8.12.3 RETRY

The following information related retry is displayed.

・ADJ RETRY POSITION
・ISSUE RETRY LABELS
・READ RETRY
・WRITE RETRY

### 8.12.3.1 ADJ RETRY POSITION

If writing data on a tag failed, the printer feeds the RFID tag forward or backward for specified length, in order to retry data write.  When "0" is set for this parameter, this function and a retry are not performed. Only the value of -3mm or less or +3mm or more is effective.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 99 | -99 | 1 | Decimal | None | 2 | 0 | None | mm |

### 8.12.3.2 ISSUE RETRY LABLES

When issuing an RFID tag failed, the printer prints the error (Void) pattern, and retries to issue the tag for up to specified number of times.  If the printer does not succeed even after having retried for the max. number of times, the printer stops, resulting in an error.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 255 | 0 | 1 | Decimal | None | 3 | 0 | None | Labels |

### 8.12.3.3 READ RETRY

The number of times tag read is retried and the timeout for read retry are set.

The printer retries to read the data in an RFID tag for up to specified number of times.  If the timeout period expired before the max. number of retries have been done, the printer stops the retries at the time. Whenever the printer writes data onto an RFID tag, the tag is read first.  The max. number of retries set by this parameter becomes also effective in this pre-read.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 255 | 0 | 1 | Decimal | None | 3 | 0 | None | Times |

The timeout for RFID tag read retry is set.

If the printer has retries for the max. number of times within the RFID read retry timeout, the printer stops the retries at the time.  Whenever the printer writes data onto an RFID tag, the tag is read first.  The read retry timeout set by this parameter becomes also effective in this pre-read.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 9.9 | 0.0 | 0.1 | Decimal | None | 1 | 1 | None | Second |

### 8.12.3.4 WRITE RETRY

The number of times tag write is retried and the timeout for write retry are set.

The printer retries to write data onto an RFID tag for up to specified number of times.　If the timeout period expired before the max. number of retries have been done, the printer stops the retries at the time.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 255 | 0 | 1 | Decimal | None | 3 | 0 | None | Times |

The timeout for RFID tag write retry is set.

If the printer has retries for the max. number of times within the RFID write retry timeout, the printer stops the retries at the time.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 9.9 | 0.0 | 0.1 | Decimal | None | 1 | 1 | None | Second |

## 8.12.4 UHF SETTING

The formation related UHF setting is displayed.
- POWER LEVEL
- Q VALUE
- AGC THRESHOLD
- WRITE AGC THRESHOLD
- WRITE RETRY MIN AGC
- CALIB. MODE[1]
- CALIB. AGC [1]
- CALIB. POSITION [1]
- ANTENNA POSITION [1]

　*1: Supported from the firmware version of C1.2 for the B-EX4T1-G/T-QM-CN.

### 8.12.4.1 POWER LEVEL

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| *1 | *1 | 1 | Decimal | None | 3 | 0 | None | None |

Radio output level of UHF.

The range of output level is 26 (approximately 500mW) to 9 (approximately 10mW).

In the case of the B-EX700-RFID-U2-EU/US-R, a value shown on the LCD ranges from 0 to 18 though the setting range is 9 to 18.　If a value from 0 to 8 is set, the printer operation is not guaranteed.

*1: The maximum and minimum values vary depending on the module type.

| | Initial value | Max. value | Min. value |
|---|---|---|---|
| B-EX700-RFID-U2-R | 18 | 26 | 18 |
| B-EX700-RFID-U2-EU-R/US-R | 18 | 18 | 9 |
| B-EX700-RFID-U4-EU/US-R<br>U4 module preinstall model<br>(B-EX4T1/EX4T2-GS18/TS18-CN-R)<br>Note: Supported from the printer firmware of C1.0I for the B-EX4T1-G/T-QM/CN and C1.0F for the B-EX4T2-G/T-QM/CN. | 18 | 18 | 0 |

### 8.12.4.2 Q VALUE

This is effective only for the B-EX700-RFID-U2-R/EU-R/US-R, EX700-RFID-U4-EU/US-R, U4 module preinstall model (B-EX4T1/EX4T2-GS18/TS18-CN-R).

In the case multiple RFID tags are read at the same time, this menu is useful to pinpoint a target tag.   Set the Q value to "1" or greater (2 is recommended) with the [UP] or [DOWN] key.   Q value "0" causes the tags to interfere with each other and disables proper data write.

When the Q value is set, set an AGC threshold for data write and an AGC threshold lower limit for retry, also.   Setting all these values enables writing data to a tag placed just above the antenna.

However, the problem that multiple tags are read at the same time does not occur with most RFID tag types. It is not necessary to change the default setting.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 15 | 0 | 1 | Decimal | None | 2 | 0 | None | None |

### 8.12.4.3 AGC THRESHOLD

This is effective only for the B-EX700-RFID-U2-R/EU-R/US-R, EX700-RFID-U4-EU/US-R, U4 module preinstall model (B-EX4T1/EX4T2-GS18/TS18-CN-R)

When the obtained gain of an RFID tag is lower than the AGC threshold, the tag is considered as an error tag even if a data write succeeds.

When the AGC threshold is set to "0", all tags are writable.

When set to "8", for example, only tags with the AGC threshold level of 9 or greater are writable.   The optimum value is different depending on the tag types.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 15 | 0 | 1 | Decimal | None | 2 | 0 | None | None |

### 8.12.4.4 WRITE AGC THRESHOLD

This is effective only for the B-EX700-RFID-U2-R/EU-R/US-R, EX700-RFID-U4-EU/US-R, U4 module preinstall model (B-EX4T1/EX4T2-GS18/TS18-CN-R).

When the Q value is set to 1 or greater, the AGC threshold for data write becomes effective.

When the obtained gain of an RFID tag is lower than the AGC threshold for data write, a data write operation is not performed.   In other words, setting an AGC threshold for data write enables writing data only to a tag placed just above the antenna.

Supposing that the gain of a tag just above the antenna is 14 and that of a tag off the antenna is 7, setting the threshold to 11 (a value between 8 and 14) enables the printer to write data only to the tag just above the antenna.

When the threshold is set to 0, a data write operation is performed regardless of the gain of a tag.

Both of the AGC threshold and the AGC threshold for data write are used to determine whether a tag is defective or not, but the timing of a gain measurement is different.   In the case of the AGC threshold, this is performed after data is written to a tag.

On the contrary, when the AGC threshold for data write is effective a measurement is performed before data is written.   And if a gain value is lower than the threshold, a data write operation is not performed.

The optimum value differs depending on the tag type.

However, the problem that multiple tags are read at the same time does not occur with most RFID tag types. It is not necessary to change the default setting.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 15 | 0 | 1 | Decimal | None | 2 | 0 | None | None |

### 8.12.4.5 WRITE RETRY MIN AGC

This is effective only for the B-EX700-RFID-U2-R/EU-R/US-R, EX700-RFID-U4-EU/US-R, U4 module preinstall model (B-EX4T1/EX4T2-GS18/TS18-CN-R).

When the Q value is set to 1 or greater, the AGC threshold lower limit for retry becomes effective.

Even if a tag's gain is lower than the AGC threshold for data write, a data write to the tag may be successful in a retry if the gain is greater than the lower limit.   For a retry, the printer lowers the threshold to the highest gain of the tag if it is greater than the lower limit or to the lower limit if it is greater than the highest gain of the tag.

Example 1

AGC threshold for data write: 11
Lower limit for retry: 9
Detected tag's gain: 10

As the gain of the tag is lower than the threshold, a data write operation is not performed for this tag at the first try.   However, the gain is greater than the lower limit.
Then the printer retires to write data to this tag according to a new AGC threshold of 10.
In this case, a retry of a data write will mostly succeed because the detected tag's gain is greater than the new threshold.   (However, the success rate is not 100% because a gain of a tag is not always the same.)

Example 2

AGC threshold for data write: 11
Lower limit for retry: 9
Detected tag's gain: 8

As the gain of the tag is lower than the threshold, a data write operation is not performed for this tag at the first try.   Also, the gain is lower than the lower limit.
Then the printer retries to write data to this tag according to a new AGC threshold of 9.
In this case, a retry of data write will mostly fail because the detected tag's gain is lower than the new threshold.   (However, the error rate is not 100% because a gain of a tag is not always the same.)

When the same value is set to the AGC threshold for data write and the AGC threshold lower limit for retry, respectively, the threshold will not be changed for a retry.

The optimum value differs depending on the tag type.

However, the problem that multiple tags are read at the same time does not occur with most RFID tag types.   It is not necessary to change the default setting.

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 15 | 0 | 1 | Decimal | None | 2 | 0 | None | None |

## 8.12.4.6 CALIB. MODE

・OFF

・ON

This parameter is to select whether the RFID calibration function is enabled or not.

When enabled (ON), the AGC value (CALIB. AGC) and the distance to the read/write position (CALIB. POSITION) obtained through an RFID calibration become effective.   Also, the printer will automatically feed RFID media forward/backward for the distance specified by CALIB. POSITION parameter before writing/reading RFID tag.   Therefore, @003 command's parameters "a" and "bbbb" become invalid. (For details of the @003 command, refer to the External Equipment Interface Specification for the B-EX Series.)

When the values obtained through an RFID calibration are set, this parameter will automatically turn ON.

This function is supported from the firmware version of C1.2 for the B-EX4T1-G/T-QM/CN. (In the case of firmware version C1.1, this parameter will automatically turn OFF.)

For details of the RFID calibration, refer to Section 6.7 RFID CALIBRATION.


## 8.12.4.7 CALIB. AGC

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| 15 | 0 | 1 | Decimal | None | 2 | 0 | None | None |

By performing an RFID calibration, an AGC (response level from an RFID tag) value is automatically obtained and set.   This parameter is effective only when the CALIB. MODE parameter is set to ON.

Data write/read is performed only for the tags having the AGC value equal to or larger than the AGC value set for this parameter.   When the AGC value is less than the one set for this parameter, RFID WRITE ERROR occurs.

This function is supported from the firmware version of C1.2 for the B-EX4T1-G/T-QM/CN.

For details of the RFID calibration, refer to Section 6.7 RFID CALIBRATION.


## 8.12.4.8 CALIB. POSITION

| Max. value | Min. value | Step | Display | Sign | Integer digit | Decimal place | 0-padding | Unit of measure |
|---|---|---|---|---|---|---|---|---|
| +999.9 | -999.9 | 0.1 | Decimal | None | 3 | 1 | None | mm |

By performing an RFID calibration, an optimum data read/write position (distance from the home position) is automatically obtained and set.   This parameter is effective only when the CALIB. MODE parameter is set to ON.

The printer will automatically feed RFID media forward/backward for the distance specified by CALIB. POSITION parameter before writing/reading RFID tag, which is normally performed with @003 command.

The feed direction is indicated by "+" (backward) and "–" (forward).   Setting values ranging from +2.9mm to +2.9mm do not affect the read/write position fine adjustment.

This function is supported from the firmware version of C1.2 for the B-EX4T1-G/T-QM/CN.

For details of the RFID calibration, refer to Section 6.7 RFID CALIBRATION.

### 8.12.4.9 ANTENNA POSITION

・FRONT
・CENTER
・REAR

This parameter, used for an RFID calibration, is to select the combinational position of the RF antenna and the wave director.　If the antenna position has been changed, this parameter must be changed, accordingly.

This function is supported from the firmware version of C1.2 for the B-EX4T1-G/T-QM/CN.

For details of the RFID calibration, refer to Section 6.7 RFID CALIBRATION.

| Antenna position | Antenna rotation | Wave director position |
|---|---|---|
| FRONT | 0° | 0 mm |
| CENTER | 0° | 9 mm |
| REAR | 180° | 12 mm |

## 8.12.5 OTHER

The following information related RFID is displayed.

・　TAG CHECK
・　MULTI WRITE
・　CARRIER SENSE

### 8.12.5.1 TAG CHECK

| OFF | Error tag detection is not performed.　Though a tag is read before writing data on it, data is always written on the tag whatever data is set as the header data. |
|---|---|
| ON (ID) | Error tag detection is performed.　A tag (EPC area for GEN2 tags) is read before writing data on it and data is written on the tag only when the header data is "A5A5". |
| ON (ACCESS PASSWORD) | Error tag detection is performed only for GEN2 tags.　The access password area of a tag is read before writing data on it.　Only when the data read matches the access password setting data, the data is written on the tag. |

To prevent unauthorized changes of the setting, a password to protect the error tag detection setting can be programmed.

| Display | Operation |
|---|---|
| When the TAG CHECK parameter is set to ON (ACCESS PASSWORD)", an entry of the password is requested. The following explanation is for when protected password is enabled. | |
| INPUT PASSWORD<br><br>0 0 0 0 | Input the default password "0000" or 4-digit password programmed in Step 6. |
| When the password matches, TAG CHECK parameter setting screen appears. | |
| If the entered password does not match, an error message is displayed and the screen returns to the upper hierarchy menu. | |
| TAG CHECK<br>OFF<br>ON(ID)<br>ON(ACCESS PASSWORD) | Select a tag check option.<br>・ Disable<br>・ Enable (ID)<br>・ Enable (Password) |
| When "Disable" or "Enable (ID)" is selected, the password setting is disabled and the screen returns to the upper hierarchy. | |
| When "Enable (Password)" is selected, the access password entry is requested. | |
| ACCESS PASSWORD<br><br>0 0 0 0 0 0 0 1 | Input 8-digit access password. |
| AUTO UNLOCK<br>OFF<br>ON | Choose whether or not to enable the auto unlock function.<br>・ OFF<br>・ ON<br>When "ON" is selected, locked tags are automatically unlocked by the access password and data write is enabled. |
| PASSWORD(RFID)<br>OFF<br>ON | Choose whether or not to set the password to protect the error tag detection setting.<br>・ OFF<br>・ ON |
| When "OFF" is selected, this menu is ended and the upper hierarchy menu is shown. | |
| When "ON" is selected, the password can be programmed. | |
| PASSWORD SETTING<br><br>0 0 0 0 | Input 4-digit password. |

## 8.12.5.2 MULT WRITE

Gen2-compatible Hibiki tag (HITACHI) has a function which reduces the time to write data on the RFID chips. This is called "Multi-word write". Use of this function enables a speed-up of the data write operation. However, this function is unique to the Hibiki tag, and not usable with the other Gen2-compatible chips.

・OFF
・ON

### 8.12.5.3 CARRIER SENSE

The printer enters the carrier sense mode, and performs a carrier sense. Environmental radio wave of each channel is picked up for about 30 times during 5 seconds. (This function is enabled only for the B-EX700-RFID-U2-R is used.)

Display example

| Display |
|---|
| CARRIER SENSE |
| CH Available    MAX |
| 1    0%      0000 |
| 2    0%      0000 |
| 3    0%      0000 |

・ The left-most number indicates a channel number. The percentage means the availability of the channel, which is determined by performing approx. 30 carrier senses. Thus, "100%" means that any other devices do not use this channel.

・ MAX column shows the value of the maximum radio wave picked up. The larger the value is, the stronger radio wave source exists nearby.

・ "MAX 0011" means the value of the maximum radio wave picked up.

・ The display can be scrolled up or down, from Channel 1 (1CH) to channel 9 (9CH), by using the [UP] or [DOWN] key.

・ Pressing the [ENTER] key causes the printer to perform a carrier sense again. To quit a carrier sense, press the [CANCEL] key.

・ When the RFID module type is set to "NONE" or a communication cannot be established, a message, "NO RFID MODULE", is displayed.

・ When the RFID module type is set to other than U2, a message, "NOT AVAILABLE" is displayed.

・ When the RFID module type is set to U2 but effective data cannot be obtained, a message, "NO RESPONSE" is displayed.

・ If the RFID module's country setting is not specified (user-inaccessible setting) for the B-EX700-RFID-U2-EU/US, an "RFID CONFIG ERR" message is displayed.

## 8.13  RTC

Contents  of  RTC  menu

| MENU  ITEM | | | Display pattern and key operation |
|---|---|---|---|
| SYSTEM  MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <11>RTC | | |
| | | DATE  TIME | 7.2 VALUE SETTING DISPLAY |
| | | BATTERY  CHECK | 7.1 LIST BOX WITH SCROLLBAR |
| | | RENEWAL | |

### 8.13.1  DATE  TIME

This setting is effective only when the optional RTC module is mounted.

Date and time are set.

### 8.13.2  BATTERY  CHECK

・OFF

・ON

### 8.13.3  RENEWAL

・BATCH As the real time clock data is read only for the first media in a batch, the same time is printed on the all media.

・PAGE As the real time clock data is read at the start of printing each media, a real time can be printed on each media.

## 8.14 Z-MODE

Contents of Z-MODE menu

| MENU ITEM | Display pattern and key operation |
|---|---|
| SYSTEM MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     &lt;12&gt;Z-MODE | |

This menu is displayed only when the destination is other than JA.

・OFF                     (Disabled)
・ON SETTING OFF     (Z-Mode is enabled. BASIC system mode program is not started immediately.)
・ON SETTING ON      (Z-Mode is enabled. BASIC system mode program is started immediately.)

The Z-Mode menu has the function to select whether to enable or disable the BASIC program (same function with the BASIC ON/OFF) and to start the BASIC system mode program only. The display and the procedure are different from the BASIC.

Turning the Z-MODE parameter setting from "OFF" to "ON SETTING OFF" or "ON SETTING ON" causes the MEDIA LOAD parameter setting to be automatically changed as follows:

| Model | Firmware version | MEDIA LOAD parameter setting |
|---|---|---|
| B-EX4T1 QM | C1.1B or later | ECO |
| B-EX4T2 | C1.1A or later | STD |
| B-EX4T2H | C1.0G or later | STD |
| B-EX6T2 | C1.0 or later | STD |
| Other combinations of model and firmware version | | Unchanged |

It is possible to change the above settings by setting the MEDIA LOAD parameter again.

## 8.15 USB MEMORY

The following table shows the error messages which may be displayed while USB memory is used, and description of the errors.

After the error message is displayed, the operation is not retried.

| Message | Description |
|---|---|
| FORMAT ERROR<br>Check the settings. | Format error or no memory installed |
| MEMORY WRITE ERR.<br>Check the data<br>and the settings. | Write error |
| MEMORY READ ERR.<br>Check the data<br>and the settings. | Read error |
| MEMORY FULL<br>Free some space. | Insufficient memory |
| FILE NOT FOUND<br>Check the data<br>and the settings. | No applicable file found |
| UNKNOWN ERROR | Other errors |

NOTE: Depending on the remaining memory size or the USB memory status, a write error may occur even when the USB memory is under the insufficient free space condition.

Usable USB memory's file system is as follows:

| File system | Max. size |
|---|---|
| FAT (FAT16) | 2GB |
| FAT32 | 8GB |

To use USB memories of the other file system, they need to be formatted to either of the above on the PC in advance.

Contents of USB MEMORY menu

| MENU ITEM | | | Display pattern and key operation |
|---|---|---|---|
| SYSTEM MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <13>USB MEMORY | | |
| | | USB TO PRINTER | |
| | | PRINTER TO USB | |

### 8.15.1 USB TO PRINTER

・COPIED DATA
・CONFIG FILE

The data store in USB memory is copied to the printer.

- COPIED DATA    File (*.DAT) containing firmware (BOOT/MAIN/ CG/KANJI/HTML), storage area information, and parameter settings
  The file is created in binary format when "PRINTER TO USB" is executed.
- CONFIG FILE    File (*.CFG) in which the path of the firmware (BOOT/MAIN/ CG/KANJI/HTML) is saved
  The file is created in text format when the master media is made.    The format of the file is described in Section 11.Auto Configuration Mode.

After an item to be saved is selected, the file selection display is shown.
For the file selection display, see Section 7.6 FILE SELECTION DISPLAY.
(The scrollbar on the file selection display is not provided with the knob regardless of the number of files.)
The confirmation display appears when a file is selected from the file selection display.
(When CFG files is selected, the message included in the CFG file is shown prior to the confirmation display.)
After confirming the data copy, the printer reads data from USB memory.
It takes about 3 to 5 minutes to read all information.

Copy data
When saving other model's data is attempted, only the parameter settings are read.  In this case, parameters not supported by the destination printer are inapplicable.  It takes about 3 seconds to copy data.
NOTES:
1. B-EX4T1-G and B-EX4T1-T, B-EX4T2-G and B-EX4T2-T, and B-EX6T2-G and B-EX6T2-T are regarded as the same mode, respectively.
2. When the CPU is the SH type, QM and CN models are regarded as the same model.
   (When printers provided with the V850 type CPU, they are regarded as the same model regardless of the destination.)
3. Printer models are identified by the CPUs (SH type and V850 type).

Parameters of copy data
Parameters not supported by the destination printer are read, but not applied.  Also, even if the destination printer has the same parameters with the source printer, options may be different.
Example 1:    In the case of the B-EX4T2-H, "Resin1" for the Energy type (Transfer) parameter is the 1st option. When the B-EX4T2-H parameter settings are copied to the B-EX4T2-G (C1.0D), "Resin1" will be the 5th option.
Example 2:    When the Energy type (Transfer) parameter for the B-EX4T2-G (C1.0D) has been set to "Wax3", and the parameter settings are copied to the B-EX4T2-H, the Energy type (Transfer) parameter will not be updated.

When the error occurs during an access to the USB memory, the error message described in Section 8.15 USB MEMORY is displayed.
The printer does not retry the operation.

## 8.15.2 PRINTER TO USB

・ ALL

Printer copies firmware (BOOT/MAIN/CG/KANJI/HTML), storage area information, and parameter settings to a USB memory.

After an item to be saved is selected, the confirmation display is shown and the data is stored in the USB memory.

It takes about 40 seconds to copy all information.

A file is automatically created in the USB memory and named in the following format based on the printer model and saved date.

/ATA0/SYSTEM/B-EX4T1-T1105.DAT (e.g. B-EX4T Type1 305dpi model, the 11th Nov.)

If a file with the same name already exists in the USB memory, it will be overwritten.

When the error occurs during an access to the USB memory, the error message described in Section 8.15 USB MEMORY the operation.

## 8.16  RESET

Contents of RESET menu

| MENU  ITEM | Display pattern and key operation |
|---|---|
| SYSTEM  MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     <14>RESET | |

The printer is reset.

# 9 USER SYSTEM MODE

## 9.1 OUTLINE OF USER SYSTEM MODE

The printer enters the user system mode when the following operation is performed from the online state.

- Press the [PAUSE] key to place the printer in pause state, then hold down the [PAUSE] key.
- Hold down the [MODE] key.

The user system mode is intended for performing parameter and other settings.
The key operations for the user system mode are described below.

Key operations follow Section 7.1 LIST BOX WITH SCROLLBAR.

| Display |
|---|
| USER SYSTEM MODE V1.0 |
| <1>RESET |
| <2>PARAMETER SET |
| <3>ADJUST SET |
| <4>LAN/WLAN |

Top menu for QM/QQ/CN model

| English |
|---|
| <1>RESET |
| <2>PARAMETER SET |
| <3>ADJUST SET |
| <4>LAN/WLAN |
| <5>BASIC |
| <6>Z-MODE |
| <7>AUTO CALIB |
| <8>DUMP MODE |
| <9>LOG |

| | |
|---|---|
| <1>RESET | Same as 8.16 RESET of the system mode. |
| <2>PARAMETER SET | Same as 8.4 PARAMETER SET of the system mode |
| <3>ADJUST SET | Same as 8.5ADJUST SET of the system mode |
| <4>LAN/WLAN | Used to enable or disable the network device. The detailed settings for the network need to be done in the system mode. |
| <5>BASIC | Same as 8.10 BASIC of the system mode |
| <6>Z-MODE | Same as 8.14 Z-MODE of the system mode |
| <7>AUTO CALIB | Used to enable or disable the auto calibration function. |
| <8>DUMP MODE | Used to print or save the data sent from the host in USB memory. |
| <9>LOG | Used to save print logs in USB memory |

## 9.2 RESET

Same as 8.16 RESET of the system mode.

Contents of RESET menu

| MENU  ITEM | Display pattern and key operation |
|---|---|
| USER  SYSTEM  MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     <1>RESET | |

## 9.3  PARAMETER  SET

Same as 8.4    PARAMETER SET of the system mode.

Contents of PARAMETER SET menu

| MENU  ITEM | Display  pattern  and  key  operation |
|---|---|
| USER  SYSTEM  MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     <2>PARAMETER  SET | |
|        PRINTER  SET | |
|        SOFTWARE  SET | |
|        PANEL | |
|        PASSWORD | |

## 9.4  ADJUST  SET

Same as 8.5    ADJUST SET of the system mode.

Contents of ADJUST SET menu

| MENU  ITEM | Display  pattern  and  key  operation |
|---|---|
| USER  SYSTEM  MODE | 7.1 LIST  BOX  WITH  SCROLLBAR |
|     <3>ADJUST  SET | |
|        FEED  ADJ. | 7.2 VALUE  SETTING  DISPLAY |
|        CUT  ADJ. | |
|        BACK  ADJ. | |
|        X  ADJUST | |
|        TONE  ADJ.  (TRANS.) | |
|        TONE  ADJ.  (DIRECT) | |
|        RBN  ADJ.<FW> | |
|        RBN  ADJ.<BK> | |
|        THRESHOLD  <REFL.> | |
|        THRESHOLD  <TRANS.> | |

# 9.5  LAN/WLAN

Contents of LAN/WLAN menu

| MENU  ITEM | | | Display  pattern  and  key  operation |
|---|---|---|---|
| USER  SYSTEM  MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <4>LAN/WLAN | | |
| | | LAN/WLAN | |
| | | SNMP | |

## 9.5.1  LAN/WLAN

・OFF

・ON (AUTO)

・ON (LAN)

・ON (WLAN)

## 9.5.2  SNMP

・OFF

・ON

## 9.6  BASIC

Same as 8.10 BASICof the system mode.

Contents of BASIC menu

| MENU  ITEM | | | Display  pattern  and  key  operation |
|---|---|---|---|
| USER  SYSTEM  MODE | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <5>BASIC | | |
| | | BASIC | |
| | | FILE  MAINTENANCE | 7.3  INFORMATION  DISPLAY |
| | | TRACE | 7.1  LIST  BOX  WITH  SCROLLBAR |
| | | EXPAND  MODE | |

## 9.7  Z-MODE

Same as 8.14 Z-MODE of the system mode.

Contents of Z-MODE menu

| MENU  ITEM | | Display  pattern  and  key  operation |
|---|---|---|
| USER  SYSTEM  MODE | | 7.1 LIST BOX WITH SCROLLBAR |
| | <6>Z-MODE | |

This menu is displayed only when the destination is other than JA.

## 9.8 AUTO CALIB

Contents of AUTO CALIB menu

| MENU ITEM | Display pattern and key operation |
|---|---|
| USER SYSTEM MODE | 7.1 LIST BOX WITH SCROLLBAR |
|       &lt;7&gt;AUTO CALIB | |

AUTO CALIB
- ・ OFF
- ・ ON TRANS.
- ・ ON REFLECT
- ・ ON ALL
- ・ ON TRANS.+Bfeed

    NOTE: Since the head-up function is not provided to the B-EX4T2, B-EX6T2, and B-EX4D2, the setting and the printer behavior will be automatically changed to "ON TRANS." even if "ON TRANS.+Bfeed" is selected for these models.

- ・ ON REFLECT+Bfeed

    NOTE: Since the head-up function is not provided to the B-EX4T2, B-EX6T2, and B-EX4D2, the setting and the printer behavior will be automatically changed to "ON REFLECT" even if "ON REFLECT+Bfeed" is selected for these models.

- ・ ON ALL+Bfeed

    NOTE: Since the head-up function is not provided to the B-EX4T2, B-EX6T2, and B-EX4D2, the setting and the printer behavior will be automatically changed to "ON ALL" even if "ON ALL+Bfeed" is selected for these models.

Explanation of printer behavior

1. When AUTO CALIB is enabled, an automatic calibration starts at an open/close of the print head and at a power on time.

2. When the automatic calibration is enabled, the media length, effective print length, sensor type and whether the ribbon is used or not are set, as follows.

Printer behavior after automatic calibration is performed

| | | QM/CN model | QQ model |
|---|---|---|---|
| Whether the ribbon is used or not | | After the automatic calibration is performed, the values obtained through the calibration will take effect until next calibration is performed or the printer power is turned off. (Settings specified by commands are ignored.) | Since this model is not provided with the ribbon mechanism, "No ribbon" is always selected. |
| Sensor type | | After the automatic calibration is performed, the values obtained through the calibration will take effect after the calibration is completed. Afterward, the sensor specified by a command is ignored. | |
| Media | Media pitch | After the automatic calibration is performed, the values obtained through the calibration will take effect until next calibration is performed or the printer power is turned off. (Settings specified by commands are ignored.) | |
| | Effective print length | | |
| | Gap length | | |

3. When the auto calibration with reflective sensor is selected, the lowest voltage detected by the black mark sensor is considered as a black mark level. And, the sum of this voltage and the threshold fine adjustment value will be adopted as a threshold.

4. When the auto calibration with transmissive sensor is selected, the highest voltage detected by the feed gap sensor is considered as a gap level.   After subtracting the threshold fine adjustment value from this voltage, the result will be adopted as a threshold.

5. When "ON ALL" is selected, the highest voltage detected by transmissive sensor or the lowest voltage detected by the refrective sensor is considered as a gap/black mark level.   After subtracting the threshold fine adjustment value for each sensor from this voltage, the result will be adopted as a threshold.

6. The printer feeds about 160 mm long media to detect a black mark/gap and determine the threshold.   When the printer detects more than one black marks/gaps during this 160-mm media feed, the printer measures the media pitch and stops the automatic calibration 1 mm short of the bottom of a black mark or gap.

7. If the second black mark/gap is not found under the above conditions, the printer continues media feed for up to 500.0 mm until the second black mark/gap is found.   If it still cannot be detected, the printer will stop, resulting in a paper jam.

8. This function is available only when the media pitch is 10.0 mm to 150.0 mm.

9. When the cutter is installed and a previous issue was performed in cut issue mode, the media is cut and ejected after an automatic calibration completes.

10. When the automatic calibration is in operation, labels do not stop at a strip position even in strip or special strip mode.

11. When a label end occurs during an automatic calibration, the printer stops, resulting in an error.   Closing the print head can clear the error and resume the automatic calibration.

12. During an automatic calibration, the ribbon motors are rotated.   Even if the ribbon is not loaded, this function does not result in an error. However, the print condition will be automatically changed to "No ribbon" after the calibration ends.

13. When "+ Bfeed" is selected, the printer feeds the media backward for the media pitch length while lifting the print head if the specified conditions are satisfied.

| | |
|---|---|
| Hardware | Optional ribbon saving module (solenoid) is installed. |
| Parameter setting | RBN SAVE parameter is set to TAG or LABEL |
| Operating condition | Media pitch falls between 20mm and 100mm. The previous issue mode was Batch without cut. (The issue mode and the cut interval are not reset by power off or a printer reset.) |
| Caution | Even if the hardware requirement is not satisfied (the optional ribbon saving module is not installed), the printer feeds the media backward when the other requirements are satisfied.   However, this operation is not guaranteed as it is outside of the specification. |

14. The feed speed during the automatic calibration is 3 ips.

15. The print head must not be opened during automatic calibration as the subsequent printer operation is not guaranteed. If the print head is opened, turn off the power and back to on.

## 9.9 DUMP MODE

Contents of DUMP MODE menu

| MENU ITEM | | | | Display pattern and key operation |
|---|---|---|---|---|
| USER SYSTEM MODE | | | | 7.1 LIST BOX WITH SCROLLBAR |
| | <8>DUMP MODE | | | |
| | | BUFFER | | |
| | | DUMP LIST | | |
| | | | USB MEMORY | 7.3 INFORMATION DISPLAY |
| | | | PRINT | |

### 9.9.1 BUFFER

- ・ RS-232C           RS-232C receive buffer
- ・ CENTRO.          Centronics receive buffer
- ・ LAN               Network I/F receive buffer
- ・ BASIC1           BASIC Interpreter: I/F $\rightarrow$ Interpreter buffer
- ・ BASIC2           BASIC Interpreter: Interpreter $\rightarrow$ I/F buffer
- ・ USB              USB receive buffer
- ・ RFID             RFID receive buffer

### 9.9.2 DUMP LIST

Output destination is selected.

#### 9.9.2.1 USB MEMORY
Data in the receive buffer is saved in USB memory.

When the data is saved in USB memory, a file is automatically created in the USB memory and named in the following format based on the printer model and saved date

.
/ATA0/DUMP/ B-EX4T1_DUMP_1007291030.BIN
(B-EX4T Type 1 mode 2010-Jul-29 10:30)
If a file with the same name already exists in the USB memory, it will be overwritten.

In the case of the RS-232C and Centronics, a 0 KB file is output if the optional board is not installed.

When an error occurs during an access to the USB memory, the same message described in Section 8.15 USB MEMORYdisplayed.

The printer does not retry the operation after displaying the message.

### 9.9.2.2 PRINT

- ・ ON DEMAND    Prints 166 lines of data (approx. 50 cm), then stops displaying "Printing…".
  Pressing the [CANCEL] key causes the printing to stop and the display to return to the upper hierarchy menu.
  Pressing the [ENTER] (or any other key than [CANCEL]) restarts printing.
- ・ ALL          Prints all data in the receive buffer page by page.

```
                    ⋮
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00    ...............
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00    ...............
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00    ...............
00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00    ...............
7B 41 58 3B 2B 30 30 30 2C 2B 30 30 30 2C 2B 30    {AX;+000,+000,+0
30 7C 7D 7B 44 30 37 37 30 2C 31 31 30 30 2C 30    0|}{D0760,1100,0
37 34 30 7C 7D 7B 43 7C 7D 7B 4C 43 3B 30 30 33    740|}{C|}{LC;003
30 2C 30 30 32 30 2C 30 30 33 30 2C 30 36 36 30    0,0020,0030,0660
2C 30 2C 32 7C 7D 7B 4C 43 3B 30 30 37 30 2C 30    ,0,2|}{LC;0070,0
30 32 30 2C 30 30 37 30 2C 30 36 36 30 2C 30 2C    020,0070,0660,0,
39 7C 7D 7B 4C 43 3B 30 30 35 30 2C 30 30 32 30    9|}{LC;0050,0020
                    ⋮

44 45 46 47 48 49 4A 7C 7D 7B 50 43 31 30 3B 30    DEFGHIJ|}{PC10;0
33 35 30 2C 30 34 30 30 2C 31 2C 31 2C 4B 2C 30    350,0400,1,1,K,0
30 2C 42 3D 41 42 43 44 65 66 67 68 69 6A 6B 6C    0,B=ABCDefghijkl

6D 6E 6F 70 7C 7D 7B 50 56 30 32 3B 30 33 33 30    mnop|}{PV02;0330
2C 30 36 36 30 2C 30 32 37 30 2C 30 32 35 30 2C    ,0660,0270,0250,
41 2C 30 30 2C 42 3D 42 7C 7D 7B 50 56 30 33 3B    A,00,B=B|}{PV03;
                    ⋮

3B 30 39 30 30 2C 30 31 38 30 2C 54 2C 48 2C 30    ;0900,0180,T,H,0
35 2C 41 2C 30 3D 31 32 33 34 35 36 37 38 39 30    5,A,0=1234567890
41 42 43 44 45 7C 7D 00 00 00 00 00 00 00 00 00    ABCDE|}.........
```

Print direction ↓

Print conditions

| Print width | Approximately 100mm |
|---|---|
| Sensor | None |
| Print speed | (203 dpi) B-EX4T1-G, B-EX4T2-G, B-EX6T2-G, B-EX4D2-G: 6 ips (300 dpi/305 dpi) B-EX4T1-T, B-EX4T2-T, B-EX6T2-T: 5 ips (600 dpi) B-EX4T2-H: 3 ips |
| Print mode | Current setting |

NOTE:  For the B-EX4D2, the print mode is always set to the direct thermal.

16-byte data is printed on one line.

Data is printed, starting from the newest data to the older data.

Data pointed by the receive buffer write pointer is printed in bold type.

Size of receive buffer

|  | B-EX4T1, B-EX4T2, B-EX4D2, B-EX6T2 (except Japan model) | B-EX6T2 (Japan model only) |
|---|---|---|
| RS-232C: | 1 MB (Max. 65536 lines) | 6 MB (Max. 393216 lines) |
| Centronics: | 1 MB (Max. 65536 lines) | 6 MB (Max. 393216 lines) |
| Network I/F: | 1 MB (Max. 65536 lines) | 6 MB (Max. 393216 lines) |
| BASIC1: | 8 KB (Max. 512 lines) | 8 KB (Max. 512 lines) |
| BASIC2: | 8 KB (Max. 512 lines) | 8 KB (Max. 512 lines) |
| USB: | 1 MB (Max. 65536 lines) | 6 MB (Max. 393216 lines) |
| RFID | 8 KB (Max. 512 lines) | 8 KB (Max. 512 lines) |

To print all of the receive buffer data, the label with the length below is required.

|  | B-EX4T1, B-EX4T2, B-EX4D2, B-EX6T2 (except Japan model) | B-EX6T2 (Japan model only) |
|---|---|---|
| RS-232C: | 198.2 m (Other than 600 dpi) 198.6 m (600 dpi) | 1189.2 m |
| Centronics: | 198.2 m (Other than 600 dpi) 198.6 m (600 dpi) | 1189.2 m |
| Network I/F: | 198.2 m (Other than 600 dpi) 198.6 m (600 dpi) | 1189.2 m |
| BASIC1: | 2 m | 2 m |
| BASIC2: | 2 m | 2 m |
| USB: | 198.2 m (Other than 600 dpi) 198.6 m (600 dpi) | 1189.2 m |
| RFID | 2 m | 2 m |

If an error occurs when printing the receive buffer dump, the printer displays an error message, and stops. The error is cleared by pressing the [PAUSE] key, and the display is returned to the PRINT menu.   Pressing the [MODE] key causes the display to return to the User System Mode top menu.

After the error is cleared, data is not automatically reprinted

## 9.10 LOG

Contents of LOG menu

| MENU ITEM | Display pattern and key operation |
|---|---|
| USER SYSTEM MODE | 7.1 LIST BOX WITH SCROLLBAR |
|     &lt;9&gt;LOG | |
|         PRINTER TO USB | |

### 9.10.1 PRINTER TO USB

Print logs are saved in USB memory.

When the print logs are saved in the USB memory, a file is automatically created in the USB memory and named in the following formatted based on the printer model and saved data.

/ATA0/LOG/B-EX4T1_LOG_1007291030.TXT
(B-EX4T Type 1 mode 2010-Jul-29 10:30)
If a file with the same name already exists in the USB memory, it will be overwritten.

When an error occurs during an access to the USB memory, the same message described in 8.15 USB MEMORY is displayed.
The printer does not retry the operation after displaying the message.

When a generated log file is opened on a PC, the print logs are shown in the following example.



NOTES:
1. Since "LF" is used as the line feed code in generated log files, lines may not be properly changed depending on the text editor used.
2. Generated log files are saved as text files.

<u>Print log format</u>

The following tables show the format of a print log.

<CASE 1>
YYMMDDhhmmssAABCCCC

| Log | Description |
| --- | --- |
| YY | Year (00 to 99) |
| MM | Month (01 to 12) |
| DD | Day (01 to 31) |
| hh | Hour (00 to 24) |
| mm | Minute (00 to 59) |
| ss | Second (00 to 59) |
| AA | Detailed status<br>For details, refer to Section 8 Status Response in the B-EX Series External Equipment Interface Specification. |
| B | Status type (Fixed to 2: Automatic status transmission) |
| CCCC | Remaining labels to print (0000 to 9999) |

<CASE 2> When the B-EX Setting Tool is used
YYMMDDhhmmssZZZ …ZZZ

| Log | Description |
| --- | --- |
| YY | Year (00 to 99) |
| MM | Month (01 to 12) |
| DD | Day (01 to 31) |
| hh | Hour (00 to 24) |
| mm | Minute (00 to 59) |
| ss | Second (00 to 59) |
| ZZZ … ZZZ | Log message<br>  Capital letter (115 digits)<br><br>Message list (2 types)<br>  SETTING MODE ON<br>  SETTING MODE OFF<br><br>Description of message<br>SETTING MODE ON (When the printer shifts to the parameter setting mode)<br>・ The printer shifts to the parameter setting mode when the printer information is obtained with the parameter setting menu of the setting tool.<br>・ The printer shifts to the parameter setting mode when the printer information is obtained with the maintenance menu of the setting tool.<br><br>SETTING MODE OFF (When the printer exits from the parameter setting mode)<br>・ After the printer information is obtained with the parameter setting menu, the printer is restored to online mode and the printer exists from the parameter setting mode.<br>・ After the printer information is obtained with the maintenance menu, the printer exits from the parameter setting mode. |

NOTE:

In the case the printer information, which was obtained with the parameter setting menu of the B-EX Setting Tool, is updated, a reboot of the printer will be prompted when the printer is restored to online mode.　As the print log is cleared when the printer is rebooted, the parameter settings should not be updated before saving the print log.　For details, refer to the B-EX Setting Tool Operation Manual.

<CASE 3> B-EX4T1 Japan model with firmware V1.0I only
YYMMDDhhmmssPR,AAAAAAAA,BBBBBBBB,CCCC,DDDD,EEEE,FF,GGGGGG,HHHHHHHH,II,JJ,KKK
…KKK,LLL…LLL,MMMMMMMM,NNNN,OOOO,PPPP

| Log | Description |
| --- | --- |
| YY | Year (00 to 99) |
| MM | Month (01 to 12) |
| DD | Day (01 to 31) |
| hh | Hour (00 to 24) |
| mm | Minute (00 to 59) |
| ss | Second (00 to 59) |
| PR | Define character (fixed to "PR") |
| AAAAAAAA | Ambient temperature |
| BBBBBBBB | Print tone fine adjustment value |
| CCCC | Print tone fine adjustment value (thermal transfer) |
| DDDD | Print tone fine adjustment value (direct thermal) |
| EEEE | Power voltage |
| FF | Head voltage rank |
| GGGGGGGG | Print head temperature |
| HHHHHHHH | Print ratio |
| II | Supply type (thermal transfer) |
| JJ | Supply type (direct thermal) |
| KKK … KKK | Energizing time (4-digit data x 9, which are comma-separated) |
| LLL … LLL | Contribution ratio (2-digit data x 16, which are comma separated) |
| MMMMMMMM | Chopping section |
| NNNN | Chopping negation time |
| OOOO | Chopping cycle |
| PPPP | Power supply pattern |

<CASE 4>
ZZZ …ZZZ (Those not applicable to the above-mentioned CASES 1 to 3)

| Log | Description |
| --- | --- |
| ZZZ … ZZZ | Print log output from the OS. The contents vary case by case. |

<u>Print Log Size</u>
Print logs are stored in two files in the RAM, and they are unified into one when saved in a USB memory. The maximum log size of each file in the RAM is 10KB.   If the log size exceeds 10KB, the oldest file will be erased to create a new file.   So, the maximum size of log files that can be saved in a USB memory is 20KB.

NOTE:  For the B-EX4T1 JP model with firmware V1.0I, the size of log file that can be stored in the RAM is up to 100KB, and in a USB memory is up to 200KB, respectively.


<u>Timing for Resetting Print Log</u>

- When the printer is reset by executing the reset menu in the user system mode or by sending a Reset Command (excluding the Reset Command {WR|})

- When the printer power is turned off and back to on
  Errors which are not restorable with a depression of the [RESTART] key can be cleared only by turning the printer off and on.   Therefore, the log of such errors cannot be saved in a USB memory.
  Refer to Section 6.8 LCD Messages and LED Indications for non-restorable errors.


<u>Timing for Saving Print Log in USB Memory</u>

- After executing PRINTER TO USB menu, the print log is saved in a USB memory.
  The information to be saved only includes the statuses automatically transmitted (excluding the non-restorable error statuses) and shift to/exit from the parameter setting mode.
  For details of the automatic status transmission, refer to Section 8 Status Response in the B-EX Series External Equipment Interface Specification.

Example of print log saved in a file

| | |
|---|---|
| 120313155139SETTING MODE ON | (Shift to the parameter setting mode) |
| 120313155143SETTING MODE OFF | (Exit from the parameter setting mode) |
| 1203131552101320005 | (Paper end with 5 labels unprinted) |
| 1203131552304120005 | (Reprint: Initial feed was performed.) |
| 1203131552334020000 | (Printing normally ended.) |

The above print log indicates the following printer actions occurred:
  The printer ran out of the labels when 5 out of 10 labels had been printed.   Then, a new label stock was loaded, the [RESTART] key was pressed, and printing was restarted.

# 10. DOWNLOAD

```
┌─────────────┐
│  Power  OFF │                    (1) Power off state
└─────────────┘
      [FEED]
        +
      [RESTART]                     (2) Turn the power on while holding down the [FEED], [RESTART]
        +                          and [PAUSE] keys at the same time.
      [PAUSE]
```

```
DOWNLOAD MODE
 Waiting for data...
   □□□□□
```
(3) Download mode display

```
Start of download
```
(4) Send a download command.

```
DOWNLOAD MODE
 Receiving...
   □□□□□
```
(5) The printer is receiving the data.

```
DOWNLOAD MODE
 Receiving...
   ■■■■□
```
(6) The printer is receiving the data

```
DOWNLOAD MODE
 Data Checking...
   ■□□□□
```
(7) Data is being checked.

```
DOWNLOAD MODE
 Data Checking...
   ■■□□□
```
(8) Data is being checked.

```
DOWNLOAD MODE
 Erasing...
   ■■■□□
 Please do not
  turn off a power.
```
(9) The flash ROM is being erased.

```
DOWNLOAD MODE
 Programming...
   ■■■■□
 Please do not
  turn off a power.
```
(10) Downloaded data is being written.

```
DOWNLOAD MODE
 Completed!
   ■■■■■
 Finish!
```
(11) Downloading is completed.

```
B-EX4T1-T      V1.0A
      ONLINE
PRINTED        000000
IP:192.168.010.020
▊◺◺▨▦▟
```
(12) After downloading is completed, the printer will be automatically rebooted, and placed in the online state.

NOTE: DOWNLOAD MODE2 is unused. There is no difference in downloading procedure from DOWNLOAD MODE.

When an error occurs while downloading in the download mode, the following error message is displayed.

Error message

| Error message | Description |
|---|---|
| DOWNLOAD MODE<br>Syntax Error<br><br>Please retry after<br>checking the data | Communication error (Command error) |
| DOWNLOAD MODE<br>Check SUM Error<br><br>Please retry after<br>checking the data | The checksum of the boot program does not end with "00". |
| DOWNLOAD MODE<br>PCB ID Conflict<br><br>Please retry after<br>checking the data | Downloading the boot program for wrong PCB was attempted. |
| DOWNLOAD MODE<br>Model Type Conflict<br><br>Please retry after<br>checking the data | Downloading the boot program for wrong printer model was attempted. |
| DOWNLOAD MODE<br>Data Size Over<br><br>Please retry after<br>checking the data | The data size is too large. |
| DOWNLOAD MODE<br>fail!<br>Format Error<br>Call a service<br>person. | Format error |
| DOWNLOAD MODE<br>fail!<br>Write Error<br>Call a service<br>person. | Write error |

NOTES:
1. When an error occurs, the printer stops and never recovers unless the power is turned off and on.
2. After a write error occurs, turning the printer off and back to on causes "DOWNLOAD MODE" to be displayed and the printer to enter the download mode. The program needs to be downloaded again.
3. While "DOWNLOAD MODE" is displayed, the expansion I/O output status becomes indefinite.
4. When there is a difference in the model name between the boot program and the actual printer, "MODEL TYPE ERROR" is displayed and the printer stops with error.
5. When the checksum for the boot program does not end with "00H", "CHECKSUM ERROR" is displayed and the printer stops with error.
6. After receiving the all data of the boot program, the printer compares it with the currently installed boot program, and erases the flash memory for writing data if there is a difference.
   When there is no difference, the downloading normally ends without erasing the memory or writing data.
7. The LCD may show the message "Initializing…" when the printer is turned off in the download mode. This does not affect the printer operation.
8. Holding down the [FEED]+[RESTART]+[PAUSE] keys at the timing of printer reset, initiated by executing the reset function in the system mode or user system mode, causes the forced download mode display to appear on the LCD. This menu is not executable. The printer must be turned off and back to on while the [FEED]+[RESTART]+[PAUSE] keys are held down.

# 11 Auto Configuration Mode

## 11.1 Outline of the Auto Configuration Mode

Turning on the printer while holding down the [CANCEL] key causes the printer to enter auto configuration mode .

The auto configuration mode allows for automatically downloading the master firmware and restarting the printer.   To enter the auto configuration mode, an optional RTCUSB host, a USB memory, and proper CFG file must be prepared.   Failure to do this disables the printer to enter the auto configuration mode. Instead, the printer will start in the online mode.

| | |
|---|---|
| Power OFF | (1) Power off state |
| [CANCEL] | (2) Turn on the printer while holding down the [CANCEL] key. |
| USB TO PRINTER<br>B-EX4T1-T C1.0A | (3) Auto configuration mode display |
| [PAUSE]/[MODE]/<br>[CANCEL]/[ENTER] | (4) Press the [PAUSE], [MODE], [CANCEL] or [ENTER] key to show the next display. |
| USB TO PRINTER<br>CANCEL<br>OK | (5) Confirmation display |
| [ENTER] | (6) Select "OK" and press the [ENTER] key.<br>* When "CANCEL" is selected, the printer returns to the online state without downloading the firmware. |
| PRINTER TO USB<br><br>WRITING... | (7) The firmware is being downloaded. |
| B-EX4T1-T      C1.0A<br>ONLINE<br>PRINTED      000000 | (8) After downloading is completed, the printer will be placed in the online state |

## 11.2 Preparation for USB Memory

To execute the auto configuration mode, the firmware file (*.bin) to be downloaded and the dedicated CFG file need to be created in the USB memory in advance.   To enter the auto configuration mode, the RTCUSB host, USB memory, correct CFG file need to be all prepared.   Lack of any one of these disables shifting to the auto configuration mode, but causes the printer to start in the online mode.

Each file is saved in the SYSTEM directory created in the root directory for the USB memory.

Example:  When BOOT/MAIN/CG are downloaded:

/ATA0/SYSTEM/B-EX-BOOT-Vx.x-xx.bin
/ATA0/SYSTEM/B-EX-MAIN-Vx.x-xx.bin
/ATA0/SYSTEM/B-EX-CG-Vx.x-xx.bin
/ATA0/SYSTEM/AUTOCONFIG.CFG

## 11.3 Auto Configuration File

To execute the auto configuration mode, it is required to create the auto configuration file, which is an exclusive CFG file, in the USB memory in advance.

The auto configuration file is stored under the following path under the name of "AUTO CONFIG.CFG".

/ATA0/SYSTEM/AUTOCONFIG.CFG

### 11.3.1 Format

Auto configuration file has the following formats.

| B-EX4T1-G,0020 | Model information |
|---|---|
| B-EX4T1-T C1.0A | Display message |
| /ATA0/SYSTEM/B-EX-BOOT-Vx.x-xx.bin | Firmware file to be downloaded |
| /ATA0/SYSTEM/B-EX-MAIN-Vx.x-xx.bin | Firmware file to be downloaded |
| /ATA0/SYSTEM/B-EX-CG-Vx.x-xx.bin | Firmware file to be downloaded |

### 11.3.2 Model Information

Applicable model's information is stored.

The information is comma separated. The first half is the model name (the above example indicates B-EX4T Type 1 203-dpi model) and the last half is the PC board information.

If the actual printer and this model information do not match, the auto configuration mode will not start.

Description of the model information:

B-EX4T1-T,0020

PC board information
0020: PC board for QM/CN/QQ model
0021: PC board for JP model

Resolution
G: 203 dpi
T: 300/305 dpi
H: 600 dpi

Model
B-EX4T1: B-EX4T1-G/T
B-EX4T2: B-EX4T2-G/T
B-EX4T2H: B-EX4T2-H
B-EX6T2: B-EX6T2-G/T
B-EX4D2: B-EX4D2-G

### 11.3.3 Display Message

A message displayed on the LCD while the printer is in the auto configuration mode.

Word-wrap feature is enabled.

Only characters that can be expressed with ASCII are allowed to be input.

### 11.3.4 Firmware File to be Downloaded

Name of the file to be downloaded.

# 12 Power Save Function

**Printer status allowing shift to the power save mode**

When the following status continues for a specified length of time, the printer will enter the power save mode.

- ONLINE (Idle, communicating)
- Pause
- Error
- Waiting for removal of a label from the media outlet
- System mode (except for the menus that use 27V line, such as self-diagnosis, test print and sensor adjustment.)
- User system mode (except for the menus that use 27V line, such as dumping.)
- Pause of the expansion I/O

**Display and key operations during the power save mode**

When the printer enters the power save mode, it shows "POWER SAVING MODE" on the LCD and turns off the LCD backlight. However, the following operations enable the printer to display usual messages and turn on the LCD backlight even in the power save mode. If the printer status remains unchanged for 30 seconds, "POWER SAVING MODE" is displayed and the LCD backlight turns off again.

**Conditions for allowing usual messages to be displayed in the power save mode**

When the following occurs in the power save mode, the LCD wakes up.

- A key is pressed in (Except for [RESTART] or [FEED] key which causes printing or paper feed)
- The head lever is unlocked or locked in the power save mode (this is because there is a message indicating the head lever unlock.)
- There is a change in the pause signal line or active signal line of the expansion I/O (This is because there is a message indicating a pause state.)

**Message in the power save mode**

The supported language differs depending on the printer status before the printer enters the power save mode.

| Multi-language | Online mode (except for manual threshold setting) |
|---|---|
| Japanese/English | System mode, User system mode and manual threshold setting in online mode |

**Power save mode display**

When the printer is placed in the power save mode by above-mentioned printer status allowing shift to the power save mode, "POWER SAVING MODE" is displayed.

| Display |
|---|
| POWER SAVING MODE |

**Conditions for displaying "POWER SAVING MODE" again**

When the power save mode is continued and there is no printer status change, such as head lock lever lock/unlock, for 30 seconds, "POWER SAVING MODE" is displayed on the LCD.

When data is saving in the storage area, "POWER SAVING MODE" is displayed in 30 seconds after the completion of the data save on the condition no printer operation is done.

**Conditions for exiting the power save mode**

The power save mode is terminated when:

- Printing is performed.
- Printing is caused by a depression of the [RESTART] key
- Paper feed/re-print is caused by a depression of the [FEED] key
- Printing or paper feed is initiated through the expansion I/O, or printing is caused by a release of the printer from the pause state instructed through the expansion I/O
- The printer receives U1/U2 command.
- The printer receives T command.
- The printer receives XS command.
- The printer receives IB command.
- The printer receives RFID-related command accompanied by printer action
- Automatic calibration is performed with the head lever locked.
- Up and down of the solenoid is tested during the Factory Adjust menu in the system mode
- Sensor adjustment is performed in the system mode.